

Subsystem DSS	1
Subsystem INS	52
Subsystem CLS	66
Subsystem DMS	85
Subsystem IOS	101
Subsystem PLS	145
Subsystem DPS	177
Subsystem CSS	248
Subsystem MSS	271

Appendix A. Software Processes

This appendix lists all ECS processes in alphabetical order by subsystem. Each process name is followed by a directory specification indicating where that process was defined. A brief description of the process may be given. This is followed by a list of classes and templates used by the process, if any, which are defined in that same directory. Finally, any Static and Shared Libraries linked into this process (other than system and COTS libraries) are also listed. These library names may be found in Appendix B.

A list of shell scripts follows the list of processes in each subsystem.

It should be noted that this appendix contains processes that are in the Drop 5B code as well as processes which are in later Drops but may not be fully operative until the delivery of the future Drops.

The first sentence of a class or library description is taken from the comments, if any, in the code for that class or library.

Subsystem DSS

The Data Server Subsystem (DSS) provides capabilities to store, search, retrieve, and distribute earth science and related data. The DSS provides data repositories and management capabilities necessary to safely store data on a permanent basis. The DSS stages data needed for data processing by the Data Processing Subsystem (DPS). The DSS organizes and stores its data by data types, and provides advanced search capabilities and processing services on those data types in support of earth science users. The DSS distributes data to users either electronically or on physical media. It also provides administrative capabilities necessary to operate and manage its hardware and software.

***process* convertEvent**

/ecs/formal/DSS/sdsrv/src/de1

Libraries Linked

- Common -- This library contains classes for the EcsToV0Server and V0ToEcsServer executables.
- DmAsGwCommon -- The DmAsGwCommon library contains utility classes and term definitions used by the Aster Gateway.
- DmDdMsg -- This library defines messages to be passed to the Data Dictionary.
- DmGwV0Util -- The DmGwV0Util library contains the implementation of functions used by the ECS to V0 Gateway for client/server interfaces.
- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.

- EcDcMsgPsng1 -- This library consists of message passing objects used by both the client and server side.
- EcDmDdClient -- The library establishes and maintains a session with the DDICT server.
- EcSbCl -- This library contains all the classes for Subscription Server client.
- EcSbMsg -- This library contains all message classes used for the communication between Subscription Server and its client objects provided by Subscription Server client library.
- MsAcClnt -- The Accountability Management Service makes the user profile available to the various subsystems, such as the Data Server subsystem, information such as the user's electronic mail address and the shipping address, which are used for the distribution of
- MsAcComm -- This library contains class used for both Accountability Server and Client
- srf -- The SRF library provides the necessary mechanism for the application to communicate asynchronously with another application.

Shared Libraries Linked

- agenteventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsEmMailRelASh -- This Library is used for the emails using sendmail utility and the nnpst for Bulletin board messages.
- CsFtFTPRelASh -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObjSh -- This library provides functions to use FTP at a scheduled time by the User.
- CsSeCryptoDesSh -- This library contains the APIs for the DES encryption algorithm.
- DsAdSh -- This library provides an administrative/M&O interface to science data server requests.
- DsBtSh -- This library implements a thread which notifies the subscription server of events.
- DsClSh -- This library contains classes which make up the Science Data Server's (SDSRV) public interface. These classes are used by clients to connect, build commands, and submit requests to the SDSRV.
- DsCnSh -- This library was used to generate files which install ESDT configuration information for each ESDT previously.
- DsCsSh -- This library is used by the HDFEOS server which supplies subsetting services to DLL or other clients.
- DsDbSh -- This library encapsulates the Sybase Open Client calls from the rest of the SDSRV.
- DsDcSh -- This library is used by subsetting code which make reformatting calls to convert HDF-EOS file format to HDF file format for subsetted HDF files.
- DsDdBSh -- This library contains base objects used in both the client and server components of DDIST.

- DsDdCSh -- This is the client side library.
- DsDdIsh
- DsDe1Sh -- This internal library contains the method to do validation, installing ESDT, sending metadata to IOS,DMS and SBSRV and generate MCF to ingest.
- DsDe2Sh -- This internal library contains the method to do validation, installing ESDT, sending metadata to IOS,DMS and SBSRV and generate MCF to ingest.
- DsGeSh -- This library provides the public interface for access to all ESDT services and ESDT specifications.
- DsHcSh -- This library provides a DCE-independent client interfaces for both Conformant and NonConformant subsetting.
- DsHrSh -- This library encapsulates all DCE exposure for the distributed objects and functions for both Conformant and NonConformant subsetting on the server side for HdfEos server.
- DsMd1Sh -- This library defines metadata classes used to access a database.
- DsMd2Sh -- This library defines metadata classes used to access a database.
- DsMd3Sh -- This library defines metadata classes used to access a database.
- DsShSh -- This internal library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- DsSiSh
- DsSrSh -- This is an internal library for Science Data Server.
- DsStCmnShSh
- DsStCopyDSh
- DsStDaemonSh
- DsStFtpSh
- DsStPrinterShSh
- DsStResShSh
- DsStStSh -- Both client and server code are contained in this library.
- EcCfSh -- The Config library (CF) is a shared library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistrySh
- EcDcMsgPng1Sh -- This library consists of message passing objects used by both the client and server side.
- EcDnDirSh -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcFhSh -- This library provides fault handling capabilities to ECS applications.

- EcNsServiceLocatorSh -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcNsServiceLocSh -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcPfSh -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPoDbRWSH
- EcPoSh -- The Persistent CSC provides a set of abstract and base classes for approved advertisements and requests.
- EcPtSpecialLockSh -- This library provides classes for mutex operations and thread IDs.
- EcSeCmiSh -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeServerKeyMgmtSh -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbedSh -- This shared Library has only the methods for completing the successful compilation.
- EcSeUtilityCtStubbedSh -- This shared Library provides stubbed version of EcSeUtilityCt for successful compilation.
- EcTiTimeSh -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUrSh -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUtFactorySh -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtMiscSh -- The EcUtMisc library contains miscellaneous utilities.
- EcUtSh -- EcUt is a utility library for all the ECS applications.
- eventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- GlSh -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.
- IoAdCoreSh -- The CoreLib CSC provides a set of functionalities for describing a generic advertisement, parsing and validating attributes that support the ECS Core meta data model, and requesting and moderating advertisements.
- IoAdProxySh -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSearchSh -- The SearchLib CSC provides a set of searching capabilities for approved advertisements, for the administration of groups, and for moderation of requests.

- IoAdServerSh -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSubsSh -- The SubsLib CSC provides a set of derived classes which represent different types of advertisements: products, services, and providers.

process dbif

/ecs/formal/DSS/stmgt/src/cmn

Libraries Linked

- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- MsAcClnt -- The Accountability Management Service makes the user profile available to the various subsystems, such as the Data Server subsystem, information such as the user's electronic mail address and the shipping address, which are used for the distribution of
- MsAcComm -- This library contains class used for both Accountability Server and Client

Shared Libraries Linked

- agenteventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsFtFTPRelASh -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObjSh -- This library provides functions to use FTP at a scheduled time by the User.
- CsSeCryptoDesSh -- This library contains the APIs for the DES encryption algorithm.
- DsCnSh -- This library was used to generate files which install ESDT configuration information for each ESDT previously.
- DsShSh -- This internal library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- DsStCmnShSh
- DsStCopyDSh
- DsStDaemonSh
- DsStFtpSh
- DsStStSh -- Both client and server code are contained in this library.
- EcCfSh -- The Config library (CF) is a shared library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistrySh
- EcDcMsgPnglSh -- This library consists of message passing objects used by both the client and server side.

- EcDnDirSh -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcFhSh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLocatorSh -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcNsServiceLocSh -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcPfSh -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPoDbRWSH
- EcPtSpecialLockSh -- This library provides classes for mutex operations and thread IDs.
- EcSeCmiSh -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeServerKeyMgmtSh -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbedSh -- This shared Library has only the methods for completing the successful compilation.
- EcSeUtilityDbStubbedSh -- This shared Library provides stubbed version of EcSeUtilityDb for successful compilation.
- EcTiTimeSh -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUrSh -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUtFactorySh -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtMiscSh -- The EcUtMisc library contains miscellaneous utilities.
- EcUtSh -- EcUt is a utility library for all the ECS applications.
- eventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- GlSh -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.

process EcDsDdistGui

/ecs/formal/DSS/gui/src/ddist

This process enables operations to initiate, track, and manipulate distribution requests by using input GUI controls and database information.

Classes

- DsGuBusyCursor -- The constructor and destructor of this class are always called in pairs to set/reset the cursor to indicate that the application is busy and unable to process user input in a window.
- DsGuDdEvents -- Created by Builder Xcessory Version 5.0.3.
- DsGuDdistMW -- Created by Builder Xcessory Version 5.0.3.
- DsGuDistRequest -- Created by Builder Xcessory Version 5.0.3.
- DsGuDistTimer -- pointer to the DDist Object.
- DsGuErrorDialog -- Created by Builder Xcessory Version 5.0.3.
- DsGuFile -- Created by Builder Xcessory Version 5.0.3.
- DsGuOperatorMessage
- DsGuPreamble -- Created by Builder Xcessory Version 5.0.3.
- DsGuSysRequest -- Created by Builder Xcessory Version 5.0.3.
- DsGuSystemSettings -- Created by Builder Xcessory Version 5.0.3.
- DsGuTapeOperation -- Created by Builder Xcessory Version 5.0.3.
- DsGuTapeTimer -- Pointer to the Tape Ops Object.
- DsGuTimer -- Assignment operator for class; should not be used.

Libraries Linked

- Common -- This library contains classes for the EcsToV0Server and V0ToEcsServer executables.
- DmAsGwCommon -- The DmAsGwCommon library contains utility classes and term definitions used by the Aster Gateway.
- DmDdMsg -- This library defines messages to be passed to the Data Dictionary.
- DmGwV0Util -- The DmGwV0Util library contains the implementation of functions used by the ECS to V0 Gateway for client/server interfaces.
- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- EcDmDdClient -- The library establishes and maintains a session with the DDICT server.
- EcSbCl -- This library contains all the classes for Subscription Server client.
- EcSbMsg -- This library contains all message classes used for the communication between Subscription Server and its client objects provided by Subscription Server client library.
- EcUtGUIg_mt_eh_tp
- EcUtHelpg_mt_eh_tp

- MsAcClnt -- The Accountability Management Service makes the user profile available to the various subsystems, such as the Data Server subsystem, information such as the user's electronic mail address and the shipping address, which are used for the distribution of
- MsAcComm -- This library contains class used for both Accountability Server and Client
- srf -- The SRF library provides the necessary mechanism for the application to communicate asynchronously with another application.

Shared Libraries Linked

- agenteventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsFtFTPRelASh -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObjSh -- This library provides functions to use FTP at a scheduled time by the User.
- CsSeCryptoDesSh -- This library contains the APIs for the DES encryption algorithm.
- DsCnSh -- This library was used to generate files which install ESDT configuration information for each ESDT previously.
- DsDdBSh -- This library contains base objects used in both the client and server components of DDIST.
- DsDdCSh -- This is the client side library.
- DsDdISh
- DsShSh -- This internal library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- DsStCmnShSh
- DsStCopyDSh
- DsStDaemonSh
- DsStFtpSh
- DsStPrinterShSh
- DsStResShSh
- DsStStSh -- Both client and server code are contained in this library.
- EcCfSh -- The Config library (CF) is a shared library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistrySh
- EcDcMsgPng1Sh -- This library consists of message passing objects used by both the client and server side.
- EcDnDirSh -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.

- EcFhSh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLocatorSh -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcNsServiceLocSh -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcPfSh -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPoDbRWSH
- EcPoSh -- The Persistent CSC provides a set of abstract and base classes for approved advertisements and requests.
- EcPtSpecialLockSh -- This library provides classes for mutex operations and thread IDs.
- EcSeCmiSh -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeServerKeyMgmtSh -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbedSh -- This shared Library has only the methods for completing the successful compilation.
- EcSeUtilityDbStubbedSh -- This shared Library provides stubbed version of EcSeUtilityDb for successful compilation.
- EcTiTimeSh -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUrSh -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUtFactorySh -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtMiscSh -- The EcUtMisc library contains miscellaneous utilities.
- EcUtSh -- EcUt is a utility library for all the ECS applications.
- eventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- GlSh -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.
- IoAdCoreSh -- The CoreLib CSC provides a set of functionalities for describing a generic advertisement, parsing and validating attributes that support the ECS Core meta data model, and requesting and moderating advertisements.
- IoAdProxySh -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSearchSh -- The SearchLib CSC provides a set of searching capabilities for approved advertisements, for the administration of groups, and for moderation of requests.

- IoAdServerSh -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSubsSh -- The SubsLib CSC provides a set of derived classes which represent different types of advertisements: products, services, and providers.

process EcDsDistributionServer

/ecs/formal/DSS/distribution/src/server/main

This process provides the control and coordination for data distribution through request processing.

Libraries Linked

- DsCl -- This library contains classes which make up the Science Data Server's (SDSRV) public interface. These classes are used by clients to connect, build commands, and submit requests to the SDSRV.
- DsCn -- This library is used to access a server specific configuration file.
- DsGe -- This library provides the public interface for access to all ESDT services and ESDT specifications.
- DsSh -- This library provides underlying DCE(ODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- EcDcMsgPsng1 -- This library consists of message passing objects used by both the client and server side.
- EcPtSpecialLock -- This library provides classes for mutex operations and thread IDs.
- EcUt -- EcUt is a utility library for all the ECS applications.
- EcUtFactory -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtMisc -- This library contains miscellaneous utilities.
- Gl -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.
- MsAcClnt -- The Accountability Management Service makes the user profile available to the various subsystems, such as the Data Server subsystem, information such as the user's electronic mail address and the shipping address, which are used for the distribution of
- MsAcComm -- This library contains class used for both Accountability Server and Client

Shared Libraries Linked

- agenteventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.

- CsEmMailRelASh -- This Library is used for the emails using sendmail utility and the nnpost for Bulletin board messages.
- CsFtFTPRelASh -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObjSh -- This library provides functions to use FTP at a scheduled time by the User.
- CsSeCryptoDesSh -- This library contains the APIs for the DES encryption algorithm.
- DsDdBSh -- This library contains base objects used in both the client and server components of DDIST.
- DsDdISh
- DsDdSSh
- DsStCmnShSh
- DsStCopyDSh
- DsStDaemonSh
- DsStFtpSh
- DsStPrinterShSh
- DsStResShSh
- DsStStSh -- Both client and server code are contained in this library.
- EcCfSh -- The Config library (CF) is a shared library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistrySh
- EcDcMsgPng1Sh -- This library consists of message passing objects used by both the client and server side.
- EcDnDirSh -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcFhSh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLocatorSh -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcNsServiceLocSh -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcPfSh -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPoDbRWSH
- EcPtSpecialLockSh -- This library provides classes for mutex operations and thread IDs.
- EcSeCmiSh -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).

- EcSeServerKeyMgmtSh -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbedSh -- This shared Library has only the methods for completing the successful compilation.
- EcSeUtilityCtStubbedSh -- This shared Library provides stubbed version of EcSeUtilityCt for successful compilation.
- EcTiTimeSh -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUrSh -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUtFactorySh -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtSh -- EcUt is a utility library for all the ECS applications.
- eventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- GlSh -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.

process EcDsHdfEosServer

/ecs/formal/DSS/sdsrv/src/hr

The EcDsHdfEosServer provides the services for both Conformant and NonConformant subsetting. It utilizes the EcDsScienceDataServer as its client for all the subsetting requests. The distributed functions are single-thread called by EcDsScienceDataServer. It provides ability to start more than one server with each corresponding server config file.

Libraries Linked

- Common -- This library contains classes for the EcsToV0Server and V0ToEcsServer executables.
- DmAsGwCommon -- The DmAsGwCommon library contains utility classes and term definitions used by the Aster Gateway.
- DmDdMsg -- This library defines messages to be passed to the Data Dictionary.
- DmGwV0Util -- The DmGwV0Util library contains the implementation of functions used by the ECS to V0 Gateway for client/server interfaces.
- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- EcDcMsgPsnng1 -- This library consists of message passing objects used by both the client and server side.
- EcDmDdClient -- The library establishes and maintains a session with the DDICT server.
- EcSbCl -- This library contains all the classes for Subscription Server client.

- EcSbMsg -- This library contains all message classes used for the communication between Subscription Server and its client objects provided by Subscription Server client library.
- MsAcClnt -- The Accountability Management Service makes the user profile available to the various subsystems, such as the Data Server subsystem, information such as the user's electronic mail address and the shipping address, which are used for the distribution of
- MsAcComm -- This library contains class used for both Accountability Server and Client
- srf -- The SRF library provides the necessary mechanism for the application to communicate asynchronously with another application.

Shared Libraries Linked

- agenteventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsEmMailRelASh -- This Library is used for the emails using sendmail utility and the nnpst for Bulletin board messages.
- CsFtFTPRelASh -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObjSh -- This library provides functions to use FTP at a scheduled time by the User.
- CsSeCryptoDesSh -- This library contains the APIs for the DES encryption algorithm.
- DsAdSh -- This library provides an administrative/M&O interface to science data server requests.
- DsBtSh -- This library implements a thread which notifies the subscription server of events.
- DsClSh -- This library contains classes which make up the Science Data Server's (SDSRV) public interface. These classes are used by clients to connect, build commands, and submit requests to the SDSRV.
- DsCnSh -- This library was used to generate files which install ESDT configuration information for each ESDT previously.
- DsCsSh -- This library is used by the HDFEOS server which supplies subsetting services to DLL or other clients.
- DsDbSh -- This library encapsulates the Sybase Open Client calls from the rest of the SDSRV.
- DsDcSh -- This library is used by subsetting code which make reformatting calls to convert HDF-EOS file format to HDF file format for subsetted HDF files.
- DsDdBSh -- This library contains base objects used in both the client and server components of DDIST.
- DsDdCSh -- This is the client side library.
- DsDdISh
- DsDe1Sh -- This internal library contains the method to do validation, installing ESDT, sending metadata to IOS, DMS and SBSRV and generate MCF to ingest.

- DsDe2Sh -- This internal library contains the method to do validation, installing ESDT, sending metadata to IOS,DMS and SBSRV and generate MCF to ingest.
- DsGeSh -- This library provides the public interface for access to all ESDT services and ESDT specifications.
- DsHcSh -- This library provides a DCE-independent client interfaces for both Conformant and NonConformant subsetting.
- DsHrSh -- This library encapsulates all DCE exposure for the distributed objects and functions for both Conformant and NonConformant subsetting on the server side for HdfEos server.
- DsMd1Sh -- This library defines metadata classes used to access a database.
- DsMd2Sh -- This library defines metadata classes used to access a database.
- DsMd3Sh -- This library defines metadata classes used to access a database.
- DsShSh -- This internal library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- DsSiSh
- DsSrSh -- This is an internal library for Science Data Server.
- DsStCmnShSh
- DsStCopyDSh
- DsStDaemonSh
- DsStFtpSh
- DsStPrinterShSh
- DsStResShSh
- DsStStSh -- Both client and server code are contained in this library.
- EcCfSh -- The Config library (CF) is a shared library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistrySh
- EcDcMsgPng1Sh -- This library consists of message passing objects used by both the client and server side.
- EcDnDirSh -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcFhSh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLocatorSh -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcNsServiceLocSh -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.

- EcPfSh -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPoDbRWSH
- EcPoSh -- The Persistent CSC provides a set of abstract and base classes for approved advertisements and requests.
- EcPtSpecialLockSh -- This library provides classes for mutex operations and thread IDs.
- EcSeCmiSh -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeServerKeyMgmtSh -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbedSh -- This shared Library has only the methods for completing the successful compilation.
- EcSeUtilityCtStubbedSh -- This shared Library provides stubbed version of EcSeUtilityCt for successful compilation.
- EcTiTimeSh -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUrSh -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUtFactorySh -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtMiscSh -- The EcUtMisc library contains miscellaneous utilities.
- EcUtSh -- EcUt is a utility library for all the ECS applications.
- eventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- GlSh -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.
- IoAdCoreSh -- The CoreLib CSC provides a set of functionalities for describing a generic advertisement, parsing and validating attributes that support the ECS Core meta data model, and requesting and moderating advertisements.
- IoAdProxySh -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSearchSh -- The SearchLib CSC provides a set of searching capabilities for approved advertisements, for the administration of groups, and for moderation of requests.
- IoAdServerSh -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSubsSh -- The SubsLib CSC provides a set of derived classes which represent different types of advertisements: products, services, and providers.

process EcDsScienceDataServer

/ecs/formal/DSS/sdsrv/src/sr

EcDsScienceDataServer is the core server of EOS system. It provides clients the basic functions: store and retrieve the EOS data with the cooperation by other subsystem servers. It allows client insert various types granules to storage and acquire them when they are needed. It keeps track of granules' information with direct access to a metadata database. With the help of other servers, it provides auxiliary services to clients so that they can use EOS system more efficiently and conveniently.

Libraries Linked

- Common -- This library contains classes for the EcsToV0Server and V0ToEcsServer executables.
- DmAsGwCommon -- The DmAsGwCommon library contains utility classes and term definitions used by the Aster Gateway.
- DmDdMsg -- This library defines messages to be passed to the Data Dictionary.
- DmGwV0Util -- The DmGwV0Util library contains the implementation of functions used by the ECS to V0 Gateway for client/server interfaces.
- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- EcDcMsgPsng1 -- This library consists of message passing objects used by both the client and server side.
- EcDmDdClient -- The library establishes and maintains a session with the DDICT server.
- EcSbCl -- This library contains all the classes for Subscription Server client.
- EcSbMsg -- This library contains all message classes used for the communication between Subscription Server and its client objects provided by Subscription Server client library.
- MsAcClnt -- The Accountability Management Service makes the user profile available to the various subsystems, such as the Data Server subsystem, information such as the user's electronic mail address and the shipping address, which are used for the distribution of
- MsAcComm -- This library contains class used for both Accountability Server and Client
- srf -- The SRF library provides the necessary mechanism for the application to communicate asynchronously with another application.

Shared Libraries Linked

- agenteventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsEmMailRelASh -- This Library is used for the emails using sendmail utility and the nnpst for Bulletin board messages.
- CsFtFTPRelASh -- This library provides a Wrapper for FTP.

- CsFtFTPSchedObjSh -- This library provides functions to use FTP at a scheduled time by the User.
- CsSeCryptoDesSh -- This library contains the APIs for the DES encryption algorithm.
- DsAdSh -- This library provides an administrative/M&O interface to science data server requests.
- DsBtSh -- This library implements a thread which notifies the subscription server of events.
- DsClSh -- This library contains classes which make up the Science Data Server's (SDSRV) public interface. These classes are used by clients to connect, build commands, and submit requests to the SDSRV.
- DsCnSh -- This library was used to generate files which install ESDT configuration information for each ESDT previously.
- DsCsSh -- This library is used by the HDFEOS server which supplies subsetting services to DLL or other clients.
- DsDbSh -- This library encapsulates the Sybase Open Client calls from the rest of the SDSRV.
- DsDcSh -- This library is used by subsetting code which make reformatting calls to convert HDF-EOS file format to HDF file format for subsetted HDF files.
- DsDdBSh -- This library contains base objects used in both the client and server components of DDIST.
- DsDdCSh -- This is the client side library.
- DsDdIsh
- DsDe1Sh -- This internal library contains the method to do validation, installing ESDT, sending metadata to IOS, DMS and SBSRV and generate MCF to ingest.
- DsDe2Sh -- This internal library contains the method to do validation, installing ESDT, sending metadata to IOS, DMS and SBSRV and generate MCF to ingest.
- DsGeSh -- This library provides the public interface for access to all ESDT services and ESDT specifications.
- DsHcSh -- This library provides a DCE-independent client interfaces for both Conformant and NonConformant subsetting.
- DsHrSh -- This library encapsulates all DCE exposure for the distributed objects and functions for both Conformant and NonConformant subsetting on the server side for HdfEos server.
- DsMd1Sh -- This library defines metadata classes used to access a database.
- DsMd2Sh -- This library defines metadata classes used to access a database.
- DsMd3Sh -- This library defines metadata classes used to access a database.
- DsShSh -- This internal library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- DsSiSh

- DsSrSh -- This is an internal library for Science Data Server.
- DsStCmnShSh
- DsStCopyDSh
- DsStDaemonSh
- DsStFtpSh
- DsStPrinterShSh
- DsStResShSh
- DsStStSh -- Both client and server code are contained in this library.
- EcCfSh -- The Config library (CF) is a shared library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistrySh
- EcDcMsgPsnng1Sh -- This library consists of message passing objects used by both the client and server side.
- EcDnDirSh -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcFhSh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLocatorSh -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcNsServiceLocSh -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcPfSh -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPoDbRWSH
- EcPoSh -- The Persistent CSC provides a set of abstract and base classes for approved advertisements and requests.
- EcPtSpecialLockSh -- This library provides classes for mutex operations and thread IDs.
- EcSeCmiSh -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeServerKeyMgmtSh -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbedSh -- This shared Library has only the methods for completing the successful compilation.
- EcSeUtilityCtStubbedSh -- This shared Library provides stubbed version of EcSeUtilityCt for successful compilation.

- EcTiTimeSh -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUrSh -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUtFactorySh -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtMiscSh -- The EcUtMisc library contains miscellaneous utilities.
- EcUtSh -- EcUt is a utility library for all the ECS applications.
- eventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- GlSh -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.
- IoAdCoreSh -- The CoreLib CSC provides a set of functionalities for describing a generic advertisement, parsing and validating attributes that support the ECS Core meta data model, and requesting and moderating advertisements.
- IoAdProxySh -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSearchSh -- The SearchLib CSC provides a set of searching capabilities for approved advertisements, for the administration of groups, and for moderation of requests.
- IoAdServerSh -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSubsSh -- The SubsLib CSC provides a set of derived classes which represent different types of advertisements: products, services, and providers.

process EcDsSdSrvGui

/ecs/formal/DSS/gui/src/sdsrv

The Science Data Server GUI provides the operator two major functions, the management of Earth Science Data Types and the monitoring of all types of requests the Science Data Server is involved with. The Data Types GUI allows operations to add and view the ESDTs offered by the Science Data Server; the System Requests GUI allows operators to monitor and change the priority for all the requests within each data server component.

Classes

- DsGuDssMW -- Created by Builder Xcessory Version 5.0.3.
- DsGuElement
- DsGuErrorDialog -- Created by Builder Xcessory Version 5.0.3.
- DsGuList
- DsGuMultiFile -- Created by Builder Xcessory Version 5.0.3.
- DsGuOperatorMessage -- Created by Builder Xcessory Version 5.0.3.

- DsGuQueue
- DsGuSdDatatype -- Created by Builder Xcessory Version 5.0.3.
- DsGuSysRequest -- Created by Builder Xcessory Version 5.0.3.
- DsGuSystemSettings -- Created by Builder Xcessory Version 5.0.3.
- UIComponent -- Base class for all C++/Motif UI components.

Libraries Linked

- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- EcDcMsgPsng1 -- This library consists of message passing objects used by both the client and server side.
- EcUtGUIg_mt_eh_tp
- EcUtHelpg_mt_eh_tp

Shared Libraries Linked

- agenteventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsEmMailRelASh -- This Library is used for the emails using sendmail utility and the nnpost for Bulletin board messages.
- CsFtFTPRelASh -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObjSh -- This library provides functions to use FTP at a scheduled time by the User.
- DsAdSh -- This library provides an administrative/M&O interface to science data server requests.
- DsClSh -- This library contains classes which make up the Science Data Server's (SDSRV) public interface. These classes are used by clients to connect, build commands, and submit requests to the SDSRV.
- DsCnSh -- This library was used to generate files which install ESDT configuration information for each ESDT previously.
- DsShSh -- This internal library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- EcCfSh -- The Config library (CF) is a shared library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistrySh
- EcDcMsgPsng1Sh -- This library consists of message passing objects used by both the client and server side.

- EcDnDirSh -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcFhSh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLocatorSh -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcNsServiceLocSh -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcPfSh -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPoDbRWSH
- EcPoSh -- The Persistent CSC provides a set of abstract and base classes for approved advertisements and requests.
- EcPtSpecialLockSh -- This library provides classes for mutex operations and thread IDs.
- EcSeCmiSh -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeServerKeyMgmtSh -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbedSh -- This shared Library has only the methods for completing the successful compilation.
- EcSeUtilityCtStubbedSh -- This shared Library provides stubbed version of EcSeUtilityCt for successful compilation.
- EcTiTimeSh -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUrSh -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUtFactorySh -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtMiscSh -- The EcUtMisc library contains miscellaneous utilities.
- EcUtSh -- EcUt is a utility library for all the ECS applications.
- eventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- GlSh -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.
- IoAdCoreSh -- The CoreLib CSC provides a set of functionalities for describing a generic advertisement, parsing and validating attributes that support the ECS Core meta data model, and requesting and moderating advertisements.
- IoAdProxySh -- The ServerLib CSC provides classes for process framework DCE server and client.

- IoAdSearchSh -- The SearchLib CSC provides a set of searching capabilities for approved advertisements, for the administration of groups, and for moderation of requests.
- IoAdServerSh -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSubsSh -- The SubsLib CSC provides a set of derived classes which represent different types of advertisements: products, services, and providers.

process EcDsSt4MMServer

/ecs/formal/DSS/stmgt/src/tp/stacker/4mm

The EcDsSt4MMServer is the resource manager for the 4MM stackers. Scheduling of the usage and any input and output from the device are handled by the 4MM stacker resource manager. This manage only handles 4MM devices that are part of automated stackers. It runs only on Sun hardware. This resource manager can handle multiple 4mm stackers, but is limited to managing only the stackers that are physically connected to the node that hosts this server.

Libraries Linked

- agentevent -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsFtFTPReIA -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObj -- This library provides functions to use FTP at a scheduled time by the User.
- CsSeCryptoDes -- This library contains the APIs for the DES encryption algorithm.
- DsCn -- This library is used to access a server specific configuration file.
- DsSh -- This library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- DsStCmn -- This internal library contains the interface that the code uses to do database access and run stored procedures.
- DsStCopyD
- DsStDaemon
- DsStDb -- This library contains the implementation of the common stacker code.
- DsStFmt -- This library is used to format the writing of files to tape and other reading of files from tape.
- DsStFtp
- DsStRes -- This library provides the common functionality for all of the resource manager servers. Libraries are maintained for both SGI and Sun.
- DsStScsi -- This library supports most standard scsi commands in hopes that there will only be minimal changes needed to support new devices.
- DsStSt -- Both client and server code are contained in the library.

- DsStStk4 -- This library implements code specific for the 4MM stacker resource manager and should only be used by the server side.
- DsStTape -- This library contains the base class functionality that is common to all tape resource managers.
- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- EcCf -- The Config library (CF) is a static library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistry
- EcDcMsgPsnng1 -- This library consists of message passing objects used by both the client and server side.
- EcDnDir -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcFh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLoc -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcNsServiceLocator -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcPf -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPoDbRW
- EcPtSpecialLock -- This library provides classes for mutex operations and thread IDs.
- EcSeCmi -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeServerKeyMgmt -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbed -- This static Library is the stubbed version of EcSeSybSecurity.
- EcSeUtilityDbStubbed -- This static Library is stub version of the EcSeUtilityDb library.
- EcTiTime -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUr -- A Universal Reference (UR) is created as a logical reference to an extant ECS object.
- EcUt -- EcUt is a utility library for all the ECS applications.
- EcUtFactory -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtMisc -- This library contains miscellaneous utilities.
- event -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.

- Gl -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.
- MsAcClnt -- The Accountability Management Service makes the user profile available to the various subsystems, such as the Data Server subsystem, information such as the user's electronic mail address and the shipping address, which are used for the distribution of
- MsAcComm -- This library contains class used for both Accountability Server and Client

process EcDsSt8MMServer

/ecs/formal/DSS/stmgt/src/tp/stacker/8mm

The EcDsSt8MMServer is the resource manager for the 8MM stackers. Scheduling of the usage and any input and output from the device are handled by the 8MM stacker resource manager. This manage only handles 8MM devices that are part of automated stackers. It runs only on Sun hardware. This resource manager can handle multiple 8mm stackers, but is limited to managing only the stackers that are physically connected to the node that hosts this server.

Libraries Linked

- agentevent -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsFtFTPRelA -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObj -- This library provides functions to use FTP at a scheduled time by the User.
- CsSeCryptoDes -- This library contains the APIs for the DES encryption algorithm.
- DsCn -- This library is used to access a server specific configuration file.
- DsSh -- This library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- DsStCmn -- This internal library contains the interface that the code uses to do database access and run stored procedures.
- DsStCopyD
- DsStDaemon
- DsStDb -- This library contains the implementation of the common stacker code.
- DsStFmt -- This library is used to format the writing of files to tape and other reading of files from tape.
- DsStFtp
- DsStRes -- This library provides the common functionality for all of the resource manager servers. Libraries are maintained for both SGI and Sun.
- DsStScsi -- This library supports most standard scsi commands in hopes that there will only be minimal changes needed to support new devices.
- DsStSt -- Both client and server code are contained in the library.

- DsStStk8 -- This library implements code specific for the 8MM stacker resource manager and should only be used by the server side.
- DsStTape -- This library contains the base class functionality that is common to all tape resource managers.
- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- EcCf -- The Config library (CF) is a static library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistry
- EcDcMsgPsnng1 -- This library consists of message passing objects used by both the client and server side.
- EcDnDir -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcFh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLoc -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcNsServiceLocator -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcPf -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPoDbRW
- EcPtSpecialLock -- This library provides classes for mutex operations and thread IDs.
- EcSeCmi -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeServerKeyMgmt -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbed -- This static Library is the stubbed version of EcSeSybSecurity.
- EcSeUtilityDbStubbed -- This static Library is stub version of the EcSeUtilityDb library.
- EcTiTime -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUr -- A Universal Reference (UR) is created as a logical reference to an extant ECS object.
- EcUt -- EcUt is a utility library for all the ECS applications.
- EcUtFactory -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtMisc -- This library contains miscellaneous utilities.
- event -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.

- Gl -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.
- MsAcClnt -- The Accountability Management Service makes the user profile available to the various subsystems, such as the Data Server subsystem, information such as the user's electronic mail address and the shipping address, which are used for the distribution of
- MsAcComm -- This library contains class used for both Accountability Server and Client

process EcDsSt9TrkTapeServer

/ecs/formal/DSS/stmgt/src/tp/9Trk

Resource manager for 9-track tape. Queues are maintained for requests based on priority and time of request receipt.

Libraries Linked

- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- MsAcClnt -- The Accountability Management Service makes the user profile available to the various subsystems, such as the Data Server subsystem, information such as the user's electronic mail address and the shipping address, which are used for the distribution of
- MsAcComm -- This library contains class used for both Accountability Server and Client

Shared Libraries Linked

- agenteventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsFtFTPRelASh -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObjSh -- This library provides functions to use FTP at a scheduled time by the User.
- CsSeCryptoDesSh -- This library contains the APIs for the DES encryption algorithm.
- DsCnSh -- This library was used to generate files which install ESDT configuration information for each ESDT previously.
- DsShSh -- This internal library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- DsSt9TrkTapeShSh
- DsStCmnShSh
- DsStCopyDSh
- DsStDaemonSh
- DsStFmtShSh
- DsStFtpSh
- DsStResShSh

- DsStScsiShSh
- DsStStSh -- Both client and server code are contained in this library.
- DsStTapeShSh
- EcCfSh -- The Config library (CF) is a shared library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistrySh
- EcDcMsgPsng1Sh -- This library consists of message passing objects used by both the client and server side.
- EcDnDirSh -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcFhSh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLocatorSh -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcNsServiceLocSh -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcPfSh -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPoDbRWSH
- EcPtSpecialLockSh -- This library provides classes for mutex operations and thread IDs.
- EcSeCmiSh -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeServerKeyMgmtSh -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbedSh -- This shared Library has only the methods for completing the successful compilation.
- EcSeUtilityDbStubbedSh -- This shared Library provides stubbed version of EcSeUtilityDb for successful compilation.
- EcTiTimeSh -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUrSh -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUtFactorySh -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtMiscSh -- The EcUtMisc library contains miscellaneous utilities.
- EcUtSh -- EcUt is a utility library for all the ECS applications.

- eventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- GlSh -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.

process EcDsStArchiveServer

/ecs/formal/DSS/stmgt/src/st

The Archive Server handles client request to put files into or take files out of the COTS archive product. As such, it provides an interface which hides the COTS implementation. Since there may be multiple archives served by different COTS or custom applications, there is an archive ID which is used to map data location into the archive and location in the archive for all files. The archive id is based on a server key and a logical volume identifier. The server key provides a means by which STMGT client supplied software can determine which archive server should be accessed. The logical volume specifier allows for a searching of one or more locations in the archive for the existence of a file. The logical specifier allows for handling multiple "directory paths" for the storage of logically connected data, e.g. all the data for a given ESDT. Currently, data storage is determined by ESDT.

Libraries Linked

- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- MsAcClnt -- The Accountability Management Service makes the user profile available to the various subsystems, such as the Data Server subsystem, information such as the user's electronic mail address and the shipping address, which are used for the distribution of
- MsAcComm -- This library contains class used for both Accountability Server and Client

Shared Libraries Linked

- agenteventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsFtFTPRelASh -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObjSh -- This library provides functions to use FTP at a scheduled time by the User.
- CsSeCryptoDesSh -- This library contains the APIs for the DES encryption algorithm.
- DsCnSh -- This library was used to generate files which install ESDT configuration information for each ESDT previously.
- DsShSh -- This internal library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- DsStCmnShSh
- DsStCopyDSh
- DsStDaemonSh

- DsStFtpSh
- DsStStSh -- Both client and server code are contained in this library.
- EcCfSh -- The Config library (CF) is a shared library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistrySh
- EcDcMsgPsnng1Sh -- This library consists of message passing objects used by both the client and server side.
- EcDnDirSh -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcFhSh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLocatorSh -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcNsServiceLocSh -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcPfSh -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPoDbRWSH
- EcPtSpecialLockSh -- This library provides classes for mutex operations and thread IDs.
- EcSeCmiSh -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeServerKeyMgmtSh -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbedSh -- This shared Library has only the methods for completing the successful compilation.
- EcSeUtilityDbStubbedSh -- This shared Library provides stubbed version of EcSeUtilityDb for successful compilation.
- EcTiTimeSh -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUrSh -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUtFactorySh -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtMiscSh -- The EcUtMisc library contains miscellaneous utilities.
- EcUtSh -- EcUt is a utility library for all the ECS applications.
- eventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.

- GISH -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.

process EcDsStCDROMServer

/ecs/formal/DSS/stmgt/src/cd

Resource manager for CD ROM. Queues are maintained for requests based on priority and time of request receipt.

Libraries Linked

- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- MsAcClnt -- The Accountability Management Service makes the user profile available to the various subsystems, such as the Data Server subsystem, information such as the user's electronic mail address and the shipping address, which are used for the distribution of
- MsAcComm -- This library contains class used for both Accountability Server and Client

Shared Libraries Linked

- agenteventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsFtFTPRelASh -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObjSh -- This library provides functions to use FTP at a scheduled time by the User.
- CsSeCryptoDesSh -- This library contains the APIs for the DES encryption algorithm.
- DsCnSh -- This library was used to generate files which install ESDT configuration information for each ESDT previously.
- DsShSh -- This internal library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- DsStCDROMShSh
- DsStCmnShSh
- DsStCopyDSh
- DsStDaemonSh
- DsStFtpSh
- DsStResShSh
- DsStStSh -- Both client and server code are contained in this library.
- EcCfSh -- The Config library (CF) is a shared library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistrySh

- EcDcMsgPsng1Sh -- This library consists of message passing objects used by both the client and server side.
- EcDnDirSh -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcFhSh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLocatorSh -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcNsServiceLocSh -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcPfSh -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPoDbRWSH
- EcPtSpecialLockSh -- This library provides classes for mutex operations and thread IDs.
- EcSeCmiSh -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeServerKeyMgmtSh -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbedSh -- This shared Library has only the methods for completing the successful compilation.
- EcSeUtilityDbStubbedSh -- This shared Library provides stubbed version of EcSeUtilityDb for successful compilation.
- EcTiTimeSh -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUrSh -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUtFactorySh -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtMiscSh -- The EcUtMisc library contains miscellaneous utilities.
- EcUtSh -- EcUt is a utility library for all the ECS applications.
- eventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- GlSh -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.

process EcDsStCopyDaemon

/ecs/formal/DSS/stmgt/src/daemon/copy

Libraries Linked

- EcUtFactory -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtNoPF -- EcUtNoPF is a utility library for all the ECS applications that do not use Process Framework.

process EcDsStD3Server

/ecs/formal/DSS/stmgt/src/tp/D3

The EcDsStD3Server executable is the image run by the resource manager for the D3 tape. The client interface is supplied by libDsStRes and the SCSI interface is supplied by libDsStScsi. The D3 resource manager schedules the use of the D3 tape drive and manages the I/O to/from the drive on behalf of clients. The D3 resource manager run only on the Sun but can service clients who are either on the Sun or on the SGI.

Libraries Linked

- agentevent -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsFtFTPRelA -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObj -- This library provides functions to use FTP at a scheduled time by the User.
- CsSeCryptoDes -- This library contains the APIs for the DES encryption algorithm.
- DsCn -- This library is used to access a server specific configuration file.
- DsSh -- This library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- DsStCmn -- This internal library contains the interface that the code uses to do database access and run stored procedures.
- DsStCopyD
- DsStD3Tape -- This is a server side library only and contains the custom code for support of the D3 tape.
- DsStDaemon
- DsStFmt -- This library is used to format the writing of files to tape and other reading of files from tape.
- DsStFtp
- DsStRes -- This library provides the common functionality for all of the resource manager servers. Libraries are maintained for both SGI and Sun.
- DsStScsi -- This library supports most standard scsi commands in hopes that there will only be minimal changes needed to support new devices.
- DsStSt -- Both client and server code are contained in the library.

- DsStTape -- This library contains the base class functionality that is common to all tape resource managers.
- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- EcCf -- The Config library (CF) is a static library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistry
- EcDcMsgPsngr1 -- This library consists of message passing objects used by both the client and server side.
- EcDnDir -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcFh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLoc -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcNsServiceLocator -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcPf -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPoDbRW
- EcPtSpecialLock -- This library provides classes for mutex operations and thread IDs.
- EcSeCmi -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeServerKeyMgmt -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbed -- This static Library is the stubbed version of EcSeSybSecurity.
- EcSeUtilityDbStubbed -- This static Library is stub version of the EcSeUtilityDb library.
- EcTiTime -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUr -- A Universal Reference (UR) is created as a logical reference to an extant ECS object.
- EcUt -- EcUt is a utility library for all the ECS applications.
- EcUtFactory -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtMisc -- This library contains miscellaneous utilities.
- event -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- Gl -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.

- MsAcClnt -- The Accountability Management Service makes the user profile available to the various subsystems, such as the Data Server subsystem, information such as the user's electronic mail address and the shipping address, which are used for the distribution of
- MsAcComm -- This library contains class used for both Accountability Server and Client

process EcDsStFTPClientDaemon

/ecs/formal/DSS/stmgt/src/daemon/ftp

Libraries Linked

- EcUtFactory -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtNoPF -- EcUtNoPF is a utility library for all the ECS applications that do not use Process Framework.

process EcDsStFtpDisServer

/ecs/formal/DSS/stmgt/src/ftp/disftp

The EcDsStFtpDisServer provides its clients the ability to do push and pull distribution ftp from a server other than the one the client is on. This is important since, for ftp push, different underlying network architecture may be required for the push than is available to the DDIST server. DDIST is the only client for this server. In turn, this server is a client of the EcDsStPullMonitorServer.

Libraries Linked

- DsStDaemon
- DsStDisFtp -- This library contains the server code which allows for the moving of data from staging to the target location either for end user pull of data from the pull area or push of data to the end user specified node and directory.
- DsStFTPClientD
- DsStNet -- This is a library for the server side only and contains the base class functionality for the classes which implement ftp push and ftp pull distribution services.
- DsStPull -- This library contains the server and client code for the pull cache manager.
- DsStRes -- This library provides the common functionality for all of the resource manager servers. Libraries are maintained for both SGI and Sun.
- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- MsAcClnt -- The Accountability Management Service makes the user profile available to the various subsystems, such as the Data Server subsystem, information such as the user's electronic mail address and the shipping address, which are used for the distribution of
- MsAcComm -- This library contains class used for both Accountability Server and Client

Shared Libraries Linked

- agenteventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsFtFTPRelASh -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObjSh -- This library provides functions to use FTP at a scheduled time by the User.
- CsSeCryptoDesSh -- This library contains the APIs for the DES encryption algorithm.
- DsCnSh -- This library was used to generate files which install ESDT configuration information for each ESDT previously.
- DsShSh -- This internal library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- DsStCmnShSh
- DsStCopyDSh
- DsStDaemonSh
- DsStFtpSh
- DsStStSh -- Both client and server code are contained in this library.
- EcCfSh -- The Config library (CF) is a shared library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistrySh
- EcDcMsgPsnng1Sh -- This library consists of message passing objects used by both the client and server side.
- EcDnDirSh -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcFhSh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLocatorSh -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcNsServiceLocSh -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcPfSh -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPoDbRWSH
- EcPtSpecialLockSh -- This library provides classes for mutex operations and thread IDs.
- EcSeCmiSh -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).

- EcSeServerKeyMgmtSh -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbedSh -- This shared Library has only the methods for completing the successful compilation.
- EcSeUtilityDbStubbedSh -- This shared Library provides stubbed version of EcSeUtilityDb for successful compilation.
- EcTiTimeSh -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUrSh -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUtFactorySh -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtMiscSh -- The EcUtMisc library contains miscellaneous utilities.
- EcUtSh -- EcUt is a utility library for all the ECS applications.
- eventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- GlSh -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.

process EcDsStIngestFtpServer

/ecs/formal/DSS/stmgt/src/ftp/inftp

The EcDsStIngestFtpServer provides ftp pull services to the Ingest subsystem. It utilizes the EcDsStStagingDiskServer as a client and libraries supplied by CSS to perform the ftp pull. It is possible to have different instances of this server running on different platforms to handle, making use of the server id to allow for ingest to move data into the system via the best path for a particular data type.

Libraries Linked

- DsStDaemon
- DsStFTPClientD
- DsStIngestFtp -- This library contains the server side code for performing ftp pulls to satisfy Ingest.
- DsStNet -- This is a library for the server side only and contains the base class functionality for the classes which implement ftp push and ftp pull distribution services.
- DsStRes -- This library provides the common functionality for all of the resource manager servers. Libraries are maintained for both SGI and Sun.
- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.

- MsAcClnt -- The Accountability Management Service makes the user profile available to the various subsystems, such as the Data Server subsystem, information such as the user's electronic mail address and the shipping address, which are used for the distribution of
- MsAcComm -- This library contains class used for both Accountability Server and Client

Shared Libraries Linked

- agenteventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsFtFTPRelASh -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObjSh -- This library provides functions to use FTP at a scheduled time by the User.
- CsSeCryptoDesSh -- This library contains the APIs for the DES encryption algorithm.
- DsCnSh -- This library was used to generate files which install ESDT configuration information for each ESDT previously.
- DsShSh -- This internal library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- DsStCmnShSh
- DsStCopyDSh
- DsStDaemonSh
- DsStFtpSh
- DsStStSh -- Both client and server code are contained in this library.
- EcCfSh -- The Config library (CF) is a shared library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistrySh
- EcDcMsgPsg1Sh -- This library consists of message passing objects used by both the client and server side.
- EcDnDirSh -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcFhSh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLocatorSh -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcNsServiceLocSh -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcPfSh -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPoDbRWSH

- EcPtSpecialLockSh -- This library provides classes for mutex operations and thread IDs.
- EcSeCmiSh -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeServerKeyMgmtSh -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbedSh -- This shared Library has only the methods for completing the successful compilation.
- EcSeUtilityDbStubbedSh -- This shared Library provides stubbed version of EcSeUtilityDb for successful compilation.
- EcTiTimeSh -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUrSh -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUtFactorySh -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtMiscSh -- The EcUtMisc library contains miscellaneous utilities.
- EcUtSh -- EcUt is a utility library for all the ECS applications.
- eventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- GlSh -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.

process EcDsStmgtGui

/ecs/formal/DSS/gui/src/stmgt

The files in this directory comprise the software for the STGMT GUI process, EcDsStmgtGui. The GUI is the primary interface for operations staff to control and monitor STMGT processing. It can be used to help assemble requests for hard media distribution for which multiple media are required. Error messages are sent to the operator GUI which indicate conditions encountered by STMGT processes that the operator needs to be aware of.

Classes

- DsGuStBackupRestart -- Created by Builder Xcessory Version 5.0.3.
- DsGuStCacheStat -- Created by Builder Xcessory Version 5.0.3.
- DsGuStConfiguration -- Created by Builder Xcessory Version 5.0.3.
- DsGuStEvents -- Created by Builder Xcessory Version 5.0.3.
- DsGuStFileViewer -- Created by Builder Xcessory Version 5.0.3.
- DsGuStmgtMW -- Created by Builder Xcessory Version 5.0.3.

- DsGuStOperatorNotify -- This class provides the object to notify the operator of server events.
- DsGuStRequest -- Created by Builder Xcessory Version 5.0.3.
- DsGuStResource -- Created by Builder Xcessory Version 5.0.3.
- DsGuStSetupBackup -- Created by Builder Xcessory Version 5.0.3.
- UIComponent -- Base class for all C++/Motif UI components.

Libraries Linked

- DsStGuiCmn
- DsStPull -- This library contains the server and client code for the pull cache manager.
- DsStRes -- This library provides the common functionality for all of the resource manager servers. Libraries are maintained for both SGI and Sun.
- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- EcUtGUIg_mt_eh_tp
- EcUtHelpg_mt_eh_tp
- MsAcClnt -- The Accountability Management Service makes the user profile available to the various subsystems, such as the Data Server subsystem, information such as the user's electronic mail address and the shipping address, which are used for the distribution of
- MsAcComm -- This library contains class used for both Accountability Server and Client

Shared Libraries Linked

- agenteventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsFtFTPRelASh -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObjSh -- This library provides functions to use FTP at a scheduled time by the User.
- CsSeCryptoDesSh -- This library contains the APIs for the DES encryption algorithm.
- DsCnSh -- This library was used to generate files which install ESDT configuration information for each ESDT previously.
- DsShSh -- This internal library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- DsStCmnShSh
- DsStCopyDSh
- DsStDaemonSh
- DsStFtpSh
- DsStStSh -- Both client and server code are contained in this library.

- EcCfSh -- The Config library (CF) is a shared library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistrySh
- EcDcMsgPsnng1Sh -- This library consists of message passing objects used by both the client and server side.
- EcDnDirSh -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcFhSh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLocatorSh -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcNsServiceLocSh -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcPfSh -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPoDbRWSH
- EcPtSpecialLockSh -- This library provides classes for mutex operations and thread IDs.
- EcSeCmiSh -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeServerKeyMgmtSh -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbedSh -- This shared Library has only the methods for completing the successful compilation.
- EcSeUtilityDbStubbedSh -- This shared Library provides stubbed version of EcSeUtilityDb for successful compilation.
- EcTiTimeSh -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUrSh -- A Universal Reference (UR) is created as a logical reference to an extant ECS object.
- EcUtFactorySh -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtMiscSh -- The EcUtMisc library contains miscellaneous utilities.
- EcUtSh -- EcUt is a utility library for all the ECS applications.
- eventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- GlSh -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.

process EcDsStPrintServer

/ecs/formal/DSS/stmgt/src/pr

Resource manager for the printer. Queues are maintained for requests based on priority and time of request receipt.

Libraries Linked

- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- EcNsServiceLoc -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- MsAcClnt -- The Accountability Management Service makes the user profile available to the various subsystems, such as the Data Server subsystem, information such as the user's electronic mail address and the shipping address, which are used for the distribution of
- MsAcComm -- This library contains class used for both Accountability Server and Client

Shared Libraries Linked

- agenteventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsFtFTPRelASh -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObjSh -- This library provides functions to use FTP at a scheduled time by the User.
- CsSeCryptoDesSh -- This library contains the APIs for the DES encryption algorithm.
- DsCnSh -- This library was used to generate files which install ESDT configuration information for each ESDT previously.
- DsShSh -- This internal library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- DsStCmnShSh
- DsStCopyDSh
- DsStDaemonSh
- DsStFtpSh
- DsStPrinterShSh
- DsStResShSh
- DsStStSh -- Both client and server code are contained in this library.
- EcCfSh -- The Config library (CF) is a shared library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistrySh

- EcDcMsgPsng1Sh -- This library consists of message passing objects used by both the client and server side.
- EcDnDirSh -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcFhSh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLocatorSh -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcNsServiceLocSh -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcPfSh -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPoDbRWSH
- EcPtSpecialLockSh -- This library provides classes for mutex operations and thread IDs.
- EcSeCmiSh -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeServerKeyMgmtSh -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbedSh -- This shared Library has only the methods for completing the successful compilation.
- EcSeUtilityDbStubbedSh -- This shared Library provides stubbed version of EcSeUtilityDb for successful compilation.
- EcTiTimeSh -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUrSh -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUtFactorySh -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtMiscSh -- The EcUtMisc library contains miscellaneous utilities.
- EcUtSh -- EcUt is a utility library for all the ECS applications.
- eventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- GlSh -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.

process EcDsStPullMonitorServer

/ecs/formal/DSS/stmgt/src/pull

The EcDsStPullMonitorServer is the cache manager for the user pull cache. Files that are requested for user pull distribution are moved from the archive to the read only cache, linked to

staging disks maintained by DDIST and the pushed via ftp to a cache directory on the user pull disk. Files are then linked from the cache area to directories with randomly generated names which can be accessed by end users to get their data. The Pull Cache manager, EcDsStPullMonitorServer, determines what files have to be removed from the cache to make room for new files. If it detects that a request is for a file that is already in the cache, it prevents the transfer of the file again. It maintains the links to the user accessible directories and keeps a count of the number of outstanding accesses for a given file in the cache. Files that are not accessed in a configurable time period are expired. The operator can request that no expired files may be deleted except for the ones that are confirmed for delete by the operator. The Pull Cache manager does not do any file transfers, those are done by its client. The EcDsStFtpDisServer is the only client of the EcDsStPullMonitor.

Libraries Linked

- DsStPull -- This library contains the server and client code for the pull cache manager.
- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- MsAcClnt -- The Accountability Management Service makes the user profile available to the various subsystems, such as the Data Server subsystem, information such as the user's electronic mail address and the shipping address, which are used for the distribution of
- MsAcComm -- This library contains class used for both Accountability Server and Client

Shared Libraries Linked

- agenteventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsFtFTPRelASh -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObjSh -- This library provides functions to use FTP at a scheduled time by the User.
- CsSeCryptoDesSh -- This library contains the APIs for the DES encryption algorithm.
- DsCnSh -- This library was used to generate files which install ESDT configuration information for each ESDT previously.
- DsShSh -- This internal library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- DsStCmnShSh
- DsStCopyDSh
- DsStDaemonSh
- DsStFtpSh
- DsStStSh -- Both client and server code are contained in this library.
- EcCfSh -- The Config library (CF) is a shared library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.

- EcCsRegistrySh
- EcDcMsgPsnng1Sh -- This library consists of message passing objects used by both the client and server side.
- EcDnDirSh -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcFhSh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLocatorSh -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcNsServiceLocSh -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcPfSh -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPoDbRWSH
- EcPtSpecialLockSh -- This library provides classes for mutex operations and thread IDs.
- EcSeCmiSh -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeServerKeyMgmtSh -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbedSh -- This shared Library has only the methods for completing the successful compilation.
- EcSeUtilityDbStubbedSh -- This shared Library provides stubbed version of EcSeUtilityDb for successful compilation.
- EcTiTimeSh -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUrSh -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUtFactorySh -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtMiscSh -- The EcUtMisc library contains miscellaneous utilities.
- EcUtSh -- EcUt is a utility library for all the ECS applications.
- eventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- G1Sh -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.

process EcDsStStagingDiskServer

/ecs/formal/DSS/stmgt/src/st

The Staging Disk Server allocates and monitors shared RAID space between competing processes. Clients for which insufficient staging is available currently are queued in a priority based queue. Staging Disk Servers also use the server key to differentiate which of the multiple Staging Disk Servers are accessed. The server key will be available to the client either as part of the archive id or as part of an existing staging disk tag.

Libraries Linked

- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- MsAcClnt -- The Accountability Management Service makes the user profile available to the various subsystems, such as the Data Server subsystem, information such as the user's electronic mail address and the shipping address, which are used for the distribution of
- MsAcComm -- This library contains class used for both Accountability Server and Client

Shared Libraries Linked

- agenteventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsFtFTPRelASh -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObjSh -- This library provides functions to use FTP at a scheduled time by the User.
- CsSeCryptoDesSh -- This library contains the APIs for the DES encryption algorithm.
- DsCnSh -- This library was used to generate files which install ESDT configuration information for each ESDT previously.
- DsShSh -- This internal library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- DsStCmnShSh
- DsStCopyDSh
- DsStDaemonSh
- DsStFtpSh
- DsStStSh -- Both client and server code are contained in this library.
- EcCfSh -- The Config library (CF) is a shared library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistrySh
- EcDcMsgPsnng1Sh -- This library consists of message passing objects used by both the client and server side.

- EcDnDirSh -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcFhSh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLocatorSh -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcNsServiceLocSh -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcPfSh -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPoDbRWSH
- EcPtSpecialLockSh -- This library provides classes for mutex operations and thread IDs.
- EcSeCmiSh -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeServerKeyMgmtSh -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbedSh -- This shared Library has only the methods for completing the successful compilation.
- EcSeUtilityDbStubbedSh -- This shared Library provides stubbed version of EcSeUtilityDb for successful compilation.
- EcTiTimeSh -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUrSh -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUtFactorySh -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtMiscSh -- The EcUtMisc library contains miscellaneous utilities.
- EcUtSh -- EcUt is a utility library for all the ECS applications.
- eventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- GlSh -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.

process EcDsStStagingMonitorServer

/ecs/formal/DSS/stmgt/src/st

The Staging Monitor Server monitors the Read Only cache area which is part of the partition monitored by the Staging Disk Server. Files which are retrieved from the archive are moved to the Read Only cache which is monitored by the Staging Monitor that shares the same Server Key as the archive server. The Staging Monitor Server governs the writing and deleting of files to the

Read Only cache. Clients of Staging Disk can access files in the Read Only cache via Staging Disk calls.

Libraries Linked

- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- MsAcClnt -- The Accountability Management Service makes the user profile available to the various subsystems, such as the Data Server subsystem, information such as the user's electronic mail address and the shipping address, which are used for the distribution of
- MsAcComm -- This library contains class used for both Accountability Server and Client

Shared Libraries Linked

- agenteventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsFtFTPRelASh -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObjSh -- This library provides functions to use FTP at a scheduled time by the User.
- CsSeCryptoDesSh -- This library contains the APIs for the DES encryption algorithm.
- DsCnSh -- This library was used to generate files which install ESDT configuration information for each ESDT previously.
- DsShSh -- This internal library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- DsStCmnShSh
- DsStCopyDSh
- DsStDaemonSh
- DsStFtpSh
- DsStStSh -- Both client and server code are contained in this library.
- EcCfSh -- The Config library (CF) is a shared library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistrySh
- EcDcMsgPng1Sh -- This library consists of message passing objects used by both the client and server side.
- EcDnDirSh -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcFhSh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLocatorSh -- The Service Locator library provides an implementation independent mechanism for specifying service locations.

- EcNsServiceLocSh -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcPfSh -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPoDbRWSH
- EcPtSpecialLockSh -- This library provides classes for mutex operations and thread IDs.
- EcSeCmiSh -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeServerKeyMgmtSh -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbedSh -- This shared Library has only the methods for completing the successful compilation.
- EcSeUtilityDbStubbedSh -- This shared Library provides stubbed version of EcSeUtilityDb for successful compilation.
- EcTiTimeSh -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUrSh -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUtFactorySh -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtMiscSh -- The EcUtMisc library contains miscellaneous utilities.
- EcUtSh -- EcUt is a utility library for all the ECS applications.
- eventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- GlSh -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.

process StoredProcedure

/ecs/formal/DSS/stmgt/src/cmn

Libraries Linked

- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- MsAcClnt -- The Accountability Management Service makes the user profile available to the various subsystems, such as the Data Server subsystem, information such as the user's electronic mail address and the shipping address, which are used for the distribution of
- MsAcComm -- This library contains class used for both Accountability Server and Client

Shared Libraries Linked

- agenteventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsFtFTPRelASh -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObjSh -- This library provides functions to use FTP at a scheduled time by the User.
- CsSeCryptoDesSh -- This library contains the APIs for the DES encryption algorithm.
- DsCnSh -- This library was used to generate files which install ESDT configuration information for each ESDT previously.
- DsShSh -- This internal library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- DsStCmnShSh
- DsStCopyDSh
- DsStDaemonSh
- DsStFtpSh
- DsStStSh -- Both client and server code are contained in this library.
- EcCfSh -- The Config library (CF) is a shared library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistrySh
- EcDcMsgPsngr1Sh -- This library consists of message passing objects used by both the client and server side.
- EcDnDirSh -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcFhSh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLocatorSh -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcNsServiceLocSh -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcPfSh -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPoDbRWSH
- EcPtSpecialLockSh -- This library provides classes for mutex operations and thread IDs.
- EcSeCmiSh -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).

- EcSeServerKeyMgmtSh -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbedSh -- This shared Library has only the methods for completing the successful compilation.
- EcSeUtilityDbStubbedSh -- This shared Library provides stubbed version of EcSeUtilityDb for successful compilation.
- EcTiTimeSh -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUrSh -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUtFactorySh -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtMiscSh -- The EcUtMisc library contains miscellaneous utilities.
- EcUtSh -- EcUt is a utility library for all the ECS applications.
- eventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- GlSh -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.

process will

/ecs/formal/DSS/stmgt/src/cd

Libraries Linked

- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- MsAcClnt -- The Accountability Management Service makes the user profile available to the various subsystems, such as the Data Server subsystem, information such as the user's electronic mail address and the shipping address, which are used for the distribution of
- MsAcComm -- This library contains class used for both Accountability Server and Client

Shared Libraries Linked

- agenteventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsFtFTPRelASh -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObjSh -- This library provides functions to use FTP at a scheduled time by the User.
- CsSeCryptoDesSh -- This library contains the APIs for the DES encryption algorithm.
- DsCnSh -- This library was used to generate files which install ESDT configuration information for each ESDT previously.

- DsShSh -- This internal library provides underlying DCE(ODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- DsStCDROMShSh
- DsStCmnShSh
- DsStCopyDSh
- DsStDaemonSh
- DsStFtpSh
- DsStResShSh
- DsStStSh -- Both client and server code are contained in this library.
- EcCfSh -- The Config library (CF) is a shared library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistrySh
- EcDcMsgPng1Sh -- This library consists of message passing objects used by both the client and server side.
- EcDnDirSh -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcFhSh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLocatorSh -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcNsServiceLocSh -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcPfSh -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPoDbRWSH
- EcPtSpecialLockSh -- This library provides classes for mutex operations and thread IDs.
- EcSeCmiSh -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeServerKeyMgmtSh -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbedSh -- This shared Library has only the methods for completing the successful compilation.
- EcSeUtilityDbStubbedSh -- This shared Library provides stubbed version of EcSeUtilityDb for successful compilation.
- EcTiTimeSh -- This library is used to obtain the current time in various formats, and manipulate the time.

- EcUrSh -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUtFactorySh -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtMiscSh -- The EcUtMisc library contains miscellaneous utilities.
- EcUtSh -- EcUt is a utility library for all the ECS applications.
- eventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- GlSh -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.

script DsDdDirSetup

/ecs/formal/DSS/distribution/src/cfg

script DsDdStartServer

/ecs/formal/DSS/distribution/src/cfg

Used for the Performance Metrics setenv EcAgInstanceID 6 the base directory where the PF data files resides.

script EcDsStartDistributionServer

/ecs/formal/DSS/distribution/src/cfg

Used for the Performance Metrics setenv EcAgInstanceID 6 the base directory where the PF data files resides.

script EcDsStartHDFSrv1

/ecs/formal/DSS/sdsrv/src/hr

script EcDsStartSDSRV

/ecs/formal/DSS/sdsrv/src/sr

script EcDsStartSDSRVApp

/ecs/formal/DSS/sdsrv/src/sr

Subsystem INS

The Ingest Subsystem supports the ingest of data into ECS repositories. This data is accepted from a variety of external data providers in various formats and is predefined within ECS with regard to expected metadata and metadata characteristics, and is ingested in accordance with approved ICDs. The Ingest Subsystem supports a variety of ingest requests and preprocesses the data for archiving into ECS. This preprocessing varies according to attributes of the ingested

data such as data type, data format, and the level to which the ingested data has been processed from raw instrument data.

The data types are formally referred to as Earth Science Data Types (ESDTs). An ESDT is a defined data set associated with a given mission/instrument or identified grouping and is registered in an ESDT Baseline List. The ESDT is identified with a short name, a long name, a collection description, and information of file type, metadata, formats, and services provided such as sub-setting by a given attribute. An example of an ESDT is AST_L1A (short name) which is the ASTER Level 1A data set which is reconstructed, unprocessed instrument digital counts with radiometric and geometric coefficients attached. ESDTs may also be ancillary data, algorithms, correlative and calibration data.

The Ingest Subsystem software is organized into collections of software processes which executes in a specific pattern depending on the ESDT being ingested. These processes include an automated ingest process, a polling ingest process and a media ingest process. These ingest processes provide the virtual interface for the receipt of all external data to be archived within the archival system of the ECS Science Data Processing System (SDPS). Specific ingest process parameters are to be modified as interface and mission requirements evolve. For a given incoming data set corresponding to an ESDT, Ingest performs data preprocessing, metadata extraction, and directs the DSS SDSRV to perform metadata validation.

process EclnAuto

/ecs/formal/INGEST/SessionMgr/src/AutoIngest

This program provides fundamental capabilities so that data may be ingested into the ECS system. This process can be tailored to fit for a specific interface. RPCs are utilized to request ingest services which include the establishment of a connection with the external source. This process manages multiple requests, checks DAN information, invokes an RPC to the Request Manager to begin request processing, sends and receives data status messages, and cleans up request information. Error log information is placed into common files for access by MSS.

Classes

- InAutoIngestIF_1_0_ABS
- InAutoIngestIF_1_0_Mgr -- This class allows the Landsat-7 Gateway to send a DAN message to Auto Ingest.
- InAutoNtwkIngestMgr -- Provides a single point of entry to the Ingest system for all ingest OODCE interfaces.
- InRequestMgrIF_1_0 -- This class provides the interfaces from the Ingest Request Manager clients to the Request Manager.
- PktStructDef_1_0

Libraries Linked

- CsEmMailRelA -- This Library is used for the emails using sendmail utility and the nnpst for Bulletin board messages.
- CsSeCryptoDes -- This library contains the APIs for the DES encryption algorithm.

- DsCl -- This library contains classes which make up the Science Data Server's (SDSRV) public interface. These classes are used by clients to connect, build commands, and submit requests to the SDSRV.
- DsCn -- This library is used to access a server specific configuration file.
- DsSh -- This library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- DsStCmn -- This internal library contains the interface that the code uses to do database access and run stored procedures.
- DsStCopyD
- DsStDaemon
- DsStFtp
- DsStRes -- This library provides the common functionality for all of the resource manager servers. Libraries are maintained for both SGI and Sun.
- DsStSt -- Both client and server code are contained in the library.
- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- EcUtMisc -- This library contains miscellaneous utilities.
- Gl -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.
- InConfig -- This library provides a class which is used by each Ingest executable to obtain parameters from its configuration file.
- InDBaccUt -- This library provides classes which allows access to the Ingest database.
- InMsg -- This library provides classes that are used for all data messages exchanged between the external source and Ingest.

Shared Libraries Linked

- agenteventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsFtFTPRelASh -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObjSh -- This library provides functions to use FTP at a scheduled time by the User.
- EcCfSh -- The Config library (CF) is a shared library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistrySh
- EcDcMsgPng1Sh -- This library consists of message passing objects used by both the client and server side.

- EcDnDirSh -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcFhSh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLocatorSh -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcNsServiceLocSh -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcPfSh -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPoDbRWSH
- EcPtSpecialLockSh -- This library provides classes for mutex operations and thread IDs.
- EcSeCmiSh -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeServerKeyMgmtSh -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbedSh -- This shared Library has only the methods for completing the successful compilation.
- EcSeUtilityDbStubbedSh -- This shared Library provides stubbed version of EcSeUtilityDb for successful compilation.
- EcTiTimeSh -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUrSh -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUtFactorySh -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtSh -- EcUt is a utility library for all the ECS applications.
- eventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.

process EcInEmailGWServer

/ecs/formal/INGEST/InEmailGWServer/src/EmailGW

Receives email distribution notification messages, stores them into files which are then converted into PDRs which are placed into a Polling directory.

Classes

- InEmailGWServer -- Rogue Wave Includes.
- InEmailParser -- The InEmailParser class is used to support the EcInEmailGWServer.

- InManagedServer -- This is an example how an application can use Process Frame Work to create a managed server.

Libraries Linked

- CsEmMailRelA -- This Library is used for the emails using sendmail utility and the nnpst for Bulletin board messages.
- CsSeCryptoDes -- This library contains the APIs for the DES encryption algorithm.
- DsSh -- This library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- DsStCmn -- This internal library contains the interface that the code uses to do database access and run stored procedures.
- DsStCopyD
- DsStDaemon
- DsStFtp
- DsStRes -- This library provides the common functionality for all of the resource manager servers. Libraries are maintained for both SGI and Sun.
- DsStSt -- Both client and server code are contained in the library.
- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- EcUtMisc -- This library contains miscellaneous utilities.
- InDBaccUt -- This library provides classes which allows access to the Ingest database.
- InMsg -- This library provides classes that are used for all data messages exchanged between the external source and Ingest.

Shared Libraries Linked

- agenteventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsFtFTPRelASh -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObjSh -- This library provides functions to use FTP at a scheduled time by the User.
- EcCfSh -- The Config library (CF) is a shared library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistrySh
- EcDcMsgPng1Sh -- This library consists of message passing objects used by both the client and server side.
- EcDnDirSh -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.

- EcFhSh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLocatorSh -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcNsServiceLocSh -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcPfSh -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPtSpecialLockSh -- This library provides classes for mutex operations and thread IDs.
- EcSeCmiSh -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeServerKeyMgmtSh -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbedSh -- This shared Library has only the methods for completing the successful compilation.
- EcSeUtilityCtStubbedSh -- This shared Library provides stubbed version of EcSeUtilityCt for successful compilation.
- EcTiTimeSh -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUrSh -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUtFactorySh -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtSh -- EcUt is a utility library for all the ECS applications.
- eventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.

process EcInGran

/ecs/formal/INGEST/GranServer/src/Server

Provides services to perform required preprocessing of data and subsequent insertion of the data into the appropriate Data Server. The preprocessing of data consists of converting the data (if needed), extracting the metadata into the standard ECS metadata format (if needed), performing required metadata existence and parameter range checks, and updating the metadata with ingest specific metadata (e.g., start and stop date/time for ingest). It is responsible for coordinating the ingest processing, which is comprised of transferring data, performing data preprocessing, and sending an insertion request to the appropriate Data Server. In addition, the EcInGran is responsible for updating the granule state.

Classes

- InDataTransferTask -- InDataTransferTask class conducts data transfer from the external sources into Ingest subsystem.
- InGranuleAsync_S -- The InGranuleAsync_S class is the server-side component of the asynchronous granule request capability.
- InGranuleDispatcher -- This is the customized version of the Ingest granule dispatcher object.
- InGranuleServer -- The InGranuleServer class listens for incoming granule request messages.

Libraries Linked

- CsEmMailRelA -- This Library is used for the emails using sendmail utility and the nnpst for Bulletin board messages.
- CsSeCryptoDes -- This library contains the APIs for the DES encryption algorithm.
- DsCl -- This library contains classes which make up the Science Data Server's (SDSRV) public interface. These classes are used by clients to connect, build commands, and submit requests to the SDSRV.
- DsCn -- This library is used to access a server specific configuration file.
- DsSh -- This library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- DsStCmn -- This internal library contains the interface that the code uses to do database access and run stored procedures.
- DsStCopyD
- DsStDaemon
- DsStFtp
- DsStRes -- This library provides the common functionality for all of the resource manager servers. Libraries are maintained for both SGI and Sun.
- DsStSt -- Both client and server code are contained in the library.
- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- EcPo -- The Persistent CSC provides a set of abstract and base classes for approved advertisements and requests.
- EcPoDbRW
- EcUtMisc -- This library contains miscellaneous utilities.
- Gl -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.
- InADPP -- This library provides additional preprocessing functionality.

- InConfig -- This library provides a class which is used by each Ingest executable to obtain parameters from its configuration file.
- InDBaccUt -- This library provides classes which allows access to the Ingest database.
- InGranResource -- This library allocates/deallocates staging disk resources and calls the IngestFtpServer to transfer files.
- InGranuleC -- This library supports the client side of the SRF request.
- InGranuleMsg -- This library supports the messages needed for SRF to communicate between Granule Server and Request Manager.
- InMetadataToolAPI -- This library provides the class which accesses the PGS Toolkit from a non PGE C++ environment.
- InMsg -- This library provides classes that are used for all data messages exchanged between the external source and Ingest.
- InPreprocess -- This library provides preprocessing functions.
- InResource -- This library allocates/deallocates staging disk resources.
- InRmQueue -- This library contains code for Request Managers queue.
- InSnowIce -- This library provides the class which inserts all of the data sets extracted from the native format file into SDSs within HDF-EOS.
- InTOMS -- This library provides the class that is designed to pre-process TOMS data in CD-ROM format into the standard ECS Internal format.
- IoAdCore -- The CoreLib CSC provides a set of functionalities for describing a generic advertisement, parsing and validating attributes that support the ECS Core meta data model, and requesting and moderating advertisements.
- IoAdProxy -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSearch -- The SearchLib CSC provides a set of searching capabilities for approved advertisements, for the administration of groups, and for moderation of requests.
- IoAdServer -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSubs -- The SubsLib CSC provides a set of derived classes which represent different types of advertisements: products, services, and providers.
- srf -- The SRF library provides the necessary mechanism for the application to communicate asynchronously with another application.

Shared Libraries Linked

- agenteventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsFtFTPRelASh -- This library provides a Wrapper for FTP.

- CsFtFTPSchedObjSh -- This library provides functions to use FTP at a scheduled time by the User.
- EcCfSh -- The Config library (CF) is a shared library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistrySh
- EcDcMsgPsngr1Sh -- This library consists of message passing objects used by both the client and server side.
- EcDnDirSh -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcFhSh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLocatorSh -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcNsServiceLocSh -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcPfSh -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPtSpecialLockSh -- This library provides classes for mutex operations and thread IDs.
- EcSeCmiSh -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeServerKeyMgmtSh -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbedSh -- This shared Library has only the methods for completing the successful compilation.
- EcSeUtilityCtStubbedSh -- This shared Library provides stubbed version of EcSeUtilityCt for successful compilation.
- EcTiTimeSh -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUrSh -- A Universal Reference (UR) is created as a logical reference to an extant ECS object.
- EcUtFactorySh -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtSh -- EcUt is a utility library for all the ECS applications.
- eventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.

process EclnGUI

/ecs/formal/INGEST/GUI/src/gui

Provides operations personnel with the capability, via the GUI Interface, to perform physical media ingest; to monitor the ingest history log; to monitor the status of ongoing ingest requests; to cancel an ingest request or granule; to resume suspended ingest requests or granules and to modify Ingest configuration parameters.

Classes

- IngestMW -- Parent Class that controls/drives the other four ingest GUI.
- IngestMWDerived
- InHistoryLog -- Provides History Log GUI functionality.
- InHistoryLogDerived
- InMediaIngest -- Created by Builder Xcessory Version 5.0.3.
- InMediaIngestDerived
- InOperatorTools -- Created by Builder Xcessory Version 5.0.3.
- InOperatorToolsDerived
- InReqCtrlBarGraph -- Created by Builder Xcessory Version 5.0.3.
- InReqCtrlBarGraphDerived
- InRequestController -- Created by Builder Xcessory Version 5.0.3.
- InRequestControllerDerived
- UIComponent -- Base class for all C++/Motif UI components.

Libraries Linked

- CsEmMailRelA -- This Library is used for the emails using sendmail utility and the nnpst for Bulletin board messages.
- CsSeCryptoDes -- This library contains the APIs for the DES encryption algorithm.
- DsCl -- This library contains classes which make up the Science Data Server's (SDSRV) public interface. These classes are used by clients to connect, build commands, and submit requests to the SDSRV.
- DsCn -- This library is used to access a server specific configuration file.
- DsSh -- This library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- DsStCmn -- This internal library contains the interface that the code uses to do database access and run stored procedures.
- DsStCopyD
- DsStDaemon

- DsStFtp
- DsStPull -- This library contains the server and client code for the pull cache manager.
- DsStRes -- This library provides the common functionality for all of the resource manager servers. Libraries are maintained for both SGI and Sun.
- DsStSt -- Both client and server code are contained in the library.
- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- EcPoDbRW
- EcUtHelpg_mt_eh_tp
- EcUtMisc -- This library contains miscellaneous utilities.
- GI -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.
- InConfig -- This library provides a class which is used by each Ingest executable to obtain parameters from its configuration file.
- InDBaccUt -- This library provides classes which allows access to the Ingest database.
- InGuiUt -- This library provides generic GUI capabilities.
- InMsg -- This library provides classes that are used for all data messages exchanged between the external source and Ingest.
- InResource -- This library allocates/deallocates staging disk resources.

Shared Libraries Linked

- agenteventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsFtFTPRelASh -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObjSh -- This library provides functions to use FTP at a scheduled time by the User.
- EcCfSh -- The Config library (CF) is a shared library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistrySh
- EcDcMsgPsnng1Sh -- This library consists of message passing objects used by both the client and server side.
- EcDnDirSh -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcFhSh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLocatorSh -- The Service Locator library provides an implementation independent mechanism for specifying service locations.

- EcNsServiceLocSh -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcPfSh -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPoDbRWSH
- EcPtSpecialLockSh -- This library provides classes for mutex operations and thread IDs.
- EcSeCmiSh -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeServerKeyMgmtSh -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbedSh -- This shared Library has only the methods for completing the successful compilation.
- EcSeUtilityDbStubbedSh -- This shared Library provides stubbed version of EcSeUtilityDb for successful compilation.
- EcTiTimeSh -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUrSh -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUtFactorySh -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtSh -- EcUt is a utility library for all the ECS applications.
- eventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.

process EcInReqMgr

/ecs/formal/INGEST/RequestMgr/src/Request

The EcInReqMgr is the core process which manages the ingest request traffic and the processing of the ingest requests, and the Ingest database in the event of a failure. ~ ~ ~

Classes

- InRequest -- This object class contains information provided by the requester or the external data source requesting ingest of data to ECS.
- InRequestManager -- Receive RPC from Client and create InRequest object to process the RPC Ingest request.
- InRequestMgrIF_1_0_ABS
- InRequestMgrIF_1_0_Mgr -- This class provides the interfaces from the Ingest Request Manager clients to the Request Manager.
- InRequestServer

Libraries Linked

- agentevent -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsEmMailRelA -- This Library is used for the emails using sendmail utility and the nnpst for Bulletin board messages.
- CsFtFTPRelA -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObj -- This library provides functions to use FTP at a scheduled time by the User.
- CsSeCryptoDes -- This library contains the APIs for the DES encryption algorithm.
- DsCl -- This library contains classes which make up the Science Data Server's (SDSRV) public interface. These classes are used by clients to connect, build commands, and submit requests to the SDSRV.
- DsCn -- This library is used to access a server specific configuration file.
- DsSh -- This library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- DsStCmn -- This internal library contains the interface that the code uses to do database access and run stored procedures.
- DsStCopyD
- DsStDaemon
- DsStFtp
- DsStRes -- This library provides the common functionality for all of the resource manager servers. Libraries are maintained for both SGI and Sun.
- DsStSt -- Both client and server code are contained in the library.
- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- EcCf -- The Config library (CF) is a static library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistry
- EcDcMsgPsngr1 -- This library consists of message passing objects used by both the client and server side.
- EcDnDir -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcFh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLoc -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcNsServiceLocator -- The Service Locator library provides an implementation independent mechanism for specifying service locations.

- EcPf -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPo -- The Persistent CSC provides a set of abstract and base classes for approved advertisements and requests.
- EcPoDbRW
- EcPtSpecialLock -- This library provides classes for mutex operations and thread IDs.
- EcSeCmi -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeServerKeyMgmt -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbed -- This static Library is the stubbed version of EcSeSybSecurity.
- EcSeUtilityDbStubbed -- This static Library is stub version of the EcSeUtilityDb library.
- EcTiTime -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUr -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUt -- EcUt is a utility library for all the ECS applications.
- EcUtFactory -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtMisc -- This library contains miscellaneous utilities.
- event -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- Gl -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.
- InConfig -- This library provides a class which is used by each Ingest executable to obtain parameters from its configuration file.
- InDBaccUt -- This library provides classes which allows access to the Ingest database.
- InGranuleC -- This library supports the client side of the SRF request.
- InGranuleMsg -- This library supports the messages needed for SRF to communicate between Granule Server and Request Manager.
- InMsg -- This library provides classes that are used for all data messages exchanged between the external source and Ingest.
- InResource -- This library allocates/deallocates staging disk resources.
- InRmQueue -- This library contains code for Request Managers queue.
- InUpdateUR -- This library provides the interface with Advertising to get the the UR associated with each data type.

- IoAdCore -- The CoreLib CSC provides a set of functionalities for describing a generic advertisement, parsing and validating attributes that support the ECS Core meta data model, and requesting and moderating advertisements.
- IoAdProxy -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSearch -- The SearchLib CSC provides a set of searching capabilities for approved advertisements, for the administration of groups, and for moderation of requests.
- IoAdServer -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSubs -- The SubsLib CSC provides a set of derived classes which represent different types of advertisements: products, services, and providers.
- srf -- The SRF library provides the necessary mechanism for the application to communicate asynchronously with another application.

Subsystem CLS

The Client Subsystem provides a collection of components through which users access the services and data available in EOSDIS and other systems interoperable with EOSDIS. The Client Subsystem components fall into one of the following general categories: a) An intuitive desktop manager, which manages desktop objects (files) in the user's local file space, and which represent applications and data in the domain of the client; and b) Application programs accessible through user interfaces which implement the range of functionality available in the client.

process EcCIDtInController

/ecs/formal/CLS/DESKT/src/Installer/AdvInstaller

Classes

- CInWorkstationInstall -- This class encapsulate the processing required to get the information need to know what we have to install on a workstation and it encapsulate the process of installing.

Libraries Linked

- EcUt -- EcUt is a utility library for all the ECS applications.
- EcUtFactory -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtMisc -- This library contains miscellaneous utilities.
- EcUtNoPF -- EcUtNoPF is a utility library for all the ECS applications that do not use Process Framework.
- IoAdInstallBase -- The installer allows one to install a compressed tar file containing some kind of application (modelled through a "IoAdInstallableServiceAdv") or a URL to get to a WWW service (modelled through a "IoAdMimeServiceAdv") onto a users workstation.

process EcCIDtUserProfileGateway

/ecs/formal/CLS/DESKT/src/ProfileGateway

The User Profile Gateway acts as a user profile retrieval engine for the Science User Desktop. The server listens on a socket for calls from the desktop. It also supports updates to the profile from the EOS Data Gateway.

Classes

- CIDtBuildProfile -- For getting the User Profile Information.
- CIDtIKSocket -- This class encapsulates the IK library routines in a class and removes all global variables required to operate.
- CIDtManagedServer -- Basic operation is as follows.
- CIDtProfileServer
- CIDtRequestReceiver -- This class is takes in a socket descriptor and request id and executes the contents of the socket in the Gateway and returns the resultant request on the new socket id.
- CIDtRpc_1_0
- CIDtRpc_1_0_ABS
- CIDtRpc_1_0_Mgr -- Manager class for CIDtRpc.

Libraries Linked

- agentevent -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CIDtProfileToOdl -- This library is used to read and write ODL parameters specific for the User Profile Gateway.
- CsFtFTPRelA -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObj -- This library provides functions to use FTP at a scheduled time by the User.
- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- EcCf -- The Config library (CF) is a static library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistry
- EcDcMsgPng1 -- This library consists of message passing objects used by both the client and server side.
- EcDnDir -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcFh -- This library provides fault handling capabilities to ECS applications.

- EcNsServiceLoc -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcNsServiceLocator -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcPf -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPtSpecialLock -- This library provides classes for mutex operations and thread IDs.
- EcSeCmi -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeLoginContext -- This library uses the key obtained from either the EcSeServerKeyMgmt or EcSeAuthn library to establish a login context for a process.
- EcSeServerKeyMgmt -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbed -- This static Library is the stubbed version of EcSeSybSecurity.
- EcSeUtilityCtStubbed -- This static Library is stub version of the EcSeUtilityCt library.
- EcTiTime -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUr -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUt -- EcUt is a utility library for all the ECS applications.
- EcUtFactory -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- event -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- MsAcClnt -- The Accountability Management Service makes the user profile available to the various subsystems, such as the Data Server subsystem, information such as the user's electronic mail address and the shipping address, which are used for the distribution of
- MsAcComm -- This library contains class used for both Accountability Server and Client

process EcClOdProductRequest

/ecs/formal/CLS/ODFRM/src/cgi-src

Classes

- ClOdDEMPProductRequest
- ClOdGCPOptions
- ClOdL1BProductRequest
- ClOdProductRequest

Libraries Linked

- agentevent -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- ClOdCommon
- CsEmMailRelA -- This Library is used for the emails using sendmail utility and the nnpst for Bulletin board messages.
- CsFtFTPRelA -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObj -- This library provides functions to use FTP at a scheduled time by the User.
- DpDeletionClient -- The library containing the client side operations to issue requests to the deletion server.
- DpPrDbPf -- This library contains the PDPS database interface classes for use with the Process Framework access to the database.
- DpPrDM -- This library supplies utility operations to manage data within DPS.
- DpPrDssIF -- This library contains the helper object for PDPS to interact with science data server.
- DpPrEM -- This library supplies utility operations to manage PGE execution within PRONG.
- DpPrException -- This library provides APIs to catch and handle signals.
- DpPrRM -- This library supplies utility operations to manage computer resources for PDPS.
- DpPrTools -- This library contains global utility functions.
- DsCl -- This library contains classes which make up the Science Data Server's (SDSRV) public interface. These classes are used by clients to connect, build commands, and submit requests to the SDSRV.
- DsCn -- This library is used to access a server specific configuration file.
- DsSh -- This library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- EcCf -- The Config library (CF) is a static library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistry
- EcDcMsgPsg1 -- This library consists of message passing objects used by both the client and server side.
- EcDnDir -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcDpJobMgmtClient -- The Job Management Client library provides the following public interfaces to the Job Management Server.

- EcFh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLoc -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcNsServiceLocator -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcPf -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPo -- The Persistent CSC provides a set of abstract and base classes for approved advertisements and requests.
- EcPoDbRW
- EcPtSpecialLock -- This library provides classes for mutex operations and thread IDs.
- ECSEAuthn
- EcSeCmi -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeLoginContext -- This library uses the key obtained from either the EcSeServerKeyMgmt or EcSeAuthn library to establish a login context for a process.
- EcSeServerKeyMgmt -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbed -- This static Library is the stubbed version of EcSeSybSecurity.
- EcSeUtilityCtStubbed -- This static Library is stub version of the EcSeUtilityCt library.
- EcSeUtilityDbStubbed -- This static Library is stub version of the EcSeUtilityDb library.
- EcTiTime -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUr -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUt -- EcUt is a utility library for all the ECS applications.
- EcUtFactory -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtMisc -- This library contains miscellaneous utilities.
- event -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- Gl -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.
- IoAdCore -- The CoreLib CSC provides a set of functionalities for describing a generic advertisement, parsing and validating attributes that support the ECS Core meta data model, and requesting and moderating advertisements.
- IoAdProxy -- The ServerLib CSC provides classes for process framework DCE server and client.

- IoAdSearch -- The SearchLib CSC provides a set of searching capabilities for approved advertisements, for the administration of groups, and for moderation of requests.
- IoAdServer -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSubs -- The SubsLib CSC provides a set of derived classes which represent different types of advertisements: products, services, and providers.
- MD5Encrypt
- MsAcClnt -- The Accountability Management Service makes the user profile available to the various subsystems, such as the Data Server subsystem, information such as the user's electronic mail address and the shipping address, which are used for the distribution of
- MsAcComm -- This library contains class used for both Accountability Server and Client
- PlCore1 -- This library contains the first half of Planning's core functionality. The CoreLib provides functionality for all areas of Planning. It was divided in half due to its large size...
- PlCore2 -- This library contains the second half of Planning's core functionality. The CoreLib provides functionality for all areas of Planning. It was divided in half due to its large size...
- PlOdmgrClient
- PISSIT -- This library manages the Science Software Integration & Test PDPS DB interfaces.
- PIUtil -- This library contains utilities dealing with current time, time periods, time boundaries, time windows, time intervals, spacecraft, orbit, instruments, and also manages their DB interfaces.

process EcClOdProductSelection

/ecs/formal/CLS/ODFRM/src/cgi-src

Classes

- ClOdDEMPProductSelection
- ClOdGCPOptions
- ClOdL1BProductSelection
- ClOdProductSelection

Libraries Linked

- agentevent -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- ClOdCommon
- CsEmMailRelA -- This Library is used for the emails using sendmail utility and the nnpost for Bulletin board messages.
- CsFtFTPRelA -- This library provides a Wrapper for FTP.

- CsFtFTPSchedObj -- This library provides functions to use FTP at a scheduled time by the User.
- DpDeletionClient -- The library containing the client side operations to issue requests to the deletion server.
- DpPrDbPf -- This library contains the PDPS database interface classes for use with the Process Framework access to the database.
- DpPrDM -- This library supplies utility operations to manage data within DPS.
- DpPrDssIF -- This library contains the helper object for PDPS to interact with science data server.
- DpPrEM -- This library supplies utility operations to manage PGE execution within PRONG.
- DpPrException -- This library provides APIs to catch and handle signals.
- DpPrRM -- This library supplies utility operations to manage computer resources for PDPS.
- DpPrTools -- This library contains global utility functions.
- DsCl -- This library contains classes which make up the Science Data Server's (SDSRV) public interface. These classes are used by clients to connect, build commands, and submit requests to the SDSRV.
- DsCn -- This library is used to access a server specific configuration file.
- DsSh -- This library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- EcCf -- The Config library (CF) is a static library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistry
- EcDcMsgPsnng1 -- This library consists of message passing objects used by both the client and server side.
- EcDnDir -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcDpJobMgmtClient -- The Job Management Client library provides the following public interfaces to the Job Management Server.
- EcFh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLoc -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcNsServiceLocator -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcPf -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.

- EcPo -- The Persistent CSC provides a set of abstract and base classes for approved advertisements and requests.
- EcPoDbRW
- EcPtSpecialLock -- This library provides classes for mutex operations and thread IDs.
- ECSAuthn
- EcSeCmi -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeLoginContext -- This library uses the key obtained from either the EcSeServerKeyMgmt or EcSeAuthn library to establish a login context for a process.
- EcSeServerKeyMgmt -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbed -- This static Library is the stubbed version of EcSeSybSecurity.
- EcSeUtilityCtStubbed -- This static Library is stub version of the EcSeUtilityCt library.
- EcSeUtilityDbStubbed -- This static Library is stub version of the EcSeUtilityDb library.
- EcTiTime -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUr -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUt -- EcUt is a utility library for all the ECS applications.
- EcUtFactory -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtMisc -- This library contains miscellaneous utilities.
- event -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- Gl -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.
- IoAdCore -- The CoreLib CSC provides a set of functionalities for describing a generic advertisement, parsing and validating attributes that support the ECS Core meta data model, and requesting and moderating advertisements.
- IoAdProxy -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSearch -- The SearchLib CSC provides a set of searching capabilities for approved advertisements, for the administration of groups, and for moderation of requests.
- IoAdServer -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSubs -- The SubsLib CSC provides a set of derived classes which represent different types of advertisements: products, services, and providers.
- MD5Encrypt

- MsAcClnt -- The Accountability Management Service makes the user profile available to the various subsystems, such as the Data Server subsystem, information such as the user's electronic mail address and the shipping address, which are used for the distribution of
- MsAcComm -- This library contains class used for both Accountability Server and Client
- PlCore1 -- This library contains the first half of Planning's core functionality. The CoreLib provides functionality for all areas of Planning. It was divided in half due to its large size...
- PlCore2 -- This library contains the second half of Planning's core functionality. The CoreLib provides functionality for all areas of Planning. It was divided in half due to its large size...
- PlOdMgrClient
- PISSIT -- This library manages the Science Software Integration & Test PDPS DB interfaces.
- PIUtil -- This library contains utilities dealing with current time, time periods, time boundaries, time windows, time intervals, spacecraft, orbit, instruments, and also manages their DB interfaces.

process EcClOdUserLogin

/ecs/formal/CLS/ODFRM/src/cgi-src

Classes

- ClOdUserLogin

Libraries Linked

- agentevent -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- ClOdCommon
- CsEmMailRelA -- This Library is used for the emails using sendmail utility and the nnpst for Bulletin board messages.
- CsFtFTPRelA -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObj -- This library provides functions to use FTP at a scheduled time by the User.
- DpDeletionClient -- The library containing the client side operations to issue requests to the deletion server.
- DpPrDbPf -- This library contains the PDPS database interface classes for use with the Process Framework access to the database.
- DpPrDM -- This library supplies utility operations to manage data within DPS.
- DpPrDssIF -- This library contains the helper object for PDPS to interact with science data server.
- DpPrEM -- This library supplies utility operations to manage PGE execution within PRONG.
- DpPrException -- This library provides APIs to catch and handle signals.

- DpPrRM -- This library supplies utility operations to manage computer resources for PDPS.
- DpPrTools -- This library contains global utility functions.
- DsCl -- This library contains classes which make up the Science Data Server's (SDSRV) public interface. These classes are used by clients to connect, build commands, and submit requests to the SDSRV.
- DsCn -- This library is used to access a server specific configuration file.
- DsSh -- This library provides underlying DCE(ODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- EcCf -- The Config library (CF) is a static library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistry
- EcDcMsgPngl -- This library consists of message passing objects used by both the client and server side.
- EcDnDir -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcDpJobMgmtClient -- The Job Management Client library provides the following public interfaces to the Job Management Server.
- EcFh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLoc -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcNsServiceLocator -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcPf -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPo -- The Persistent CSC provides a set of abstract and base classes for approved advertisements and requests.
- EcPoDbRW
- EcPtSpecialLock -- This library provides classes for mutex operations and thread IDs.
- ECSAuthn
- EcSeCmi -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeLoginContext -- This library uses the key obtained from either the EcSeServerKeyMgmt or EcSeAuthn library to establish a login context for a process.
- EcSeServerKeyMgmt -- This library provides a mechanism for servers to read their DCE login key from a keytab file.

- EcSeSybSecurityStubbed -- This static Library is the stubbed version of EcSeSybSecurity.
- EcSeUtilityCtStubbed -- This static Library is stub version of the EcSeUtilityCt library.
- EcSeUtilityDbStubbed -- This static Library is stub version of the EcSeUtilityDb library.
- EcTiTime -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUr -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUt -- EcUt is a utility library for all the ECS applications.
- EcUtFactory -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtMisc -- This library contains miscellaneous utilities.
- event -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- Gl -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.
- IoAdCore -- The CoreLib CSC provides a set of functionalities for describing a generic advertisement, parsing and validating attributes that support the ECS Core meta data model, and requesting and moderating advertisements.
- IoAdProxy -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSearch -- The SearchLib CSC provides a set of searching capabilities for approved advertisements, for the administration of groups, and for moderation of requests.
- IoAdServer -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSubs -- The SubsLib CSC provides a set of derived classes which represent different types of advertisements: products, services, and providers.
- MD5Encrypt
- MsAcClnt -- The Accountability Management Service makes the user profile available to the various subsystems, such as the Data Server subsystem, information such as the user's electronic mail address and the shipping address, which are used for the distribution of
- MsAcComm -- This library contains class used for both Accountability Server and Client
- PICore1 -- This library contains the first half of Planning's core functionality. The CoreLib provides functionality for all areas of Planning. It was divided in half due to its large size...
- PICore2 -- This library contains the second half of Planning's core functionality. The CoreLib provides functionality for all areas of Planning. It was divided in half due to its large size...
- PIODMgrClient
- PISSIT -- This library manages the Science Software Integration & Test PDPS DB interfaces.

- PIUtil -- This library contains utilities dealing with current time, time periods, time boundaries, time windows, time intervals, spacecraft, orbit, instruments, and also manages their DB interfaces.

process EcCIWbFoliodProxyServer

/ecs/formal/CLS/WKBCH/FoliodProxy

Classes

- CIWbFoliodProxyServer

Libraries Linked

- agentevent -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsFtFTPReIA -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObj -- This library provides functions to use FTP at a scheduled time by the User.
- DsSh -- This library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- EcCf -- The Config library (CF) is a static library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistry
- EcDcMsgPsgn1 -- This library consists of message passing objects used by both the client and server side.
- EcDnDir -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcFh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLoc -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcNsServiceLocator -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcPf -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPoDbRW
- EcPtSpecialLock -- This library provides classes for mutex operations and thread IDs.
- EcSeCmi -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).

- EcSeServerKeyMgmt -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbed -- This static Library is the stubbed version of EcSeSybSecurity.
- EcSeUtilityDbStubbed -- This static Library is stub version of the EcSeUtilityDb library.
- EcTiTime -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUr -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUt -- EcUt is a utility library for all the ECS applications.
- EcUtFactory -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- event -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.

process EcCIWbJessProxyServer

/ecs/formal/CLS/WKBCH/JessProxy

Classes

- EcCIWbJessProxyServer

Libraries Linked

- agentevent -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsFtFTPReLA -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObj -- This library provides functions to use FTP at a scheduled time by the User.
- DsSh -- This library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- EcCf -- The Config library (CF) is a static library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistry
- EcDcMsgPsg1 -- This library consists of message passing objects used by both the client and server side.
- EcDnDir -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcFh -- This library provides fault handling capabilities to ECS applications.

- EcNsServiceLoc -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcNsServiceLocator -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcPf -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPoDbRW
- EcPtSpecialLock -- This library provides classes for mutex operations and thread IDs.
- EcSeCmi -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeServerKeyMgmt -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbed -- This static Library is the stubbed version of EcSeSybSecurity.
- EcSeUtilityDbStubbed -- This static Library is stub version of the EcSeUtilityDb library.
- EcTiTime -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUr -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUt -- EcUt is a utility library for all the ECS applications.
- EcUtFactory -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- event -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.

process EcCIWbJtFolindex

/ecs/formal/CLS/WKBCH/CIWbMp/foliod

Libraries Linked

- CIWbJtFolioUtils

process EcCIWbJtFoliod

/ecs/formal/CLS/WKBCH/CIWbMp/foliod

Libraries Linked

- CIWbJtFolioUtils

process EcCIWbJtMapMaker

/ecs/formal/CLS/WKBCH/CIWbMp/mapmaker

Libraries Linked

- CIWbJtdb
- CIWbJtFolioUtils
- CIWbJtgd
- CIWbJtMap
- CIWbJtProjections

process EcCIWbUr

/ecs/formal/CLS/WKBCH/URT

This is the CGI script that displays the User Registration input form to the user. It uses an HTML template to dynamically generate the form.

Classes

- CIWbUrAddress -- This class provides a base for three different types of addresses - Mailing, Billing, and Shipping.
- CIWbUrProfile -- A profile display object contains user info, affiliation, mailing, billing, and shipping addresses.
- CIWbUrRequest -- A request display object contains user info, affiliation, and mailing address.
- CIWbUrUserInfo -- This class provides a base for request and profile objects.

Libraries Linked

- agentevent -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsFtFTPRelA -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObj -- This library provides functions to use FTP at a scheduled time by the User.
- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- EcCf -- The Config library (CF) is a static library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCIWbCgiVar -- This library contains utilities to read HTML templates and build HTML pages from the templates.
- EcCsRegistry
- EcDcMsgPsgn1 -- This library consists of message passing objects used by both the client and server side.

- EcDnDir -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcFh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLoc -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcNsServiceLocator -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcPf -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPoDbRW
- EcPtSpecialLock -- This library provides classes for mutex operations and thread IDs.
- EcSeCmi -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeServerKeyMgmt -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbed -- This static Library is the stubbed version of EcSeSybSecurity.
- EcSeUtilityDbStubbed -- This static Library is stub version of the EcSeUtilityDb library.
- EcTiTime -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUr -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUt -- EcUt is a utility library for all the ECS applications.
- EcUtFactory -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- event -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- MsAcClnt -- The Accountability Management Service makes the user profile available to the various subsystems, such as the Data Server subsystem, information such as the user's electronic mail address and the shipping address, which are used for the distribution of
- MsAcComm -- This library contains class used for both Accountability Server and Client

process EcCIWbUrConfirm

/ecs/formal/CLS/WKBCH/URT

This is the CGI script that displays the User Reservation confirmation screen.

Classes

- CIWbUrAddress -- This class provides a base for three different types of addresses - Mailing, Billing, and Shipping.

- CIWbUrProfile -- A profile display object contains user info, affiliation, mailing, billing, and shipping addresses.
- CIWbUrRequest -- A request display object contains user info, affiliation, and mailing address.
- CIWbUrUserInfo -- This class provides a base for request and profile objects.

Libraries Linked

- agentevent -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsFtFTPRelA -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObj -- This library provides functions to use FTP at a scheduled time by the User.
- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- EcCf -- The Config library (CF) is a static library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCIWbCgiVar -- This library contains utilities to read HTML templates and build HTML pages from the templates.
- EcCsRegistry
- EcDcMsgPsng1 -- This library consists of message passing objects used by both the client and server side.
- EcDnDir -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcFh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLoc -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcNsServiceLocator -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcPf -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPoDbRW
- EcPtSpecialLock -- This library provides classes for mutex operations and thread IDs.
- EcSeCmi -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeServerKeyMgmt -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbed -- This static Library is the stubbed version of EcSeSybSecurity.

- EcSeUtilityDbStubbed -- This static Library is stub version of the EcSeUtilityDb library.
- EcTiTime -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUr -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUt -- EcUt is a utility library for all the ECS applications.
- EcUtFactory -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- event -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- MsAcClnt -- The Accountability Management Service makes the user profile available to the various subsystems, such as the Data Server subsystem, information such as the user's electronic mail address and the shipping address, which are used for the distribution of
- MsAcComm -- This library contains class used for both Accountability Server and Client

process EcCIWbUrSubmit

/ecs/formal/CLS/WKBCH/URT

This is the CGI script that displays the User Registration submission screen.

Classes

- CIWbUrAddress -- This class provides a base for three different types of addresses - Mailing, Billing, and Shipping.
- CIWbUrProfile -- A profile display object contains user info, affiliation, mailing, billing, and shipping addresses.
- CIWbUrRequest -- A request display object contains user info, affiliation, and mailing address.
- CIWbUrUserInfo -- This class provides a base for request and profile objects.

Libraries Linked

- agentevent -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsFtFTPRelA -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObj -- This library provides functions to use FTP at a scheduled time by the User.
- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- EcCf -- The Config library (CF) is a static library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.

- EcCIWbCgiVar -- This library contains utilities to read HTML templates and build HTML pages from the templates.
- EcCsRegistry
- EcDcMsgPsngr1 -- This library consists of message passing objects used by both the client and server side.
- EcDnDir -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcFh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLoc -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcNsServiceLocator -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcPf -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPoDbRW
- EcPtSpecialLock -- This library provides classes for mutex operations and thread IDs.
- EcSeCmi -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeServerKeyMgmt -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbed -- This static Library is the stubbed version of EcSeSybSecurity.
- EcSeUtilityDbStubbed -- This static Library is stub version of the EcSeUtilityDb library.
- EcTiTime -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUr -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUt -- EcUt is a utility library for all the ECS applications.
- EcUtFactory -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- event -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- MsAcClnt -- The Accountability Management Service makes the user profile available to the various subsystems, such as the Data Server subsystem, information such as the user's electronic mail address and the shipping address, which are used for the distribution of
- MsAcComm -- This library contains class used for both Accountability Server and Client

script EcCIDtInInstaller

/ecs/formal/CLS/DESKT/src/Installer/InstallerScript

The ECS Installer program downloads and installs the Service/Product that a user has chosen for installation. The Installer script takes a set of options and values as arguments. The required options and values are the input that the user gives in the advertisement form.

script startEcCIDtUserProfileGateway

/ecs/formal/CLS/DESKT/src/ProfileGateway

This is the script to start up CLS User Profile Gateway server.

Subsystem DMS

The Data Management Subsystem (DMS) receives service request (to search the inventory or directory databases, to browse search results or to order data) from a user's client (i.e., a GUI), translates it from ODL to ECS formats, forwards it to the SDSRV and vice versa.

process EcDmAsterToEcsGateway

/ecs/formal/DM/ASTGW/src/AsterToEcsGateway

Classes

- DmAsGwAsterReqRcvr -- This class is takes in a socket descriptor and request id and executes the contents of the socket in the Gateway and returns the resultant request on the new socket id.
- DmAsGwIKSocket -- This class encapsulates the IK library routines in a class and removes all global variables required to operate.
- DmAsGwMngdSrvr -- This class is the AsterGateway server class built on the top of process framework managed server class.

Libraries Linked

- agentevent -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- Common -- This library contains classes for the EcsToV0Server and V0ToEcsServer executables.
- CsFtFTPReIA -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObj -- This library provides functions to use FTP at a scheduled time by the User.
- DmAsGwAsterReqProc -- The lib_DmAsGwAsterReqProc library contains classes for processing ASTER to ECS requests.
- DmAsGwCommon -- The DmAsGwCommon library contains utility classes and term definitions used by the Aster Gateway.

- DmAsGwEcsReqProc -- The DmAsGwEcsReqProc library contains classes for all the ECS to ASTER request processing.
- DmGwV0If -- The DmGwV0If library contains classes for all the ECS to V0 request processing.
- DmGwV0Util -- The DmGwV0Util library contains the implementation of functions used by the ECS to V0 Gateway for client/server interfaces.
- DmLmAsterIfFactory -- The DmLmAsterIfFactory library contains classes that create the correct type of external interface used by the LIMGR to access external interfaces.
- DmLmDbi -- The DmLmDbi library contains utilities for interfacing and connecting with the DDICT database.
- DmLmExtIf -- The DmLmExtIf library contains classes that allow the LIMGR to interface with external information managers.
- DmLmGlobal -- The global CSC provides classes for DM subsystem to handle the global variables.
- DmLmInfoMgrFactory -- The DmLmInfoMgrFactory library contains classes that create the correct type of external interface used by the LIMGR to access external interfaces.
- DmLmMapper -- The DmLmMapper library contain a class used to map client attribute names to science data server attribute names and map ECS attribute names and values to VO attribute names and values.
- DmLmMsg -- The msg CSC provides classes for DM subsystem server and client.
- DmLmReqProc -- The reqproc CSC provides classes for DM subsystem server.
- DsCn -- This library is used to access a server specific configuration file.
- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- EcCf -- The Config library (CF) is a static library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistry
- EcDcMsgPsnng1 -- This library consists of message passing objects used by both the client and server side.
- EcDmLmClient
- EcDnDir -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcFh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLoc -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcNsServiceLocator -- The Service Locator library provides an implementation independent mechanism for specifying service locations.

- EcPf -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPoDbRW
- EcPtSpecialLock -- This library provides classes for mutex operations and thread IDs.
- EcSeCmi -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeLoginContext -- This library uses the key obtained from either the EcSeServerKeyMgmt or EcSeAuthn library to establish a login context for a process.
- EcSeServerKeyMgmt -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbed -- This static Library is the stubbed version of EcSeSybSecurity.
- EcSeUtilityDbStubbed -- This static Library is stub version of the EcSeUtilityDb library.
- EcTiTime -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUr -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUt -- EcUt is a utility library for all the ECS applications.
- EcUtFactory -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- event -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- Persistant
- RequestProcessing
- srf -- The SRF library provides the necessary mechansim for the application to communicate asynchronously with another application.

Shared Libraries Linked

- DsClSh -- This library contains classes which make up the Science Data Server's (SDSRV) public interface. These classes are used by clients to connect,build commands, and submit requests to the SDSRV.
- DsCnSh -- This library was used to generate files which install ESDT configuration information for each ESDT previously.
- DsShSh -- This internal library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- EcPoDbRWSh
- EcPoSh -- The Persistent CSC provides a set of abstract and base classes for approved advertisements and requests.
- EcUtMiscSh -- The EcUtMisc library contains miscellaneous utilities.

- GISH -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.
- IoAdCoreSh -- The CoreLib CSC provides a set of functionalities for describing a generic advertisement, parsing and validating attributes that support the ECS Core meta data model, and requesting and moderating advertisements.
- IoAdProxySh -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSearchSh -- The SearchLib CSC provides a set of searching capabilities for approved advertisements, for the administration of groups, and for moderation of requests.
- IoAdServerSh -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSubsSh -- The SubsLib CSC provides a set of derived classes which represent different types of advertisements: products, services, and providers.
- MsAcClntSh -- The Accountability Management Service makes the user profile available to the various subsystems, such as the Data Server subsystem, information such as the user's electronic mail address and the shipping address, which are used for the distribution of
- MsAcCommSh -- This library contains class used for both Accountability Server and Client

process EcDmDictServer

/ecs/formal/DM/DDICT/src/ddserver

The Data Dictionary Server is the primary server interface to collection and collection related information for the DMS and other subsystems. It allows DDICT client processes the capability to perform data searches, insertions, updates, or deletions to the collection information held in the DDICT database.

The Data Dictionary offers two basic interfaces:

- * DDICT Data Search: The Data Dictionary Server allows a user to specify search requests on the Data Dictionary database using a GIParameterList.
- * DDICT Data Insert and Delete: Provides a client process with the capability to insert and delete data within the Data Dictionary database.

The Data Dictionary Server supports:

- * Single requests at a time
- * Synchronous request processing
- * Asynchronous request processing

Libraries Linked

- agentevent -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsFtFTPRelA -- This library provides a Wrapper for FTP.

- CsFtFTPSchedObj -- This library provides functions to use FTP at a scheduled time by the User.
- DsCl -- This library contains classes which make up the Science Data Server's (SDSRV) public interface. These classes are used by clients to connect, build commands, and submit requests to the SDSRV.
- DsCn -- This library is used to access a server specific configuration file.
- DsSh -- This library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- EcCf -- The Config library (CF) is a static library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistry
- EcDcMsgPsgn1 -- This library consists of message passing objects used by both the client and server side.
- EcDnDir -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcFh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLoc -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcNsServiceLocator -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcPf -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPoDbRW
- EcPtSpecialLock -- This library provides classes for mutex operations and thread IDs.
- EcSeCmi -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeServerKeyMgmt -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbed -- This static Library is the stubbed version of EcSeSybSecurity.
- EcSeUtilityDbStubbed -- This static Library is stub version of the EcSeUtilityDb library.
- EcTiTime -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUr -- A Universal Reference (UR) is created as a logical reference to an extant ECS object.
- EcUt -- EcUt is a utility library for all the ECS applications.

- EcUtFactory -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- event -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- Gl -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.
- srf -- The SRF library provides the necessary mechansim for the application to communicate asynchronously with another application.

process EcDmEcsToAsterGateway

/ecs/formal/DM/ASTGW/src/EcsToAsterGateway

Libraries Linked

- agentevent -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- Common -- This library contains classes for the EcsToV0Server and V0ToEcsServer executables.
- CsFtFTPReLA -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObj -- This library provides functions to use FTP at a scheduled time by the User.
- DmAsGwCommon -- The DmAsGwCommon library contains utility classes and term definitions used by the Aster Gateway.
- DmAsGwEcsReqProc -- The DmAsGwEcsReqProc library contains classes for all the ECS to ASTER request processing.
- DmGwV0If -- The DmGwV0If library contains classes for all the ECS to V0 request processing.
- DmGwV0Util -- The DmGwV0Util library contains the implementation of functions used by the ECS to V0 Gateway for client/server interfaces.
- DmLmDbi -- The DmLmDbi library contains utilities for interfacing and connecting with the DDICT database.
- DmLmExtIf -- The DmLmExtIf library contains classes that allow the LIMGR to interface with external information managers.
- DmLmGlobal -- The global CSC provides classes for DM subsystem to handle the global variables.
- DmLmMsg -- The msg CSC provides classes for DM subsystem server and client.
- DsCn -- This library is used to access a server specific configuration file.
- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.

- EcCf -- The Config library (CF) is a static library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistry
- EcDcMsgPsnng1 -- This library consists of message passing objects used by both the client and server side.
- EcDmLmClient
- EcDnDir -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcFh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLoc -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcNsServiceLocator -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcPf -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPoDbRW
- EcPtSpecialLock -- This library provides classes for mutex operations and thread IDs.
- EcSeCmi -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeLoginContext -- This library uses the key obtained from either the EcSeServerKeyMgmt or EcSeAuthn library to establish a login context for a process.
- EcSeServerKeyMgmt -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbed -- This static Library is the stubbed version of EcSeSybSecurity.
- EcSeUtilityDbStubbed -- This static Library is stub version of the EcSeUtilityDb library.
- EcTiTime -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUr -- A Universal Reference (UR) is created as a logical reference to an extant ECS object.
- EcUt -- EcUt is a utility library for all the ECS applications.
- EcUtFactory -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- event -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- Persistent
- RequestProcessing

- srf -- The SRF library provides the necessary mechanism for the application to communicate asynchronously with another application.

Shared Libraries Linked

- DsClSh -- This library contains classes which make up the Science Data Server's (SDSRV) public interface. These classes are used by clients to connect, build commands, and submit requests to the SDSRV.
- DsCnSh -- This library was used to generate files which install ESDT configuration information for each ESDT previously.
- DsShSh -- This internal library provides underlying DCE(ODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- EcPoDbRWSH
- EcPoSh -- The Persistent CSC provides a set of abstract and base classes for approved advertisements and requests.
- EcUtMiscSh -- The EcUtMisc library contains miscellaneous utilities.
- GlSh -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.
- IoAdCoreSh -- The CoreLib CSC provides a set of functionalities for describing a generic advertisement, parsing and validating attributes that support the ECS Core meta data model, and requesting and moderating advertisements.
- IoAdProxySh -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSearchSh -- The SearchLib CSC provides a set of searching capabilities for approved advertisements, for the administration of groups, and for moderation of requests.
- IoAdServerSh -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSubsSh -- The SubsLib CSC provides a set of derived classes which represent different types of advertisements: products, services, and providers.
- MsAcClntSh -- The Accountability Management Service makes the user profile available to the various subsystems, such as the Data Server subsystem, information such as the user's electronic mail address and the shipping address, which are used for the distribution of
- MsAcCommSh -- This library contains class used for both Accountability Server and Client

process EcDmEcsToV0Gateway

/ecs/formal/DM/GatewayCSCI/src/EcsToV0Server

The ECS to V0 Gateway server allows users to search for data and request data in the V0 IMS data archive and request services of the V0 IMS.

Major Interfaces:

- * **Inventory Search:** The ECS to V0 Gateway allows requesters to perform searches for data granules within the V0 IMS archive.
- * **Browse:** Allows users to browse data granules previously found during a search.
- * **Acquire:** Provides the capability for requesters to submit data acquire requests for obtaining billing and accounting information from the V0 IMS.

Server Supports:

- * Synchronous request processing
- * Asynchronous request processing
- * Multiple concurrent requests

Classes

- **DmGwManagedServer** -- This is an example how an application can use Process Frame Work to create a managed server.

Libraries Linked

- **agentevent** -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- **Common** -- This library contains classes for the EcsToV0Server and V0ToEcsServer executables.
- **CsFtFTPReIA** -- This library provides a Wrapper for FTP.
- **CsFtFTPSchedObj** -- This library provides functions to use FTP at a scheduled time by the User.
- **DmGwV0If** -- The DmGwV0If library contains classes for all the ECS to V0 request processing.
- **DmGwV0Util** -- The DmGwV0Util library contains the implementation of functions used by the ECS to V0 Gateway for client/server interfaces.
- **DmLmDbi** -- The DmLmDbi library contains utilities for interfacing and connecting with the DDICT database.
- **DmLmExtIf** -- The DmLmExtIf library contains classes that allow the LIMGR to interface with external information managers.
- **DmLmMapper** -- The DmLmMapper library contain a class used to map client attribute names to science data server attribute names and map ECS attribute names and values to V0 attribute names and values.
- **DmLmMsg** -- The msg CSC provides classes for DM subsystem server and client.
- **DmLmReqProc** -- The reqproc CSC provides classes for DM subsystem server.
- **DmLmV0IfFactory** -- The DmLmV0IfFactory library contains classes that create the correct type of external interface used by the LIMGR to access external interfaces.

- DsCn -- This library is used to access a server specific configuration file.
- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- EcCf -- The Config library (CF) is a static library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistry
- EcDcMsgPsnng1 -- This library consists of message passing objects used by both the client and server side.
- EcDmLmLimServer -- The server CSC provides classes for DM subsystem servers, it contains classes for making LIM server.
- EcDnDir -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcFh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLoc -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcNsServiceLocator -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcPf -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPoDbRW
- EcPtSpecialLock -- This library provides classes for mutex operations and thread IDs.
- EcSeCmi -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeLoginContext -- This library uses the key obtained from either the EcSeServerKeyMgmt or EcSeAuthn library to establish a login context for a process.
- EcSeServerKeyMgmt -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbed -- This static Library is the stubbed version of EcSeSybSecurity.
- EcSeUtilityDbStubbed -- This static Library is stub version of the EcSeUtilityDb library.
- EcTiTime -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUr -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUt -- EcUt is a utility library for all the ECS applications.
- EcUtFactory -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- event -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.

- MsAcClnt -- The Accountability Management Service makes the user profile available to the various subsystems, such as the Data Server subsystem, information such as the user's electronic mail address and the shipping address, which are used for the distribution of
- MsAcComm -- This library contains class used for both Accountability Server and Client
- srf -- The SRF library provides the necessary mechanism for the application to communicate asynchronously with another application.

Shared Libraries Linked

- DmLmGlobalSh -- The global CSC provides classes for DM subsystem to handle the global variables.
- DsClSh -- This library contains classes which make up the Science Data Server's (SDSRV) public interface. These classes are used by clients to connect, build commands, and submit requests to the SDSRV.
- DsCnSh -- This library was used to generate files which install ESDT configuration information for each ESDT previously.
- DsShSh -- This internal library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- EcPoDbRWSH
- EcPoSh -- The Persistent CSC provides a set of abstract and base classes for approved advertisements and requests.
- EcUtMiscSh -- The EcUtMisc library contains miscellaneous utilities.
- GlSh -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.
- IoAdCoreSh -- The CoreLib CSC provides a set of functionalities for describing a generic advertisement, parsing and validating attributes that support the ECS Core meta data model, and requesting and moderating advertisements.
- IoAdProxySh -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSearchSh -- The SearchLib CSC provides a set of searching capabilities for approved advertisements, for the administration of groups, and for moderation of requests.
- IoAdServerSh -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSubsSh -- The SubsLib CSC provides a set of derived classes which represent different types of advertisements: products, services, and providers.
- MsAcClntSh -- The Accountability Management Service makes the user profile available to the various subsystems, such as the Data Server subsystem, information such as the user's electronic mail address and the shipping address, which are used for the distribution of
- MsAcCommSh -- This library contains class used for both Accountability Server and Client

process EcDmLimServer

/ecs/formal/DM/LIMGR/src/server

The EcDmLimServer receives acquire requests from the EcDmV0ToEcsGateway, translates it, and forwards it to the local EcDsScienceDataServer or the EcDmEcsToV0Gateway. The EcDmLimServer determines where to send the data types requested and queries the EcDmDictServer to find the server to contact. The results received from the local EcDmV0ToEcsGateway or EcDsScienceDataServer are translated appropriately and returned to the requester.

Major Interfaces:

- * Product request: Provides the capability for client processes to submit data acquire requests for obtaining data granules.
- * The EcDmLimServer supports synchronous request processing, asynchronous request processing, and multiple concurrent requests.

Libraries Linked

- agentevent -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsFtFTPRelA -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObj -- This library provides functions to use FTP at a scheduled time by the User.
- DmLmDbi -- The DmLmDbi library contains utilities for interfacing and connecting with the DDICT database.
- DmLmExtIf -- The DmLmExtIf library contains classes that allow the LIMGR to interface with external information managers.
- DmLmGlobal -- The global CSC provides classes for DM subsystem to handle the global variables.
- DmLmInfoMgrFactory -- The DmLmInfoMgrFactory library contains classes that create the correct type of external interface used by the LIMGR to access external interfaces.
- DmLmMapper -- The DmLmMapper library contain a class used to map client attribute names to science data server attribute names and map ECS attribute names and values to VO attribute names and values.
- DmLmMsg -- The msg CSC provides classes for DM subsystem server and client.
- DmLmReqProc -- The reqproc CSC provides classes for DM subsystem server.
- DsCl -- This library contains classes which make up the Science Data Server's (SDSRV) public interface. These classes are used by clients to connect, build commands, and submit requests to the SDSRV.
- DsCn -- This library is used to access a server specific configuration file.
- DsSh -- This library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.

- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- EcCf -- The Config library (CF) is a static library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistry
- EcDcMsgPsng1 -- This library consists of message passing objects used by both the client and server side.
- EcDmLmClient
- EcDmLmLimServer -- The server CSC provides classes for DM subsystem servers, it contains classes for making LIM server.
- EcDnDir -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcFh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLoc -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcNsServiceLocator -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcPf -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPo -- The Persistent CSC provides a set of abstract and base classes for approved advertisements and requests.
- EcPoDbRW
- EcPtSpecialLock -- This library provides classes for mutex operations and thread IDs.
- EcSeCmi -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeServerKeyMgmt -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbed -- This static Library is the stubbed version of EcSeSybSecurity.
- EcSeUtilityDbStubbed -- This static Library is stub version of the EcSeUtilityDb library.
- EcTiTime -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUr -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUt -- EcUt is a utility library for all the ECS applications.
- EcUtFactory -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtMisc -- This library contains miscellaneous utilities.

- event -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- GI -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.
- IoAdCore -- The CoreLib CSC provides a set of functionalities for describing a generic advertisement, parsing and validating attributes that support the ECS Core meta data model, and requesting and moderating advertisements.
- IoAdProxy -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSearch -- The SearchLib CSC provides a set of searching capabilities for approved advertisements, for the administration of groups, and for moderation of requests.
- IoAdServer -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSubs -- The SubsLib CSC provides a set of derived classes which represent different types of advertisements: products, services, and providers.
- MsAcCInt -- The Accountability Management Service makes the user profile available to the various subsystems, such as the Data Server subsystem, information such as the user's electronic mail address and the shipping address, which are used for the distribution of
- MsAcComm -- This library contains class used for both Accountability Server and Client
- srf -- The SRF library provides the necessary mechanism for the application to communicate asynchronously with another application.

process EcDmV0ToEcsGateway

/ecs/formal/DM/GatewayCSCI/src/ProgFrame

The EcDmV0ToEcsGateway program runs the V0 Gateway server. This program initializes the ManagedServer class which listens for new requests over the socket. If a request comes in, a thread is spawned and the RequestReceiver class is instantiated. This class checks authentication and determines the type of request to be processed.

Libraries Linked

- agentevent -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- Common -- This library contains classes for the EcsToV0Server and V0ToEcsServer executables.
- CsFtFTPRelA -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObj -- This library provides functions to use FTP at a scheduled time by the User.
- DmAsGwCommon -- The DmAsGwCommon library contains utility classes and term definitions used by the Aster Gateway.

- DmAsGwEcsReqProc -- The DmAsGwEcsReqProc library contains classes for all the ECS to ASTER request processing.
- DmGwV0Util -- The DmGwV0Util library contains the implementation of functions used by the ECS to V0 Gateway for client/server interfaces.
- DmLmDbi -- The DmLmDbi library contains utilities for interfacing and connecting with the DDICT database.
- DmLmExtIf -- The DmLmExtIf library contains classes that allow the LIMGR to interface with external information managers.
- DmLmGlobal -- The global CSC provides classes for DM subsystem to handle the global variables.
- DmLmMsg -- The msg CSC provides classes for DM subsystem server and client.
- DsCn -- This library is used to access a server specific configuration file.
- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- EcCf -- The Config library (CF) is a static library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistry
- EcDcMsgPsngr1 -- This library consists of message passing objects used by both the client and server side.
- EcDmLmClient
- EcDnDir -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcFh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLoc -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcNsServiceLocator -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcPf -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPoDbRW
- EcPtSpecialLock -- This library provides classes for mutex operations and thread IDs.
- EcSeCmi -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeLoginContext -- This library uses the key obtained from either the EcSeServerKeyMgmt or EcSeAuthn library to establish a login context for a process.
- EcSeServerKeyMgmt -- This library provides a mechanism for servers to read their DCE login key from a keytab file.

- EcSeSybSecurityStubbed -- This static Library is the stubbed version of EcSeSybSecurity.
- EcSeUtilityDbStubbed -- This static Library is stub version of the EcSeUtilityDb library.
- EcTiTime -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUr -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUt -- EcUt is a utility library for all the ECS applications.
- EcUtFactory -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- event -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- Persistent
- RequestProcessing
- srf -- The SRF library provides the necessary mechansim for the application to communicate asynchronously with another application.

Shared Libraries Linked

- DsClSh -- This library contains classes which make up the Science Data Server's (SDSRV) public interface. These classes are used by clients to connect,build commands, and submit requests to the SDSRV.
- DsCnSh -- This library was used to generate files which install ESDT configuration information for each ESDT previously.
- DsShSh -- This internal library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- EcPoDbRWSH
- EcPoSh -- The Persistent CSC provides a set of abstract and base classes for approved advertisements and requests.
- EcUtMiscSh -- The EcUtMisc library contains miscellaneous utilities.
- GlSh -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.
- IoAdCoreSh -- The CoreLib CSC provides a set of functionalities for describing a generic advertisement, parsing and validating attributes that support the ECS Core meta data model, and requesting and moderating advertisements.
- IoAdProxySh -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSearchSh -- The SearchLib CSC provides a set of searching capabilities for approved advertisements, for the administration of groups, and for moderation of requests.
- IoAdServerSh -- The ServerLib CSC provides classes for process framework DCE server and client.

- IoAdSubsSh -- The SubsLib CSC provides a set of derived classes which represent different types of advertisements: products, services, and providers.
- MsAcClntSh -- The Accountability Management Service makes the user profile available to the various subsystems, such as the Data Server subsystem, information such as the user's electronic mail address and the shipping address, which are used for the distribution of
- MsAcCommSh -- This library contains class used for both Accountability Server and Client

script EcDmDictServerRun

/ecs/formal/DM/B0DDICT/src/ddserver

script EcDmV0ToEcsPing

/ecs/formal/DM/GatewayCSCI/src/ProgFrame

script EcDmV0ToEcsRun

/ecs/formal/DM/GatewayCSCI/src/ProgFrame

Subsystem IOS

The Interoperability Subsystem(IOS) receives advertising information from ECS and non-ECS service providers, and provides interfaces for users to access to the advertising information.

process EcloAdServer

/ecs/formal/IOS/AdvService/src/Server

The Advertising Server is used for searching, inserting, deleting and updating various types of advertisements. The Advertising server uses a relational DBMS server (Sybase) for persistent storage of the advertisements. The Sybase server is shared with the DMS software configuration items.

The Advertising Service offers two basic interfaces

- * Advertising Search: The Advertising Server allows a user to specify search requests on the Advertising database. Searches include searches for data, signature service and subscription event advertisements.
- * Advertisement Insert and Delete: Provides a user with the capability to insert and delete advertisements within the Advertising database.

The Advertising Server supports:

- * Multiple concurrent requests
- * Synchronous request processing
- * Asynchronous request processing

Classes

- TestServerObject

Libraries Linked

- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.

Shared Libraries Linked

- agenteventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsFtFTPRelASh -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObjSh -- This library provides functions to use FTP at a scheduled time by the User.
- DsClSh -- This library contains classes which make up the Science Data Server's (SDSRV) public interface. These classes are used by clients to connect, build commands, and submit requests to the SDSRV.
- DsCnSh -- This library was used to generate files which install ESDT configuration information for each ESDT previously.
- DsShSh -- This internal library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- EcCfSh -- The Config library (CF) is a shared library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistrySh
- EcDcMsgPng1Sh -- This library consists of message passing objects used by both the client and server side.
- EcDnDirSh -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcFhSh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLocatorSh -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcNsServiceLocSh -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcPfSh -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPoDbRWSH
- EcPoSh -- The Persistent CSC provides a set of abstract and base classes for approved advertisements and requests.
- EcPtSpecialLockSh -- This library provides classes for mutex operations and thread IDs.
- EcSeCmiSh -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).

- EcSeServerKeyMgmtSh -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbedSh -- This shared Library has only the methods for completing the successful compilation.
- EcSeUtilityDbStubbedSh -- This shared Library provides stubbed version of EcSeUtilityDb for successful compilation.
- EcTiTimeSh -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUrSh -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUtFactorySh -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtMiscSh -- The EcUtMisc library contains miscellaneous utilities.
- EcUtSh -- EcUt is a utility library for all the ECS applications.
- eventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- GlSh -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.
- IoAdCoreSh -- The CoreLib CSC provides a set of functionalities for describing a generic advertisement, parsing and validating attributes that support the ECS Core meta data model, and requesting and moderating advertisements.
- IoAdProxySh -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSearchSh -- The SearchLib CSC provides a set of searching capabilities for approved advertisements, for the administration of groups, and for moderation of requests.
- IoAdServerSh -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSubsSh -- The SubsLib CSC provides a set of derived classes which represent different types of advertisements: products, services, and providers.

***process* IoAdEsodamGroups**

/ecs/formal/IOS/AdvService/src/Progs

Driver program to display create/update/delete group forms and also to create/update/delete groups.

Libraries Linked

- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.

Shared Libraries Linked

- agenteventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsEmMailRelASh -- This Library is used for the emails using sendmail utility and the nnpst for Bulletin board messages.
- CsFtFTPRelASh -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObjSh -- This library provides functions to use FTP at a scheduled time by the User.
- DsClSh -- This library contains classes which make up the Science Data Server's (SDSRV) public interface. These classes are used by clients to connect, build commands, and submit requests to the SDSRV.
- DsCnSh -- This library was used to generate files which install ESDT configuration information for each ESDT previously.
- DsShSh -- This internal library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- EcCfSh -- The Config library (CF) is a shared library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistrySh
- EcDcMsgPng1Sh -- This library consists of message passing objects used by both the client and server side.
- EcDnDirSh -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcFhSh -- This library provides fault handling capabilities to ECS applications.
- EcHtSh -- This library provides classes that contain operations to handle all HTML tags.
- EcNsServiceLocatorSh -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcNsServiceLocSh -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcPfSh -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPoDbRWSH
- EcPoSh -- The Persistent CSC provides a set of abstract and base classes for approved advertisements and requests.
- EcPtSpecialLockSh -- This library provides classes for mutex operations and thread IDs.
- EcSeCmiSh -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).

- EcSeLoginContextSh -- This library uses the key obtained from either the EcSeServerKeyMgmt or EcSeAuthn library to establish a login context for a process.
- EcSeServerKeyMgmtSh -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbedSh -- This shared Library has only the methods for completing the successful compilation.
- EcSeUtilityDbStubbedSh -- This shared Library provides stubbed version of EcSeUtilityDb for successful compilation.
- EcTiTimeSh -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUrSh -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUtFactorySh -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtMiscSh -- The EcUtMisc library contains miscellaneous utilities.
- EcUtSh -- EcUt is a utility library for all the ECS applications.
- eventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- GlSh -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.
- IoAdCoreSh -- The CoreLib CSC provides a set of functionalities for describing a generic advertisement, parsing and validating attributes that support the ECS Core meta data model, and requesting and moderating advertisements.
- IoAdHtmlCoreSh
- IoAdHtmlSubsSh
- IoAdInstallBaseSh -- The installer allows one to install a compressed tar file containing some kind of application (modelled through a "IoAdInstallableServiceAdv") or a URL to get to a WWW service (modelled through a "IoAdMimeServiceAdv") onto a users workstation.
- IoAdProxySh -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSearchSh -- The SearchLib CSC provides a set of searching capabilities for approved advertisements, for the administration of groups, and for moderation of requests.
- IoAdServerSh -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSubsSh -- The SubsLib CSC provides a set of derived classes which represent different types of advertisements: products, services, and providers.

process loAdEsodamGroupSearch

/ecs/formal/IOS/AdvService/src/Progs

CGI program for doing a search on moderation groups.

Libraries Linked

- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.

Shared Libraries Linked

- agenteventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsEmMailRelASh -- This Library is used for the emails using sendmail utility and the nnpost for Bulletin board messages.
- CsFtFTPRelASh -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObjSh -- This library provides functions to use FTP at a scheduled time by the User.
- DsClSh -- This library contains classes which make up the Science Data Server's (SDSRV) public interface. These classes are used by clients to connect, build commands, and submit requests to the SDSRV.
- DsCnSh -- This library was used to generate files which install ESDT configuration information for each ESDT previously.
- DsShSh -- This internal library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- EcCfSh -- The Config library (CF) is a shared library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistrySh
- EcDcMsgPng1Sh -- This library consists of message passing objects used by both the client and server side.
- EcDnDirSh -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcFhSh -- This library provides fault handling capabilities to ECS applications.
- EcHtSh -- This library provides classes that contain operations to handle all HTML tags.
- EcNsServiceLocatorSh -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcNsServiceLocSh -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.

- EcPfSh -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPoDbRWSH
- EcPoSh -- The Persistent CSC provides a set of abstract and base classes for approved advertisements and requests.
- EcPtSpecialLockSh -- This library provides classes for mutex operations and thread IDs.
- EcSeCmiSh -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeLoginContextSh -- This library uses the key obtained from either the EcSeServerKeyMgmt or EcSeAuthn library to establish a login context for a process.
- EcSeServerKeyMgmtSh -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbedSh -- This shared Library has only the methods for completing the successful compilation.
- EcSeUtilityDbStubbedSh -- This shared Library provides stubbed version of EcSeUtilityDb for successful compilation.
- EcTiTimeSh -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUrSh -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUtFactorySh -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtMiscSh -- The EcUtMisc library contains miscellaneous utilities.
- EcUtSh -- EcUt is a utility library for all the ECS applications.
- eventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- GlSh -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.
- IoAdCoreSh -- The CoreLib CSC provides a set of functionalities for describing a generic advertisement, parsing and validating attributes that support the ECS Core meta data model, and requesting and moderating advertisements.
- IoAdHtmlCoreSh
- IoAdHtmlSubsSh
- IoAdInstallBaseSh -- The installer allows one to install a compressed tar file containing some kind of application (modelled through a "IoAdInstallableServiceAdv") or a URL to get to a WWW service (modelled through a "IoAdMimeServiceAdv") onto a users workstation.
- IoAdProxySh -- The ServerLib CSC provides classes for process framework DCE server and client.

- IoAdSearchSh -- The SearchLib CSC provides a set of searching capabilities for approved advertisements, for the administration of groups, and for moderation of requests.
- IoAdServerSh -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSubsSh -- The SubsLib CSC provides a set of derived classes which represent different types of advertisements: products, services, and providers.

***process* IoAdEsodamModeration**

/ecs/formal/IOS/AdvService/src/Progs

Libraries Linked

- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.

Shared Libraries Linked

- agenteventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsEmMailRelASh -- This Library is used for the emails using sendmail utility and the nnpst for Bulletin board messages.
- CsFtFTPRelASh -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObjSh -- This library provides functions to use FTP at a scheduled time by the User.
- DsClSh -- This library contains classes which make up the Science Data Server's (SDSRV) public interface. These classes are used by clients to connect, build commands, and submit requests to the SDSRV.
- DsCnSh -- This library was used to generate files which install ESDT configuration information for each ESDT previously.
- DsShSh -- This internal library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- EcCfSh -- The Config library (CF) is a shared library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistrySh
- EcDcMsgPsnng1Sh -- This library consists of message passing objects used by both the client and server side.
- EcDnDirSh -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcFhSh -- This library provides fault handling capabilities to ECS applications.
- EcHtSh -- This library provides classes that contain operations to handle all HTML tags.

- EcNsServiceLocatorSh -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcNsServiceLocSh -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcPfSh -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPoDbRWSH
- EcPoSh -- The Persistent CSC provides a set of abstract and base classes for approved advertisements and requests.
- EcPtSpecialLockSh -- This library provides classes for mutex operations and thread IDs.
- EcSeCmiSh -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeLoginContextSh -- This library uses the key obtained from either the EcSeServerKeyMgmt or EcSeAuthn library to establish a login context for a process.
- EcSeServerKeyMgmtSh -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbedSh -- This shared Library has only the methods for completing the successful compilation.
- EcSeUtilityDbStubbedSh -- This shared Library provides stubbed version of EcSeUtilityDb for successful compilation.
- EcTiTimeSh -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUrSh -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUtFactorySh -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtMiscSh -- The EcUtMisc library contains miscellaneous utilities.
- EcUtSh -- EcUt is a utility library for all the ECS applications.
- eventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- GlSh -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.
- IoAdCoreSh -- The CoreLib CSC provides a set of functionalities for describing a generic advertisement, parsing and validating attributes that support the ECS Core meta data model, and requesting and moderating advertisements.
- IoAdHtmlCoreSh
- IoAdHtmlSubsSh

- IoAdInstallBaseSh -- The installer allows one to install a compressed tar file containing some kind of application (modelled through a "IoAdInstallableServiceAdv") or a URL to get to a WWW service (modelled through a "IoAdMimeServiceAdv") onto a users workstation.
- IoAdProxySh -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSearchSh -- The SearchLib CSC provides a set of searching capabilities for approved advertisements, for the administration of groups, and for moderation of requests.
- IoAdServerSh -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSubsSh -- The SubsLib CSC provides a set of derived classes which represent different types of advertisements: products, services, and providers.

process IoAdEsodamModerationForm

/ecs/formal/IOS/AdvService/src/Progs

CGI program that displays a request to be moderated.

Libraries Linked

- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.

Shared Libraries Linked

- agenteventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsEmMailRelASh -- This Library is used for the emails using sendmail utility and the nnpst for Bulletin board messages.
- CsFtFTPRelASh -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObjSh -- This library provides functions to use FTP at a scheduled time by the User.
- DsClSh -- This library contains classes which make up the Science Data Server's (SDSRV) public interface. These classes are used by clients to connect, build commands, and submit requests to the SDSRV.
- DsCnSh -- This library was used to generate files which install ESDT configuration information for each ESDT previously.
- DsShSh -- This internal library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- EcCfSh -- The Config library (CF) is a shared library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistrySh

- EcDcMsgPsnng1Sh -- This library consists of message passing objects used by both the client and server side.
- EcDnDirSh -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcFhSh -- This library provides fault handling capabilities to ECS applications.
- EcHtSh -- This library provides classes that contain operations to handle all HTML tags.
- EcNsServiceLocatorSh -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcNsServiceLocSh -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcPfSh -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPoDbRWSH
- EcPoSh -- The Persistent CSC provides a set of abstract and base classes for approved advertisements and requests.
- EcPtSpecialLockSh -- This library provides classes for mutex operations and thread IDs.
- EcSeCmiSh -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeLoginContextSh -- This library uses the key obtained from either the EcSeServerKeyMgmt or EcSeAuthn library to establish a login context for a process.
- EcSeServerKeyMgmtSh -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbedSh -- This shared Library has only the methods for completing the successful compilation.
- EcSeUtilityDbStubbedSh -- This shared Library provides stubbed version of EcSeUtilityDb for successful compilation.
- EcTiTimeSh -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUrSh -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUtFactorySh -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtMiscSh -- The EcUtMisc library contains miscellaneous utilities.
- EcUtSh -- EcUt is a utility library for all the ECS applications.
- eventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.

- GSh -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.
- IoAdCoreSh -- The CoreLib CSC provides a set of functionalities for describing a generic advertisement, parsing and validating attributes that support the ECS Core meta data model, and requesting and moderating advertisements.
- IoAdHtmlCoreSh
- IoAdHtmlSubsSh
- IoAdInstallBaseSh -- The installer allows one to install a compressed tar file containing some kind of application (modelled through a "IoAdInstallableServiceAdv") or a URL to get to a WWW service (modelled through a "IoAdMimeServiceAdv") onto a users workstation.
- IoAdProxySh -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSearchSh -- The SearchLib CSC provides a set of searching capabilities for approved advertisements, for the administration of groups, and for moderation of requests.
- IoAdServerSh -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSubsSh -- The SubsLib CSC provides a set of derived classes which represent different types of advertisements: products, services, and providers.

process IoAdEsodamModerationGroups

/ecs/formal/IOS/AdvService/src/Progs

CGI program for doing a search of groups.

Libraries Linked

- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.

Shared Libraries Linked

- agenteventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsEmMailRelASh -- This Library is used for the emails using sendmail utility and the nnpst for Bulletin board messages.
- CsFtFTPRelASh -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObjSh -- This library provides functions to use FTP at a scheduled time by the User.
- DsClSh -- This library contains classes which make up the Science Data Server's (SDSRV) public interface. These classes are used by clients to connect, build commands, and submit requests to the SDSRV.

- DsCnSh -- This library was used to generate files which install ESDT configuration information for each ESDT previously.
- DsShSh -- This internal library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- EcCfSh -- The Config library (CF) is a shared library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistrySh
- EcDcMsgPsnng1Sh -- This library consists of message passing objects used by both the client and server side.
- EcDnDirSh -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcFhSh -- This library provides fault handling capabilities to ECS applications.
- EcHtSh -- This library provides classes that contain operations to handle all HTML tags.
- EcNsServiceLocatorSh -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcNsServiceLocSh -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcPfSh -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPoDbRWSH
- EcPoSh -- The Persistent CSC provides a set of abstract and base classes for approved advertisements and requests.
- EcPtSpecialLockSh -- This library provides classes for mutex operations and thread IDs.
- EcSeCmiSh -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeLoginContextSh -- This library uses the key obtained from either the EcSeServerKeyMgmt or EcSeAuthn library to establish a login context for a process.
- EcSeServerKeyMgmtSh -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbedSh -- This shared Library has only the methods for completing the successful compilation.
- EcSeUtilityDbStubbedSh -- This shared Library provides stubbed version of EcSeUtilityDb for successful compilation.
- EcTiTimeSh -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUrSh -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.

- EcUtFactorySh -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtMiscSh -- The EcUtMisc library contains miscellaneous utilities.
- EcUtSh -- EcUt is a utility library for all the ECS applications.
- eventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- GlSh -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.
- IoAdCoreSh -- The CoreLib CSC provides a set of functionalities for describing a generic advertisement, parsing and validating attributes that support the ECS Core meta data model, and requesting and moderating advertisements.
- IoAdHtmlCoreSh
- IoAdHtmlSubsSh
- IoAdInstallBaseSh -- The installer allows one to install a compressed tar file containing some kind of application (modelled through a "IoAdInstallableServiceAdv") or a URL to get to a WWW service (modelled through a "IoAdMimeServiceAdv") onto a users workstation.
- IoAdProxySh -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSearchSh -- The SearchLib CSC provides a set of searching capabilities for approved advertisements, for the administration of groups, and for moderation of requests.
- IoAdServerSh -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSubsSh -- The SubsLib CSC provides a set of derived classes which represent different types of advertisements: products, services, and providers.

***process* IoAdEsodamModerationQueue**

/ecs/formal/IOS/AdvService/src/Progs

CGI program that lists all the ads to be moderated for a given group.

Libraries Linked

- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.

Shared Libraries Linked

- agenteventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsEmMailRelASh -- This Library is used for the emails using sendmail utility and the nnpst for Bulletin board messages.
- CsFtFTPRelASh -- This library provides a Wrapper for FTP.

- CsFtFTPSchedObjSh -- This library provides functions to use FTP at a scheduled time by the User.
- DsClSh -- This library contains classes which make up the Science Data Server's (SDSRV) public interface. These classes are used by clients to connect, build commands, and submit requests to the SDSRV.
- DsCnSh -- This library was used to generate files which install ESDT configuration information for each ESDT previously.
- DsShSh -- This internal library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- EcCfSh -- The Config library (CF) is a shared library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistrySh
- EcDcMsgPsngr1Sh -- This library consists of message passing objects used by both the client and server side.
- EcDnDirSh -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcFhSh -- This library provides fault handling capabilities to ECS applications.
- EcHtSh -- This library provides classes that contain operations to handle all HTML tags.
- EcNsServiceLocatorSh -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcNsServiceLocSh -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcPfSh -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPoDbRWSH
- EcPoSh -- The Persistent CSC provides a set of abstract and base classes for approved advertisements and requests.
- EcPtSpecialLockSh -- This library provides classes for mutex operations and thread IDs.
- EcSeCmiSh -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeLoginContextSh -- This library uses the key obtained from either the EcSeServerKeyMgmt or EcSeAuthn library to establish a login context for a process.
- EcSeServerKeyMgmtSh -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbedSh -- This shared Library has only the methods for completing the successful compilation.

- EcSeUtilityDbStubbedSh -- This shared Library provides stubbed version of EcSeUtilityDb for successful compilation.
- EcTiTimeSh -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUrSh -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUtFactorySh -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtMiscSh -- The EcUtMisc library contains miscellaneous utilities.
- EcUtSh -- EcUt is a utility library for all the ECS applications.
- eventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- GlSh -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.
- IoAdCoreSh -- The CoreLib CSC provides a set of functionalities for describing a generic advertisement, parsing and validating attributes that support the ECS Core meta data model, and requesting and moderating advertisements.
- IoAdHtmlCoreSh
- IoAdHtmlSubsSh
- IoAdInstallBaseSh -- The installer allows one to install a compressed tar file containing some kind of application (modelled through a "IoAdInstallableServiceAdv") or a URL to get to a WWW service (modelled through a "IoAdMimeServiceAdv") onto a users workstation.
- IoAdProxySh -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSearchSh -- The SearchLib CSC provides a set of searching capabilities for approved advertisements, for the administration of groups, and for moderation of requests.
- IoAdServerSh -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSubsSh -- The SubsLib CSC provides a set of derived classes which represent different types of advertisements: products, services, and providers.

process IoAdEsodamObsoleteReqs

/ecs/formal/IOS/AdvService/src/Progs

CGI program that displays obsolete requests.

Libraries Linked

- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.

Shared Libraries Linked

- agenteventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsEmMailRelASh -- This Library is used for the emails using sendmail utility and the nnpost for Bulletin board messages.
- CsFtFTPRelASh -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObjSh -- This library provides functions to use FTP at a scheduled time by the User.
- DsClSh -- This library contains classes which make up the Science Data Server's (SDSRV) public interface. These classes are used by clients to connect, build commands, and submit requests to the SDSRV.
- DsCnSh -- This library was used to generate files which install ESDT configuration information for each ESDT previously.
- DsShSh -- This internal library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- EcCfSh -- The Config library (CF) is a shared library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistrySh
- EcDcMsgPsnng1Sh -- This library consists of message passing objects used by both the client and server side.
- EcDnDirSh -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcFhSh -- This library provides fault handling capabilities to ECS applications.
- EcHtSh -- This library provides classes that contain operations to handle all HTML tags.
- EcNsServiceLocatorSh -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcNsServiceLocSh -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcPfSh -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPoDbRWSH
- EcPoSh -- The Persistent CSC provides a set of abstract and base classes for approved advertisements and requests.
- EcPtSpecialLockSh -- This library provides classes for mutex operations and thread IDs.
- EcSeCmiSh -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).

- EcSeLoginContextSh -- This library uses the key obtained from either the EcSeServerKeyMgmt or EcSeAuthn library to establish a login context for a process.
- EcSeServerKeyMgmtSh -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbedSh -- This shared Library has only the methods for completing the successful compilation.
- EcSeUtilityDbStubbedSh -- This shared Library provides stubbed version of EcSeUtilityDb for successful compilation.
- EcTiTimeSh -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUrSh -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUtFactorySh -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtMiscSh -- The EcUtMisc library contains miscellaneous utilities.
- EcUtSh -- EcUt is a utility library for all the ECS applications.
- eventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- GlSh -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.
- IoAdCoreSh -- The CoreLib CSC provides a set of functionalities for describing a generic advertisement, parsing and validating attributes that support the ECS Core meta data model, and requesting and moderating advertisements.
- IoAdHtmlCoreSh
- IoAdHtmlSubsSh
- IoAdInstallBaseSh -- The installer allows one to install a compressed tar file containing some kind of application (modelled through a "IoAdInstallableServiceAdv") or a URL to get to a WWW service (modelled through a "IoAdMimeServiceAdv") onto a users workstation.
- IoAdProxySh -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSearchSh -- The SearchLib CSC provides a set of searching capabilities for approved advertisements, for the administration of groups, and for moderation of requests.
- IoAdServerSh -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSubsSh -- The SubsLib CSC provides a set of derived classes which represent different types of advertisements: products, services, and providers.

process loAdEsodContributionForm

/ecs/formal/IOS/AdvService/src/Progs

CGI program to display a form for creating/updating/deleting advertisements.

Libraries Linked

- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.

Shared Libraries Linked

- agenteventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsEmMailRelASh -- This Library is used for the emails using sendmail utility and the nnpost for Bulletin board messages.
- CsFtFTPRelASh -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObjSh -- This library provides functions to use FTP at a scheduled time by the User.
- DsClSh -- This library contains classes which make up the Science Data Server's (SDSRV) public interface. These classes are used by clients to connect, build commands, and submit requests to the SDSRV.
- DsCnSh -- This library was used to generate files which install ESDT configuration information for each ESDT previously.
- DsShSh -- This internal library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- EcCfSh -- The Config library (CF) is a shared library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistrySh
- EcDcMsgPng1Sh -- This library consists of message passing objects used by both the client and server side.
- EcDnDirSh -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcFhSh -- This library provides fault handling capabilities to ECS applications.
- EcHtSh -- This library provides classes that contain operations to handle all HTML tags.
- EcNsServiceLocatorSh -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcNsServiceLocSh -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.

- EcPfSh -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPoDbRWSH
- EcPoSh -- The Persistent CSC provides a set of abstract and base classes for approved advertisements and requests.
- EcPtSpecialLockSh -- This library provides classes for mutex operations and thread IDs.
- EcSeCmiSh -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeLoginContextSh -- This library uses the key obtained from either the EcSeServerKeyMgmt or EcSeAuthn library to establish a login context for a process.
- EcSeServerKeyMgmtSh -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbedSh -- This shared Library has only the methods for completing the successful compilation.
- EcSeUtilityDbStubbedSh -- This shared Library provides stubbed version of EcSeUtilityDb for successful compilation.
- EcTiTimeSh -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUrSh -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUtFactorySh -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtMiscSh -- The EcUtMisc library contains miscellaneous utilities.
- EcUtSh -- EcUt is a utility library for all the ECS applications.
- eventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- GlSh -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.
- IoAdCoreSh -- The CoreLib CSC provides a set of functionalities for describing a generic advertisement, parsing and validating attributes that support the ECS Core meta data model, and requesting and moderating advertisements.
- IoAdHtmlCoreSh
- IoAdHtmlSubsSh
- IoAdInstallBaseSh -- The installer allows one to install a compressed tar file containing some kind of application (modelled through a "IoAdInstallableServiceAdv") or a URL to get to a WWW service (modelled through a "IoAdMimeServiceAdv") onto a users workstation.
- IoAdProxySh -- The ServerLib CSC provides classes for process framework DCE server and client.

- IoAdSearchSh -- The SearchLib CSC provides a set of searching capabilities for approved advertisements, for the administration of groups, and for moderation of requests.
- IoAdServerSh -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSubsSh -- The SubsLib CSC provides a set of derived classes which represent different types of advertisements: products, services, and providers.

***process* IoAdEsodContributions**

/ecs/formal/IOS/AdvService/src/Progs

CGI program to create/update/delete advertisements.

Libraries Linked

- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.

Shared Libraries Linked

- agenteventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsEmMailRelASh -- This Library is used for the emails using sendmail utility and the nnpst for Bulletin board messages.
- CsFtFTPRelASh -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObjSh -- This library provides functions to use FTP at a scheduled time by the User.
- DsClSh -- This library contains classes which make up the Science Data Server's (SDSRV) public interface. These classes are used by clients to connect, build commands, and submit requests to the SDSRV.
- DsCnSh -- This library was used to generate files which install ESDT configuration information for each ESDT previously.
- DsShSh -- This internal library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- EcCfSh -- The Config library (CF) is a shared library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistrySh
- EcDcMsgPng1Sh -- This library consists of message passing objects used by both the client and server side.
- EcDnDirSh -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcFhSh -- This library provides fault handling capabilities to ECS applications.

- EcHtSh -- This library provides classes that contain operations to handle all HTML tags.
- EcNsServiceLocatorSh -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcNsServiceLocSh -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcPfSh -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPoDbRWSH
- EcPoSh -- The Persistent CSC provides a set of abstract and base classes for approved advertisements and requests.
- EcPtSpecialLockSh -- This library provides classes for mutex operations and thread IDs.
- EcSeCmiSh -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeLoginContextSh -- This library uses the key obtained from either the EcSeServerKeyMgmt or EcSeAuthn library to establish a login context for a process.
- EcSeServerKeyMgmtSh -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbedSh -- This shared Library has only the methods for completing the successful compilation.
- EcSeUtilityDbStubbedSh -- This shared Library provides stubbed version of EcSeUtilityDb for successful compilation.
- EcTiTimeSh -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUrSh -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUtFactorySh -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtMiscSh -- The EcUtMisc library contains miscellaneous utilities.
- EcUtSh -- EcUt is a utility library for all the ECS applications.
- eventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- GlSh -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.
- IoAdCoreSh -- The CoreLib CSC provides a set of functionalities for describing a generic advertisement, parsing and validating attributes that support the ECS Core meta data model, and requesting and moderating advertisements.
- IoAdHtmlCoreSh

- IoAdHtmlSubsSh
- IoAdInstallBaseSh -- The installer allows one to install a compressed tar file containing some kind of application (modelled through a "IoAdInstallableServiceAdv") or a URL to get to a WWW service (modelled through a "IoAdMimeServiceAdv") onto a users workstation.
- IoAdProxySh -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSearchSh -- The SearchLib CSC provides a set of searching capabilities for approved advertisements, for the administration of groups, and for moderation of requests.
- IoAdServerSh -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSubsSh -- The SubsLib CSC provides a set of derived classes which represent different types of advertisements: products, services, and providers.

***process* IoAdEsodEntryDetail**

/ecs/formal/IOS/AdvService/src/Progs

CGI program that displays an advertisement in detail.

Libraries Linked

- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.

Shared Libraries Linked

- agenteventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsEmMailRelASh -- This Library is used for the emails using sendmail utility and the nnpst for Bulletin board messages.
- CsFtFTPRelASh -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObjSh -- This library provides functions to use FTP at a scheduled time by the User.
- DsClSh -- This library contains classes which make up the Science Data Server's (SDSRV) public interface. These classes are used by clients to connect, build commands, and submit requests to the SDSRV.
- DsCnSh -- This library was used to generate files which install ESDT configuration information for each ESDT previously.
- DsShSh -- This internal library provides underlying DCE(ODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- EcCfSh -- The Config library (CF) is a shared library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.

- EcCsRegistrySh
- EcDcMsgPsng1Sh -- This library consists of message passing objects used by both the client and server side.
- EcDnDirSh -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcFhSh -- This library provides fault handling capabilities to ECS applications.
- EcHtSh -- This library provides classes that contain operations to handle all HTML tags.
- EcNsServiceLocatorSh -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcNsServiceLocSh -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcPfSh -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPoDbRWSH
- EcPoSh -- The Persistent CSC provides a set of abstract and base classes for approved advertisements and requests.
- EcPtSpecialLockSh -- This library provides classes for mutex operations and thread IDs.
- EcSeCmiSh -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeLoginContextSh -- This library uses the key obtained from either the EcSeServerKeyMgmt or EcSeAuthn library to establish a login context for a process.
- EcSeServerKeyMgmtSh -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbedSh -- This shared Library has only the methods for completing the successful compilation.
- EcSeUtilityDbStubbedSh -- This shared Library provides stubbed version of EcSeUtilityDb for successful compilation.
- EcTiTimeSh -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUrSh -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUtFactorySh -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtMiscSh -- The EcUtMisc library contains miscellaneous utilities.
- EcUtSh -- EcUt is a utility library for all the ECS applications.
- eventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.

- GISH -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.
- IoAdCoreSh -- The CoreLib CSC provides a set of functionalities for describing a generic advertisement, parsing and validating attributes that support the ECS Core meta data model, and requesting and moderating advertisements.
- IoAdHtmlCoreSh
- IoAdHtmlSubsSh
- IoAdInstallBaseSh -- The installer allows one to install a compressed tar file containing some kind of application (modelled through a "IoAdInstallableServiceAdv") or a URL to get to a WWW service (modelled through a "IoAdMimeServiceAdv") onto a users workstation.
- IoAdProxySh -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSearchSh -- The SearchLib CSC provides a set of searching capabilities for approved advertisements, for the administration of groups, and for moderation of requests.
- IoAdServerSh -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSubsSh -- The SubsLib CSC provides a set of derived classes which represent different types of advertisements: products, services, and providers.

process IoAdEsodExamples

/ecs/formal/IOS/AdvService/src/Progs

CGI program that lists examples of different kinds of advertisements in the Earth Science Online Directory (ESOD).

Libraries Linked

- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.

Shared Libraries Linked

- agenteventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsEmMailRelASh -- This Library is used for the emails using sendmail utility and the nnpst for Bulletin board messages.
- CsFtFTPRelASh -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObjSh -- This library provides functions to use FTP at a scheduled time by the User.
- DsClSh -- This library contains classes which make up the Science Data Server's (SDSRV) public interface. These classes are used by clients to connect, build commands, and submit requests to the SDSRV.

- DsCnSh -- This library was used to generate files which install ESDT configuration information for each ESDT previously.
- DsShSh -- This internal library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- EcCfSh -- The Config library (CF) is a shared library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistrySh
- EcDcMsgPsngr1Sh -- This library consists of message passing objects used by both the client and server side.
- EcDnDirSh -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcFhSh -- This library provides fault handling capabilities to ECS applications.
- EcHtSh -- This library provides classes that contain operations to handle all HTML tags.
- EcNsServiceLocatorSh -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcNsServiceLocSh -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcPfSh -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPoDbRWSH
- EcPoSh -- The Persistent CSC provides a set of abstract and base classes for approved advertisements and requests.
- EcPtSpecialLockSh -- This library provides classes for mutex operations and thread IDs.
- EcSeCmiSh -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeLoginContextSh -- This library uses the key obtained from either the EcSeServerKeyMgmt or EcSeAuthn library to establish a login context for a process.
- EcSeServerKeyMgmtSh -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbedSh -- This shared Library has only the methods for completing the successful compilation.
- EcSeUtilityDbStubbedSh -- This shared Library provides stubbed version of EcSeUtilityDb for successful compilation.
- EcTiTimeSh -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUrSh -- A Universal Reference (UR) is created as a logical reference to an extant ECS object.

- EcUtFactorySh -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtMiscSh -- The EcUtMisc library contains miscellaneous utilities.
- EcUtSh -- EcUt is a utility library for all the ECS applications.
- eventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- GlSh -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.
- IoAdCoreSh -- The CoreLib CSC provides a set of functionalities for describing a generic advertisement, parsing and validating attributes that support the ECS Core meta data model, and requesting and moderating advertisements.
- IoAdHtmlCoreSh
- IoAdHtmlSubsSh
- IoAdInstallBaseSh -- The installer allows one to install a compressed tar file containing some kind of application (modelled through a "IoAdInstallableServiceAdv") or a URL to get to a WWW service (modelled through a "IoAdMimeServiceAdv") onto a users workstation.
- IoAdProxySh -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSearchSh -- The SearchLib CSC provides a set of searching capabilities for approved advertisements, for the administration of groups, and for moderation of requests.
- IoAdServerSh -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSubsSh -- The SubsLib CSC provides a set of derived classes which represent different types of advertisements: products, services, and providers.

***process* IoAdEsodGroupDetail**

/ecs/formal/IOS/AdvService/src/Progs

CGI program that displays a moderation group in detail.

Libraries Linked

- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.

Shared Libraries Linked

- agenteventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsEmMailRelASh -- This Library is used for the emails using sendmail utility and the nnpst for Bulletin board messages.
- CsFtFTPRelASh -- This library provides a Wrapper for FTP.

- CsFtFTPSchedObjSh -- This library provides functions to use FTP at a scheduled time by the User.
- DsClSh -- This library contains classes which make up the Science Data Server's (SDSRV) public interface. These classes are used by clients to connect, build commands, and submit requests to the SDSRV.
- DsCnSh -- This library was used to generate files which install ESDT configuration information for each ESDT previously.
- DsShSh -- This internal library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- EcCfSh -- The Config library (CF) is a shared library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistrySh
- EcDcMsgPsngr1Sh -- This library consists of message passing objects used by both the client and server side.
- EcDnDirSh -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcFhSh -- This library provides fault handling capabilities to ECS applications.
- EcHtSh -- This library provides classes that contain operations to handle all HTML tags.
- EcNsServiceLocatorSh -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcNsServiceLocSh -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcPfSh -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPoDbRWSH
- EcPoSh -- The Persistent CSC provides a set of abstract and base classes for approved advertisements and requests.
- EcPtSpecialLockSh -- This library provides classes for mutex operations and thread IDs.
- EcSeCmiSh -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeLoginContextSh -- This library uses the key obtained from either the EcSeServerKeyMgmt or EcSeAuthn library to establish a login context for a process.
- EcSeServerKeyMgmtSh -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbedSh -- This shared Library has only the methods for completing the successful compilation.

- EcSeUtilityDbStubbedSh -- This shared Library provides stubbed version of EcSeUtilityDb for successful compilation.
- EcTiTimeSh -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUrSh -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUtFactorySh -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtMiscSh -- The EcUtMisc library contains miscellaneous utilities.
- EcUtSh -- EcUt is a utility library for all the ECS applications.
- eventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- GlSh -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.
- IoAdCoreSh -- The CoreLib CSC provides a set of functionalities for describing a generic advertisement, parsing and validating attributes that support the ECS Core meta data model, and requesting and moderating advertisements.
- IoAdHtmlCoreSh
- IoAdHtmlSubsSh
- IoAdInstallBaseSh -- The installer allows one to install a compressed tar file containing some kind of application (modelled through a "IoAdInstallableServiceAdv") or a URL to get to a WWW service (modelled through a "IoAdMimeServiceAdv") onto a users workstation.
- IoAdProxySh -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSearchSh -- The SearchLib CSC provides a set of searching capabilities for approved advertisements, for the administration of groups, and for moderation of requests.
- IoAdServerSh -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSubsSh -- The SubsLib CSC provides a set of derived classes which represent different types of advertisements: products, services, and providers.

process IoAdEsodScienceSearch

/ecs/formal/IOS/AdvService/src/Progs

CGI program for finding particular advertisements based on a combination of criteria. An entry will be displayed if it meets all of the criteria specified in all of the sections.

Libraries Linked

- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.

Shared Libraries Linked

- agenteventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsEmMailRelASh -- This Library is used for the emails using sendmail utility and the nnpst for Bulletin board messages.
- CsFtFTPRelASh -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObjSh -- This library provides functions to use FTP at a scheduled time by the User.
- DsClSh -- This library contains classes which make up the Science Data Server's (SDSRV) public interface. These classes are used by clients to connect, build commands, and submit requests to the SDSRV.
- DsCnSh -- This library was used to generate files which install ESDT configuration information for each ESDT previously.
- DsShSh -- This internal library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- EcCfSh -- The Config library (CF) is a shared library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistrySh
- EcDcMsgPsnng1Sh -- This library consists of message passing objects used by both the client and server side.
- EcDnDirSh -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcFhSh -- This library provides fault handling capabilities to ECS applications.
- EcHtSh -- This library provides classes that contain operations to handle all HTML tags.
- EcNsServiceLocatorSh -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcNsServiceLocSh -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcPfSh -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPoDbRWSH
- EcPoSh -- The Persistent CSC provides a set of abstract and base classes for approved advertisements and requests.
- EcPtSpecialLockSh -- This library provides classes for mutex operations and thread IDs.
- EcSeCmiSh -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).

- EcSeLoginContextSh -- This library uses the key obtained from either the EcSeServerKeyMgmt or EcSeAuthn library to establish a login context for a process.
- EcSeServerKeyMgmtSh -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbedSh -- This shared Library has only the methods for completing the successful compilation.
- EcSeUtilityDbStubbedSh -- This shared Library provides stubbed version of EcSeUtilityDb for successful compilation.
- EcTiTimeSh -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUrSh -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUtFactorySh -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtMiscSh -- The EcUtMisc library contains miscellaneous utilities.
- EcUtSh -- EcUt is a utility library for all the ECS applications.
- eventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- GlSh -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.
- IoAdCoreSh -- The CoreLib CSC provides a set of functionalities for describing a generic advertisement, parsing and validating attributes that support the ECS Core meta data model, and requesting and moderating advertisements.
- IoAdHtmlCoreSh
- IoAdHtmlSubsSh
- IoAdInstallBaseSh -- The installer allows one to install a compressed tar file containing some kind of application (modelled through a "IoAdInstallableServiceAdv") or a URL to get to a WWW service (modelled through a "IoAdMimeServiceAdv") onto a users workstation.
- IoAdProxySh -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSearchSh -- The SearchLib CSC provides a set of searching capabilities for approved advertisements, for the administration of groups, and for moderation of requests.
- IoAdServerSh -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSubsSh -- The SubsLib CSC provides a set of derived classes which represent different types of advertisements: products, services, and providers.

process loAdEsodScienceSearchForm

/ecs/formal/IOS/AdvService/src/Progs

CGI program that displays a form for searching to be performed on data advertisements only based on the time ranges, geo-coordinates, and attributes specified.

Libraries Linked

- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.

Shared Libraries Linked

- agenteventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsEmMailRelASh -- This Library is used for the emails using sendmail utility and the nnpost for Bulletin board messages.
- CsFtFTPRelASh -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObjSh -- This library provides functions to use FTP at a scheduled time by the User.
- DsClSh -- This library contains classes which make up the Science Data Server's (SDSRV) public interface. These classes are used by clients to connect, build commands, and submit requests to the SDSRV.
- DsCnSh -- This library was used to generate files which install ESDT configuration information for each ESDT previously.
- DsShSh -- This internal library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- EcCfSh -- The Config library (CF) is a shared library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistrySh
- EcDcMsgPng1Sh -- This library consists of message passing objects used by both the client and server side.
- EcDnDirSh -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcFhSh -- This library provides fault handling capabilities to ECS applications.
- EcHtSh -- This library provides classes that contain operations to handle all HTML tags.
- EcNsServiceLocatorSh -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcNsServiceLocSh -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.

- EcPfSh -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPoDbRWSH
- EcPoSh -- The Persistent CSC provides a set of abstract and base classes for approved advertisements and requests.
- EcPtSpecialLockSh -- This library provides classes for mutex operations and thread IDs.
- EcSeCmiSh -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeLoginContextSh -- This library uses the key obtained from either the EcSeServerKeyMgmt or EcSeAuthn library to establish a login context for a process.
- EcSeServerKeyMgmtSh -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbedSh -- This shared Library has only the methods for completing the successful compilation.
- EcSeUtilityDbStubbedSh -- This shared Library provides stubbed version of EcSeUtilityDb for successful compilation.
- EcTiTimeSh -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUrSh -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUtFactorySh -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtMiscSh -- The EcUtMisc library contains miscellaneous utilities.
- EcUtSh -- EcUt is a utility library for all the ECS applications.
- eventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- GlSh -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.
- IoAdCoreSh -- The CoreLib CSC provides a set of functionalities for describing a generic advertisement, parsing and validating attributes that support the ECS Core meta data model, and requesting and moderating advertisements.
- IoAdHtmlCoreSh
- IoAdHtmlSubsSh
- IoAdInstallBaseSh -- The installer allows one to install a compressed tar file containing some kind of application (modelled through a "IoAdInstallableServiceAdv") or a URL to get to a WWW service (modelled through a "IoAdMimeServiceAdv") onto a users workstation.
- IoAdProxySh -- The ServerLib CSC provides classes for process framework DCE server and client.

- IoAdSearchSh -- The SearchLib CSC provides a set of searching capabilities for approved advertisements, for the administration of groups, and for moderation of requests.
- IoAdServerSh -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSubsSh -- The SubsLib CSC provides a set of derived classes which represent different types of advertisements: products, services, and providers.

process IoAdEsodTextSearch

/ecs/formal/IOS/AdvService/src/Progs

CGI program for doing a general search of advertisements based on a search string. (Also does filtering based on class IDs -- can retrieve Product ads alone, Service ads alone, etc...)

Libraries Linked

- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.

Shared Libraries Linked

- agenteventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsEmMailRelASh -- This Library is used for the emails using sendmail utility and the nnpst for Bulletin board messages.
- CsFtFTPRelASh -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObjSh -- This library provides functions to use FTP at a scheduled time by the User.
- DsCISh -- This library contains classes which make up the Science Data Server's (SDSRV) public interface. These classes are used by clients to connect, build commands, and submit requests to the SDSRV.
- DsCnSh -- This library was used to generate files which install ESDT configuration information for each ESDT previously.
- DsShSh -- This internal library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- EcCfSh -- The Config library (CF) is a shared library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistrySh
- EcDcMsgPng1Sh -- This library consists of message passing objects used by both the client and server side.
- EcDnDirSh -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.

- EcFhSh -- This library provides fault handling capabilities to ECS applications.
- EcHtSh -- This library provides classes that contain operations to handle all HTML tags.
- EcNsServiceLocatorSh -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcNsServiceLocSh -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcPfSh -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPoDbRWSH
- EcPoSh -- The Persistent CSC provides a set of abstract and base classes for approved advertisements and requests.
- EcPtSpecialLockSh -- This library provides classes for mutex operations and thread IDs.
- EcSeCmiSh -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeLoginContextSh -- This library uses the key obtained from either the EcSeServerKeyMgmt or EcSeAuthn library to establish a login context for a process.
- EcSeServerKeyMgmtSh -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbedSh -- This shared Library has only the methods for completing the successful compilation.
- EcSeUtilityDbStubbedSh -- This shared Library provides stubbed version of EcSeUtilityDb for successful compilation.
- EcTiTimeSh -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUrSh -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUtFactorySh -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtMiscSh -- The EcUtMisc library contains miscellaneous utilities.
- EcUtSh -- EcUt is a utility library for all the ECS applications.
- eventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- GlSh -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.
- IoAdCoreSh -- The CoreLib CSC provides a set of functionalities for describing a generic advertisement, parsing and validating attributes that support the ECS Core meta data model, and requesting and moderating advertisements.

- IoAdHtmlCoreSh
- IoAdHtmlSubsSh
- IoAdInstallBaseSh -- The installer allows one to install a compressed tar file containing some kind of application (modelled through a "IoAdInstallableServiceAdv") or a URL to get to a WWW service (modelled through a "IoAdMimeServiceAdv") onto a users workstation.
- IoAdProxySh -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSearchSh -- The SearchLib CSC provides a set of searching capabilities for approved advertisements, for the administration of groups, and for moderation of requests.
- IoAdServerSh -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSubsSh -- The SubsLib CSC provides a set of derived classes which represent different types of advertisements: products, services, and providers.

process IoAdEsodTextSearchForm

/ecs/formal/IOS/AdvService/src/Progs

CGI program that displays a form to allow searching to be performed on all advertisements by specifying search words on Title, Description, or Keywords.

Libraries Linked

- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.

Shared Libraries Linked

- agenteventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsEmMailRelASh -- This Library is used for the emails using sendmail utility and the nnpost for Bulletin board messages.
- CsFtFTPRelASh -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObjSh -- This library provides functions to use FTP at a scheduled time by the User.
- DsClSh -- This library contains classes which make up the Science Data Server's (SDSRV) public interface. These classes are used by clients to connect, build commands, and submit requests to the SDSRV.
- DsCnSh -- This library was used to generate files which install ESDT configuration information for each ESDT previously.
- DsShSh -- This internal library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.

- EcCfSh -- The Config library (CF) is a shared library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistrySh
- EcDcMsgPsnng1Sh -- This library consists of message passing objects used by both the client and server side.
- EcDnDirSh -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcFhSh -- This library provides fault handling capabilities to ECS applications.
- EcHtSh -- This library provides classes that contain operations to handle all HTML tags.
- EcNsServiceLocatorSh -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcNsServiceLocSh -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcPfSh -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPoDbRWSH
- EcPoSh -- The Persistent CSC provides a set of abstract and base classes for approved advertisements and requests.
- EcPtSpecialLockSh -- This library provides classes for mutex operations and thread IDs.
- EcSeCmiSh -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeLoginContextSh -- This library uses the key obtained from either the EcSeServerKeyMgmt or EcSeAuthn library to establish a login context for a process.
- EcSeServerKeyMgmtSh -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbedSh -- This shared Library has only the methods for completing the successful compilation.
- EcSeUtilityDbStubbedSh -- This shared Library provides stubbed version of EcSeUtilityDb for successful compilation.
- EcTiTimeSh -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUrSh -- A Universal Reference (UR) is created as a logical reference to an extant ECS object.
- EcUtFactorySh -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtMiscSh -- The EcUtMisc library contains miscellaneous utilities.

- EcUtSh -- EcUt is a utility library for all the ECS applications.
- eventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- GlSh -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.
- IoAdCoreSh -- The CoreLib CSC provides a set of functionalities for describing a generic advertisement, parsing and validating attributes that support the ECS Core meta data model, and requesting and moderating advertisements.
- IoAdHtmlCoreSh
- IoAdHtmlSubsSh
- IoAdInstallBaseSh -- The installer allows one to install a compressed tar file containing some kind of application (modelled through a "IoAdInstallableServiceAdv") or a URL to get to a WWW service (modelled through a "IoAdMimeServiceAdv") onto a users workstation.
- IoAdProxySh -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSearchSh -- The SearchLib CSC provides a set of searching capabilities for approved advertisements, for the administration of groups, and for moderation of requests.
- IoAdServerSh -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSubsSh -- The SubsLib CSC provides a set of derived classes which represent different types of advertisements: products, services, and providers.

process IoAdEsodUpdateTemplate

/ecs/formal/IOS/AdvService/src/Progs

Libraries Linked

- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.

Shared Libraries Linked

- agenteventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsEmMailRelASh -- This Library is used for the emails using sendmail utility and the nnpost for Bulletin board messages.
- CsFtFTPRelASh -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObjSh -- This library provides functions to use FTP at a scheduled time by the User.

- DsClSh -- This library contains classes which make up the Science Data Server's (SDSRV) public interface. These classes are used by clients to connect, build commands, and submit requests to the SDSRV.
- DsCnSh -- This library was used to generate files which install ESDT configuration information for each ESDT previously.
- DsShSh -- This internal library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- EcCfSh -- The Config library (CF) is a shared library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistrySh
- EcDcMsgPng1Sh -- This library consists of message passing objects used by both the client and server side.
- EcDnDirSh -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcFhSh -- This library provides fault handling capabilities to ECS applications.
- EcHtSh -- This library provides classes that contain operations to handle all HTML tags.
- EcNsServiceLocatorSh -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcNsServiceLocSh -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcPfSh -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPoDbRWSH
- EcPoSh -- The Persistent CSC provides a set of abstract and base classes for approved advertisements and requests.
- EcPtSpecialLockSh -- This library provides classes for mutex operations and thread IDs.
- EcSeCmiSh -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeLoginContextSh -- This library uses the key obtained from either the EcSeServerKeyMgmt or EcSeAuthn library to establish a login context for a process.
- EcSeServerKeyMgmtSh -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbedSh -- This shared Library has only the methods for completing the successful compilation.
- EcSeUtilityDbStubbedSh -- This shared Library provides stubbed version of EcSeUtilityDb for successful compilation.

- EcTiTimeSh -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUrSh -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUtFactorySh -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtMiscSh -- The EcUtMisc library contains miscellaneous utilities.
- EcUtSh -- EcUt is a utility library for all the ECS applications.
- eventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- GlSh -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.
- IoAdCoreSh -- The CoreLib CSC provides a set of functionalities for describing a generic advertisement, parsing and validating attributes that support the ECS Core meta data model, and requesting and moderating advertisements.
- IoAdHtmlCoreSh
- IoAdHtmlSubsSh
- IoAdInstallBaseSh -- The installer allows one to install a compressed tar file containing some kind of application (modelled through a "IoAdInstallableServiceAdv") or a URL to get to a WWW service (modelled through a "IoAdMimeServiceAdv") onto a users workstation.
- IoAdProxySh -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSearchSh -- The SearchLib CSC provides a set of searching capabilities for approved advertisements, for the administration of groups, and for moderation of requests.
- IoAdServerSh -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSubsSh -- The SubsLib CSC provides a set of derived classes which represent different types of advertisements: products, services, and providers.

process IoAdEsodWhatsNew

/ecs/formal/IOS/AdvService/src/Progs

CGI program for finding advertisements that are less than "certain days" old.

Libraries Linked

- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.

Shared Libraries Linked

- `agenteventSh` -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- `CsEmMailRelASh` -- This Library is used for the emails using sendmail utility and the `nnpost` for Bulletin board messages.
- `CsFtFTPRelASh` -- This library provides a Wrapper for FTP.
- `CsFtFTPSchedObjSh` -- This library provides functions to use FTP at a scheduled time by the User.
- `DsClSh` -- This library contains classes which make up the Science Data Server's (SDSRV) public interface. These classes are used by clients to connect, build commands, and submit requests to the SDSRV.
- `DsCnSh` -- This library was used to generate files which install ESDT configuration information for each ESDT previously.
- `DsShSh` -- This internal library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- `EcCfSh` -- The Config library (CF) is a shared library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- `EcCsRegistrySh`
- `EcDcMsgPsnng1Sh` -- This library consists of message passing objects used by both the client and server side.
- `EcDnDirSh` -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- `EcFhSh` -- This library provides fault handling capabilities to ECS applications.
- `EcHtSh` -- This library provides classes that contain operations to handle all HTML tags.
- `EcNsServiceLocatorSh` -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- `EcNsServiceLocSh` -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- `EcPfSh` -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- `EcPoDbRWSH`
- `EcPoSh` -- The Persistent CSC provides a set of abstract and base classes for approved advertisements and requests.
- `EcPtSpecialLockSh` -- This library provides classes for mutex operations and thread IDs.
- `EcSeCmiSh` -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).

- EcSeLoginContextSh -- This library uses the key obtained from either the EcSeServerKeyMgmt or EcSeAuthn library to establish a login context for a process.
- EcSeServerKeyMgmtSh -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbedSh -- This shared Library has only the methods for completing the successful compilation.
- EcSeUtilityDbStubbedSh -- This shared Library provides stubbed version of EcSeUtilityDb for successful compilation.
- EcTiTimeSh -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUrSh -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUtFactorySh -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtMiscSh -- The EcUtMisc library contains miscellaneous utilities.
- EcUtSh -- EcUt is a utility library for all the ECS applications.
- eventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- GlSh -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.
- IoAdCoreSh -- The CoreLib CSC provides a set of functionalities for describing a generic advertisement, parsing and validating attributes that support the ECS Core meta data model, and requesting and moderating advertisements.
- IoAdHtmlCoreSh
- IoAdHtmlSubsSh
- IoAdInstallBaseSh -- The installer allows one to install a compressed tar file containing some kind of application (modelled through a "IoAdInstallableServiceAdv") or a URL to get to a WWW service (modelled through a "IoAdMimeServiceAdv") onto a users workstation.
- IoAdProxySh -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSearchSh -- The SearchLib CSC provides a set of searching capabilities for approved advertisements, for the administration of groups, and for moderation of requests.
- IoAdServerSh -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSubsSh -- The SubsLib CSC provides a set of derived classes which represent different types of advertisements: products, services, and providers.

process loAdInstallForm

/ecs/formal/IOS/AdvService/src/Progs

Main program for both showing install forms for services and processes the form when complete.

Libraries Linked

- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.

Shared Libraries Linked

- agenteventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsEmMailRelASh -- This Library is used for the emails using sendmail utility and the nnpst for Bulletin board messages.
- CsFtFTPRelASh -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObjSh -- This library provides functions to use FTP at a scheduled time by the User.
- DsClSh -- This library contains classes which make up the Science Data Server's (SDSRV) public interface. These classes are used by clients to connect, build commands, and submit requests to the SDSRV.
- DsCnSh -- This library was used to generate files which install ESDT configuration information for each ESDT previously.
- DsShSh -- This internal library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- EcCfSh -- The Config library (CF) is a shared library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistrySh
- EcDcMsgPng1Sh -- This library consists of message passing objects used by both the client and server side.
- EcDnDirSh -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcFhSh -- This library provides fault handling capabilities to ECS applications.
- EcHtSh -- This library provides classes that contain operations to handle all HTML tags.
- EcNsServiceLocatorSh -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcNsServiceLocSh -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.

- EcPfSh -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPoDbRWSH
- EcPoSh -- The Persistent CSC provides a set of abstract and base classes for approved advertisements and requests.
- EcPtSpecialLockSh -- This library provides classes for mutex operations and thread IDs.
- EcSeCmiSh -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeLoginContextSh -- This library uses the key obtained from either the EcSeServerKeyMgmt or EcSeAuthn library to establish a login context for a process.
- EcSeServerKeyMgmtSh -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbedSh -- This shared Library has only the methods for completing the successful compilation.
- EcSeUtilityDbStubbedSh -- This shared Library provides stubbed version of EcSeUtilityDb for successful compilation.
- EcTiTimeSh -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUrSh -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUtFactorySh -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtMiscSh -- The EcUtMisc library contains miscellaneous utilities.
- EcUtSh -- EcUt is a utility library for all the ECS applications.
- eventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- GlSh -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.
- IoAdCoreSh -- The CoreLib CSC provides a set of functionalities for describing a generic advertisement, parsing and validating attributes that support the ECS Core meta data model, and requesting and moderating advertisements.
- IoAdHtmlCoreSh
- IoAdHtmlSubsSh
- IoAdInstallBaseSh -- The installer allows one to install a compressed tar file containing some kind of application (modelled through a "IoAdInstallableServiceAdv") or a URL to get to a WWW service (modelled through a "IoAdMimeServiceAdv") onto a users workstation.
- IoAdProxySh -- The ServerLib CSC provides classes for process framework DCE server and client.

- IoAdSearchSh -- The SearchLib CSC provides a set of searching capabilities for approved advertisements, for the administration of groups, and for moderation of requests.
- IoAdServerSh -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSubsSh -- The SubsLib CSC provides a set of derived classes which represent different types of advertisements: products, services, and providers.

script EcCgiWrapper

/ecs/formal/IOS/AdvService/src/EcHtmlLib

This cgibin program is used to fix common cgibin problems. This should always be called first and it will call the intended cgibin programs. We use the URL technique of path-prefixing to support this.

script EcIoAdServerRun

/ecs/formal/IOS/AdvService/src/Server

script EcReplace

/ecs/formal/IOS/AdvService/src/EcHtmlLib

A generic script for replacing strings inside files.

Subsystem PLS

The Planning Subsystem (PLS) supports the operations staff in managing the data productions activities at a site. It assists with two major functions:

- * Defining the data processing tasks (processes to run) to be performed at a site.
- * Generating efficient data productions plans for the scheduling of those tasks.

In addition, PLS coordinates the procedure with the Data Server and Data processing subsystems to achieve a highly automated productions system.

process EcPIPREditor

/ecs/formal/PDPS/PLS/PLANG/src/PRE_GUI

The production request editor GUI is a utility which provides operations personnel with the capability to define Production Requests (PRs) that are used as part of the planning process. This GUI is constructed with the aid of

Builder xcessory and combined with custom code which interfaces to the planning database for storage of PRs.

This utility application allows the users to enter production requests into the PDPS production system. The production requests are "exploded" into data processing requests, which may then be inspected within the GUI.

Libraries Linked

- agentevent -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsEmMailRelA -- This Library is used for the emails using sendmail utility and the nnpst for Bulletin board messages.
- CsFtFTPRelA -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObj -- This library provides functions to use FTP at a scheduled time by the User.
- DpDeletionClient -- The library containing the client side operations to issue requests to the deletion server.
- DpPrDbPf -- This library contains the PDPS database interface classes for use with the Process Framework access to the database.
- DpPrDM -- This library supplies utility operations to manage data within DPS.
- DpPrDssIF -- This library contains the helper object for PDPS to interact with science data server.
- DpPrEM -- This library supplies utility operations to manage PGE execution within PRONG.
- DpPrException -- This library provides APIs to catch and handle signals.
- DpPrRM -- This library supplies utility operations to manage computer resources for PDPS.
- DpPrTools -- This library contains global utility functions.
- DsCn -- This library is used to access a server specific configuration file.
- DsSh -- This library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- EcCf -- The Config library (CF) is a static library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistry
- EcDcMsgPsnng1 -- This library consists of message passing objects used by both the client and server side.
- EcDnDir -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcDpJobMgmtClient -- The Job Management Client library provides the following public interfaces to the Job Management Server.
- EcFh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLoc -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.

- EcNsServiceLocator -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcPf -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPo -- The Persistent CSC provides a set of abstract and base classes for approved advertisements and requests.
- EcPoDbRW
- EcPtSpecialLock -- This library provides classes for mutex operations and thread IDs.
- EcSeCmi -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeServerKeyMgmt -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbed -- This static Library is the stubbed version of EcSeSybSecurity.
- EcSeUtilityDbStubbed -- This static Library is stub version of the EcSeUtilityDb library.
- EcTiTime -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUr -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUt -- EcUt is a utility library for all the ECS applications.
- EcUtFactory -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtGUIg_mt_eh_tp
- EcUtHelpg_mt_eh_tp
- EcUtMisc -- This library contains miscellaneous utilities.
- event -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- Gl -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.
- IoAdCore -- The CoreLib CSC provides a set of functionalities for describing a generic advertisement, parsing and validating attributes that support the ECS Core meta data model, and requesting and moderating advertisements.
- IoAdProxy -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSearch -- The SearchLib CSC provides a set of searching capabilities for approved advertisements, for the administration of groups, and for moderation of requests.
- IoAdServer -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSubs -- The SubsLib CSC provides a set of derived classes which represent different types of advertisements: products, services, and providers.

- MsAcClnt -- The Accountability Management Service makes the user profile available to the various subsystems, such as the Data Server subsystem, information such as the user's electronic mail address and the shipping address, which are used for the distribution of
- MsAcComm -- This library contains class used for both Accountability Server and Client
- PICore1 -- This library contains the first half of Planning's core functionality. The CoreLib provides functionality for all areas of Planning. It was divided in half due to its large size...
- PICore2 -- This library contains the second half of Planning's core functionality. The CoreLib provides functionality for all areas of Planning. It was divided in half due to its large size...
- PISSIT -- This library manages the Science Software Integration & Test PDPS DB interfaces.
- PIUtil -- This library contains utilities dealing with current time, time periods, time boundaries, time windows, time intervals, spacecraft, orbit, instruments, and also manages their DB interfaces.

process EcPIPREditor_IF

/ecs/formal/PDPS/PLS/PLANG/src/PRE_GUI

The Planning User Interface (Production Request Editor) allows the Operations staff to submit production requests to describing the data products to generate. The production request uses the PGE descriptions (profiles) entered during Algorithm Integration and Test (AI&T) to define the Data Processing Requests. The request adds, modifies, and deletes Production Requests, and reviews and modifies the resulting Data Processing Requests. The user specifies rules for producing the individual DPRs for the reprocessing requests. The production request editor is a distinct application and separate from the workbench because defining a production request is unrelated to the planning of a production request.

Libraries Linked

- agentevent -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsEmMailRelA -- This Library is used for the emails using sendmail utility and the nnpst for Bulletin board messages.
- CsFtFTPRelA -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObj -- This library provides functions to use FTP at a scheduled time by the User.
- DpDeletionClient -- The library containing the client side operations to issue requests to the deletion server.
- DpPrDbPf -- This library contains the PDPS database interface classes for use with the Process Framework access to the database.
- DpPrDM -- This library supplies utility operations to manage data within DPS.
- DpPrDssIF -- This library contains the helper object for PDPS to interact with science data server.
- DpPrEM -- This library supplies utility operations to manage PGE execution within PRONG.

- DpPrException -- This library provides APIs to catch and handle signals.
- DpPrRM -- This library supplies utility operations to manage computer resources for PDPS.
- DpPrTools -- This library contains global utility functions.
- DsCl -- This library contains classes which make up the Science Data Server's (SDSRV) public interface. These classes are used by clients to connect, build commands, and submit requests to the SDSRV.
- DsCn -- This library is used to access a server specific configuration file.
- DsSh -- This library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- EcCf -- The Config library (CF) is a static library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistry
- EcDcMsgPsgn1 -- This library consists of message passing objects used by both the client and server side.
- EcDnDir -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcDpJobMgmtClient -- The Job Management Client library provides the following public interfaces to the Job Management Server.
- EcFh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLoc -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcNsServiceLocator -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcPf -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPo -- The Persistent CSC provides a set of abstract and base classes for approved advertisements and requests.
- EcPoDbRW
- EcPtSpecialLock -- This library provides classes for mutex operations and thread IDs.
- EcSbCl -- This library contains all the classes for Subscription Server client.
- EcSbMsg -- This library contains all message classes used for the communication between Subscription Server and its client objects provided by Subscription Server client library.
- EcSeCmi -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).

- EcSeServerKeyMgmt -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbed -- This static Library is the stubbed version of EcSeSybSecurity.
- EcSeUtilityDbStubbed -- This static Library is stub version of the EcSeUtilityDb library.
- EcTiTime -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUr -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUt -- EcUt is a utility library for all the ECS applications.
- EcUtFactory -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtGUIg_mt_eh_tp
- EcUtHelpg_mt_eh_tp
- EcUtMisc -- This library contains miscellaneous utilities.
- event -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- Gl -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.
- IoAdCore -- The CoreLib CSC provides a set of functionalities for describing a generic advertisement, parsing and validating attributes that support the ECS Core meta data model, and requesting and moderating advertisements.
- IoAdProxy -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSearch -- The SearchLib CSC provides a set of searching capabilities for approved advertisements, for the administration of groups, and for moderation of requests.
- IoAdServer -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSubs -- The SubsLib CSC provides a set of derived classes which represent different types of advertisements: products, services, and providers.
- MsAcClnt -- The Accountability Management Service makes the user profile available to the various subsystems, such as the Data Server subsystem, information such as the user's electronic mail address and the shipping address, which are used for the distribution of
- MsAcComm -- This library contains class used for both Accountability Server and Client
- PlCore1IF -- This library contains the Science Data Server, advertisement, and subscription server interfaces that are needed to run the Production request editor.
- PlCore2 -- This library contains the second half of Planning's core functionality. The CoreLib provides functionality for all areas of Planning. It was divided in half due to its large size...
- PlSSIT -- This library manages the Science Software Integration & Test PDPS DB interfaces.

- PIUtil -- This library contains utilities dealing with current time, time periods, time boundaries, time windows, time intervals, spacecraft, orbit, instruments, and also manages their DB interfaces.
- srf -- The SRF library provides the necessary mechanism for the application to communicate asynchronously with another application.

process EcPIProdStrat

/ecs/formal/PDPS/PLS/PLANG/src/PIGui

The EcPIProdStrat GUI allows the user/operator to have control over the strategies used to determine priorities of the Data Processing Requests that are in a plan. Each plan will have a particular set of production strategies that are keyed to it, but the same production strategies can be used in multiple plans.

This GUI is developed with the aid of Builder xcessory (BX) and combined with custom code which interfaces to the planning database.

Production Strategies work on two levels. First the operator can update lists of DPR attributes such as PGE Type, Production Request Type and User Type. Each value an attribute can have is tied to a particular priority. Next the operator can change the weight that each attribute's priority is given. A weight is also given to the priority selected by the user who entered the request. In this way, a priority can be calculated for each DPR. There are number of deltas that can be added to the calculated priority

based on certain conditions. For example, an operator may select to increase the priority of all jobs that produce data that is needed by other DAACs or that have been waiting in the production queue for more than a day.

Classes

- PIProdStratActive -- This class provides a dialog box for displaying the Active strategies screen as part of the Production Strategy GUI.
- PIProdStratClient -- End of code for accessing the main window This class was created to make this program a client..
- PIProdStratClusterPriority -- This class provides a dialog box for displaying the Cluster Priorities screen as part of the Production Strategy GUI.
- PIProdStratDelete -- This class provides a dialog box for displaying the Delete screen as part of the Production Strategy GUI.
- PIProdStratExit -- This class provides a dialog box for displaying the Exit screen as part of the Production Strategy GUI.
- PIProdStratMainForm -- Created by Builder Xcessory Version 5.0.3.
- PIProdStratOpen -- This class provides a dialog box for displaying the open screen as part of the Production Strategy GUI.
- PIProdStratSaveAs -- This class provides a dialog box for displaying the SaveAs screen as part of the Production Strategy GUI.
- UIComponent -- Base class for all C++/Motif UI components.

Libraries Linked

- agentevent -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsFtFTPReIA -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObj -- This library provides functions to use FTP at a scheduled time by the User.
- DpDeletionClient -- The library containing the client side operations to issue requests to the deletion server.
- DpPrDbPf -- This library contains the PDPS database interface classes for use with the Process Framework access to the database.
- DpPrDM -- This library supplies utility operations to manage data within DPS.
- DpPrDssIF -- This library contains the helper object for PDPS to interact with science data server.
- DpPrEM -- This library supplies utility operations to manage PGE execution within PRONG.
- DpPrException -- This library provides APIs to catch and handle signals.
- DpPrRM -- This library supplies utility operations to manage computer resources for PDPS.
- DpPrTools -- This library contains global utility functions.
- DsCl -- This library contains classes which make up the Science Data Server's (SDSRV) public interface. These classes are used by clients to connect, build commands, and submit requests to the SDSRV.
- DsCn -- This library is used to access a server specific configuration file.
- DsSh -- This library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- EcCf -- The Config library (CF) is a static library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistry
- EcDcMsgPsnng1 -- This library consists of message passing objects used by both the client and server side.
- EcDnDir -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcDpJobMgmtClient -- The Job Management Client library provides the following public interfaces to the Job Management Server.
- EcFh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLoc -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.

- EcNsServiceLocator -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcPf -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPo -- The Persistent CSC provides a set of abstract and base classes for approved advertisements and requests.
- EcPoDbRW
- EcPtSpecialLock -- This library provides classes for mutex operations and thread IDs.
- EcSeCmi -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeServerKeyMgmt -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbed -- This static Library is the stubbed version of EcSeSybSecurity.
- EcSeUtilityDbStubbed -- This static Library is stub version of the EcSeUtilityDb library.
- EcTiTime -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUr -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUt -- EcUt is a utility library for all the ECS applications.
- EcUtFactory -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtGUIg_mt_eh_tp
- EcUtHelpg_mt_eh_tp
- EcUtMisc -- This library contains miscellaneous utilities.
- event -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- Gl -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.
- IoAdCore -- The CoreLib CSC provides a set of functionalities for describing a generic advertisement, parsing and validating attributes that support the ECS Core meta data model, and requesting and moderating advertisements.
- IoAdProxy -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSearch -- The SearchLib CSC provides a set of searching capabilities for approved advertisements, for the administration of groups, and for moderation of requests.
- IoAdServer -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSubs -- The SubsLib CSC provides a set of derived classes which represent different types of advertisements: products, services, and providers.

- PICore1 -- This library contains the first half of Planning's core functionality. The CoreLib provides functionality for all areas of Planning. It was divided in half due to its large size...
- PICore2 -- This library contains the second half of Planning's core functionality. The CoreLib provides functionality for all areas of Planning. It was divided in half due to its large size...
- PISSIT -- This library manages the Science Software Integration & Test PDPS DB interfaces.
- PIUtil -- This library contains utilities dealing with current time, time periods, time boundaries, time windows, time intervals, spacecraft, orbit, instruments, and also manages their DB interfaces.

process EcPIRm

/ecs/formal/PDPS/PLS/PLANG/src/PWB/rm/src

The Resource Model is a background process to manage resources, activities, and plans through the model/view communication architecture and protocols, along with responsibility of interfacing with PDPS database. It constructs all the activity pools through the database interface, and also is responsible for handling the different kinds of manipulation requests from all its maintained pools, and keeping the consistency of pools among registered Noids.

Classes

- PIRmAppl -- Instances of PIRmAppl are resource model applications.
- PIRmCatalog -- An instance of PIRmCatalog is owned by a PIRmSrm client.
- PIRmSigHand -- Instances of PIRmSigHand are signal catchers for a resource model to detect termination signals and save our resource model states.
- PIRmSrm -- Instances of PIRmSrm are resource model editors that know about ecs notions, plan accesses, etc.
- PIRmSrmNoid -- The PIRmSrmNoid is an ipc msgAgent that services resource model requests.

Libraries Linked

- agentevent -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsFtFTPReIA -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObj -- This library provides functions to use FTP at a scheduled time by the User.
- DpDeletionClient -- The library containing the client side operations to issue requests to the deletion server.
- DpPrDbPf -- This library contains the PDPS database interface classes for use with the Process Framework access to the database.
- DpPrDM -- This library supplies utility operations to manage data within DPS.

- DpPrDssIF -- This library contains the helper object for PDPS to interact with science data server.
- DpPrEM -- This library supplies utility operations to manage PGE execution within PRONG.
- DpPrException -- This library provides APIs to catch and handle signals.
- DpPrRM -- This library supplies utility operations to manage computer resources for PDPS.
- DpPrTools -- This library contains global utility functions.
- DsCl -- This library contains classes which make up the Science Data Server's (SDSRV) public interface. These classes are used by clients to connect, build commands, and submit requests to the SDSRV.
- DsCn -- This library is used to access a server specific configuration file.
- DsSh -- This library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- EcCf -- The Config library (CF) is a static library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistry
- EcDcMsgPsn1 -- This library consists of message passing objects used by both the client and server side.
- EcDnDir -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcDpJobMgmtClient -- The Job Management Client library provides the following public interfaces to the Job Management Server.
- EcFh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLoc -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcNsServiceLocator -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcPf -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPo -- The Persistent CSC provides a set of abstract and base classes for approved advertisements and requests.
- EcPoDbRW
- EcPtSpecialLock -- This library provides classes for mutex operations and thread IDs.
- EcSeCmi -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).

- EcSeServerKeyMgmt -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbed -- This static Library is the stubbed version of EcSeSybSecurity.
- EcSeUtilityDbStubbed -- This static Library is stub version of the EcSeUtilityDb library.
- EcTiTime -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUr -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUt -- EcUt is a utility library for all the ECS applications.
- EcUtFactory -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtMisc -- This library contains miscellaneous utilities.
- event -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- Gl -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.
- IoAdCore -- The CoreLib CSC provides a set of functionalities for describing a generic advertisement, parsing and validating attributes that support the ECS Core meta data model, and requesting and moderating advertisements.
- IoAdProxy -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSearch -- The SearchLib CSC provides a set of searching capabilities for approved advertisements, for the administration of groups, and for moderation of requests.
- IoAdServer -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSubs -- The SubsLib CSC provides a set of derived classes which represent different types of advertisements: products, services, and providers.
- plac -- Activities.
- plcl -- Client resource model (rm) messages, and noid.
- PlCore1 -- This library contains the first half of Planning's core functionality. The CoreLib provides functionality for all areas of Planning. It was divided in half due to its large size...
- PlCore2 -- This library contains the second half of Planning's core functionality. The CoreLib provides functionality for all areas of Planning. It was divided in half due to its large size...
- pldb -- Database Interface.
- plip -- Interprocess Communication Agent.
- plmi -- Miscellaneous.
- plpl -- Plans.
- plrc -- Resources.

- plrm -- Resource Model.
- plsc -- Schedulable Resources.
- PISSIT -- This library manages the Science Software Integration & Test PDPS DB interfaces.
- PIUtil -- This library contains utilities dealing with current time, time periods, time boundaries, time windows, time intervals, spacecraft, orbit, instruments, and also manages their DB interfaces.

process EcPIRpRe

/ecs/formal/PDPS/PLS/PLANG/src/RPL/sre

The Resource Planning Workbench prepares a schedule for the resources at each respective site, and forecasts the start and completion times of the ground events and the impact on the resources used within the schedule. The workbench allows the Operations staff to:

- * Edit the resources currently available at a site.
- * Associate the resources with production strings (logical groupings of resources used by AutoSys and Data Processing) when allocating resources for a particular PGE.
- * Create ground events (maintenance, etc.) on the allocated resources.

Classes

- PIRpReAppl -- Instances of PIRpReAppl are derived PIRpDiAppl's capable of using it's noid to request resources from the resource model.
- PIRpReAutosysWin -- An instance of this class provides a view of the details associated with the selected Autosys resource.
- PIRpReComputerWin -- An instance of this class provides a view of the details associated with the selected computer (host) resource.
- PIRpReConfirmWin -- An instance of the class brings up a confirmation window for deleting the resources.
- PIRpReDateDlg -- An instance of the class brings up a date entry dialog for the MSS resource baseline.
- PIRpReDiskWin -- An instance of this class provides a view of the details associated with the selected disk partition resource.
- PIRpReHardwareWin -- An instance of this class provides a view of the details associated with the selected hardware resource.
- PIRpReMsgBox -- An instance of this provides a message popup box for displaying information to the user.
- PIRpReNoid -- Instances of PIRpReNoids handle resource planning related client noid messages.
- PIRpReRealComputerWin -- An instance of this class provides a view of the details associated with the selected realComputer resource.

- PIRpReSelBox -- An instance of this provides a message popup box for displaying information to the user.
- PIRpReStringWin -- An instance of this class provides a view of the details associated with the selected string resource.
- PIRpReWin -- This class is Motif Window for controlling the setup and display of the resource planning workbench.
- PIRpReWinAbs -- PIRpReWinAbs establishes protocol for System Resource Editor Windows.

Libraries Linked

- agentevent -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsEmMailRelA -- This Library is used for the emails using sendmail utility and the nnpst for Bulletin board messages.
- CsFtFTPRelA -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObj -- This library provides functions to use FTP at a scheduled time by the User.
- DpDeletionClient -- The library containing the client side operations to issue requests to the deletion server.
- DpPrDbPf -- This library contains the PDPS database interface classes for use with the Process Framework access to the database.
- DpPrDM -- This library supplies utility operations to manage data within DPS.
- DpPrDssIF -- This library contains the helper object for PDPS to interact with science data server.
- DpPrEM -- This library supplies utility operations to manage PGE execution within PRONG.
- DpPrException -- This library provides APIs to catch and handle signals.
- DpPrJM -- The Job Management library provides service routines for the Job Management Server to use to manage the flow of jobs in all AutoSys instances for a mode.
- DpPrRM -- This library supplies utility operations to manage computer resources for PDPS.
- DpPrTools -- This library contains global utility functions.
- DpPrUpdateStatus
- DsCl -- This library contains classes which make up the Science Data Server's (SDSRV) public interface. These classes are used by clients to connect, build commands, and submit requests to the SDSRV.
- DsCn -- This library is used to access a server specific configuration file.
- DsSh -- This library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.

- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- EcCf -- The Config library (CF) is a static library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistry
- EcDcMsgPsng1 -- This library consists of message passing objects used by both the client and server side.
- EcDnDir -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcDpJobMgmtClient -- The Job Management Client library provides the following public interfaces to the Job Management Server.
- EcFh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLoc -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcNsServiceLocator -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcPf -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPo -- The Persistent CSC provides a set of abstract and base classes for approved advertisements and requests.
- EcPoDbRW
- EcPtSpecialLock -- This library provides classes for mutex operations and thread IDs.
- EcSeCmi -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeServerKeyMgmt -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbed -- This static Library is the stubbed version of EcSeSybSecurity.
- EcSeUtilityDbStubbed -- This static Library is stub version of the EcSeUtilityDb library.
- EcTiTime -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUr -- A Universal Reference (UR) is created as a logical reference to an extant ECS object.
- EcUt -- EcUt is a utility library for all the ECS applications.
- EcUtFactory -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtMisc -- This library contains miscellaneous utilities.
- event -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.

- GI -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.
- IoAdCore -- The CoreLib CSC provides a set of functionalities for describing a generic advertisement, parsing and validating attributes that support the ECS Core meta data model, and requesting and moderating advertisements.
- IoAdProxy -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSearch -- The SearchLib CSC provides a set of searching capabilities for approved advertisements, for the administration of groups, and for moderation of requests.
- IoAdServer -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSubs -- The SubsLib CSC provides a set of derived classes which represent different types of advertisements: products, services, and providers.
- MsAcClnt -- The Accountability Management Service makes the user profile available to the various subsystems, such as the Data Server subsystem, information such as the user's electronic mail address and the shipping address, which are used for the distribution of
- MsAcComm -- This library contains class used for both Accountability Server and Client
- plac -- Activities.
- PlCore1 -- This library contains the first half of Planning's core functionality. The CoreLib provides functionality for all areas of Planning. It was divided in half due to its large size...
- PlCore2 -- This library contains the second half of Planning's core functionality. The CoreLib provides functionality for all areas of Planning. It was divided in half due to its large size...
- plip -- Interprocess Communication Agent.
- plmi -- Miscellaneous.
- plpl -- Plans.
- PIRpAc -- Manages the scheduling activities.
- PIRpCl -- Manages the resource model clients.
- PIRpDb -- Accesses and modifies the database.
- PIRpDi -- A resource model client display application.
- PIRpRc -- Manages resources.
- PIRpRe -- Manages the Resource Editor GUI.
- PIRpRm -- Manages the resource model.
- PIRpSc -- Manages schedulable resources.
- PlSSIT -- This library manages the Science Software Integration & Test PDPS DB interfaces.
- PlUtil -- This library contains utilities dealing with current time, time periods, time boundaries, time windows, time intervals, spacecraft, orbit, instruments, and also manages their DB interfaces.

process EcPIRpRm

/ecs/formal/PDPS/PLS/PLANG/src/RPL/srm

Classes

- PIRpRmAppl -- Instances of PIRpRmAppl are resource model applications.
- PIRpRmCatalog -- An instance of PIRpRmCatalog is owned by a PIRpRmSrm client.
- PIRpRmSigHand -- Instances of PIRpRmSigHand are signal catchers for a resource model to detect termination signals and save our resource model states.
- PIRpRmSrm -- Instances of PIRpRmSrm are resource model editors that know about ecs notions, plan accesses, etc.
- PIRpRmSrmNoid -- The PIRpRmSrmNoid is an ipc msgAgent that services resource model requests.

Libraries Linked

- agentevent -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsFtFTPRelA -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObj -- This library provides functions to use FTP at a scheduled time by the User.
- DpDeletionClient -- The library containing the client side operations to issue requests to the deletion server.
- DpPrDbPf -- This library contains the PDPS database interface classes for use with the Process Framework access to the database.
- DpPrDssIF -- This library contains the helper object for PDPS to interact with science data server.
- DpPrException -- This library provides APIs to catch and handle signals.
- DpPrRM -- This library supplies utility operations to manage computer resources for PDPS.
- DsCl -- This library contains classes which make up the Science Data Server's (SDSRV) public interface. These classes are used by clients to connect, build commands, and submit requests to the SDSRV.
- DsCn -- This library is used to access a server specific configuration file.
- DsSh -- This library provides underlying DCE(ODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- EcCf -- The Config library (CF) is a static library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.

- EcCsRegistry
- EcDcMsgPsnng1 -- This library consists of message passing objects used by both the client and server side.
- EcDnDir -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcDpJobMgmtClient -- The Job Management Client library provides the following public interfaces to the Job Management Server.
- EcFh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLoc -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcNsServiceLocator -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcPf -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPo -- The Persistent CSC provides a set of abstract and base classes for approved advertisements and requests.
- EcPoDbRW
- EcPtSpecialLock -- This library provides classes for mutex operations and thread IDs.
- EcSeCmi -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeServerKeyMgmt -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbed -- This static Library is the stubbed version of EcSeSybSecurity.
- EcSeUtilityDbStubbed -- This static Library is stub version of the EcSeUtilityDb library.
- EcTiTime -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUr -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUt -- EcUt is a utility library for all the ECS applications.
- EcUtFactory -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtMisc -- This library contains miscellaneous utilities.
- event -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- Gl -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.
- IoAdCore -- The CoreLib CSC provides a set of functionalities for describing a generic advertisement, parsing and validating attributes that support the ECS Core meta data model, and requesting and moderating advertisements.

- plac -- Activities.
- PlCore1 -- This library contains the first half of Planning's core functionality. The CoreLib provides functionality for all areas of Planning. It was divided in half due to its large size...
- PlCore2 -- This library contains the second half of Planning's core functionality. The CoreLib provides functionality for all areas of Planning. It was divided in half due to its large size...
- plip -- Interprocess Communication Agent.
- plmi -- Miscellaneous.
- plpl -- Plans.
- PIRpAc -- Manages the scheduling activities.
- PIRpCl -- Manages the resource model clients.
- PIRpDb -- Accesses and modifies the database.
- PIRpRc -- Manages resources.
- PIRpRm -- Manages the resource model.
- PIRpSc -- Manages schedulable resources.
- PISSIT -- This library manages the Science Software Integration & Test PDPS DB interfaces.
- PIUtil -- This library contains utilities dealing with current time, time periods, time boundaries, time windows, time intervals, spacecraft, orbit, instruments, and also manages their DB interfaces.

process EcPIRpSi

/ecs/formal/PDPS/PLS/PLANG/src/RPL/si

Libraries Linked

- agentevent -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsFtFTPReIA -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObj -- This library provides functions to use FTP at a scheduled time by the User.
- DpDeletionClient -- The library containing the client side operations to issue requests to the deletion server.
- DpPrDbPf -- This library contains the PDPS database interface classes for use with the Process Framework access to the database.
- DpPrDM -- This library supplies utility operations to manage data within DPS.
- DpPrDssIF -- This library contains the helper object for PDPS to interact with science data server.
- DpPrEM -- This library supplies utility operations to manage PGE execution within PRONG.
- DpPrException -- This library provides APIs to catch and handle signals.

- DpPrJM -- The Job Management library provides service routines for the Job Management Server to use to manage the flow of jobs in all AutoSys instances for a mode.
- DpPrRM -- This library supplies utility operations to manage computer resources for PDPS.
- DpPrTools -- This library contains global utility functions.
- DsCl -- This library contains classes which make up the Science Data Server's (SDSRV) public interface. These classes are used by clients to connect, build commands, and submit requests to the SDSRV.
- DsCn -- This library is used to access a server specific configuration file.
- DsSh -- This library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- EcCf -- The Config library (CF) is a static library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistry
- EcDcMsgPsgn1 -- This library consists of message passing objects used by both the client and server side.
- EcDnDir -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcDpJobMgmtClient -- The Job Management Client library provides the following public interfaces to the Job Management Server.
- EcFh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLoc -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcNsServiceLocator -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcPf -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPo -- The Persistent CSC provides a set of abstract and base classes for approved advertisements and requests.
- EcPoDbRW
- EcPtSpecialLock -- This library provides classes for mutex operations and thread IDs.
- EcSeCmi -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeServerKeyMgmt -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbed -- This static Library is the stubbed version of EcSeSybSecurity.

- EcSeUtilityDbStubbed -- This static Library is stub version of the EcSeUtilityDb library.
- EcTiTime -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUr -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUt -- EcUt is a utility library for all the ECS applications.
- EcUtFactory -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtMisc -- This library contains miscellaneous utilities.
- event -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- Gl -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.
- IoAdCore -- The CoreLib CSC provides a set of functionalities for describing a generic advertisement, parsing and validating attributes that support the ECS Core meta data model, and requesting and moderating advertisements.
- IoAdProxy -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSearch -- The SearchLib CSC provides a set of searching capabilities for approved advertisements, for the administration of groups, and for moderation of requests.
- IoAdServer -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSubs -- The SubsLib CSC provides a set of derived classes which represent different types of advertisements: products, services, and providers.
- plac -- Activities.
- PlCore1 -- This library contains the first half of Planning's core functionality. The CoreLib provides functionality for all areas of Planning. It was divided in half due to its large size...
- PlCore2 -- This library contains the second half of Planning's core functionality. The CoreLib provides functionality for all areas of Planning. It was divided in half due to its large size...
- plip -- Interprocess Communication Agent.
- plmi -- Miscellaneous.
- plpl -- Plans.
- PIRpAc -- Manages the scheduling activities.
- PIRpCl -- Manages the resource model clients.
- PIRpDb -- Accesses and modifies the database.
- PIRpDi -- A resource model client display application.
- PIRpRc -- Manages resources.
- PIRpRm -- Manages the resource model.

- PIRpSc -- Manages schedulable resources.
- PIRpSi -- Manages the Resource Scheduler GUI.
- PISSIT -- This library manages the Science Software Integration & Test PDPS DB interfaces.
- PIUtil -- This library contains utilities dealing with current time, time periods, time boundaries, time windows, time intervals, spacecraft, orbit, instruments, and also manages their DB interfaces.

process EcPIRpTI

/ecs/formal/PDPS/PLS/PLANG/src/RPL/tl

Libraries Linked

- agentevent -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsFtFTPRelA -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObj -- This library provides functions to use FTP at a scheduled time by the User.
- DpDeletionClient -- The library containing the client side operations to issue requests to the deletion server.
- DpPrDbPf -- This library contains the PDPS database interface classes for use with the Process Framework access to the database.
- DpPrDM -- This library supplies utility operations to manage data within DPS.
- DpPrDssIF -- This library contains the helper object for PDPS to interact with science data server.
- DpPrEM -- This library supplies utility operations to manage PGE execution within PRONG.
- DpPrException -- This library provides APIs to catch and handle signals.
- DpPrRM -- This library supplies utility operations to manage computer resources for PDPS.
- DpPrTools -- This library contains global utility functions.
- DsCl -- This library contains classes which make up the Science Data Server's (SDSRV) public interface. These classes are used by clients to connect, build commands, and submit requests to the SDSRV.
- DsCn -- This library is used to access a server specific configuration file.
- DsSh -- This library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- EcCf -- The Config library (CF) is a static library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.

- EcCsRegistry
- EcDcMsgPsnng1 -- This library consists of message passing objects used by both the client and server side.
- EcDnDir -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcDpJobMgmtClient -- The Job Management Client library provides the following public interfaces to the Job Management Server.
- EcFh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLoc -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcNsServiceLocator -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcPf -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPo -- The Persistent CSC provides a set of abstract and base classes for approved advertisements and requests.
- EcPoDbRW
- EcPtSpecialLock -- This library provides classes for mutex operations and thread IDs.
- EcSeCmi -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeServerKeyMgmt -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbed -- This static Library is the stubbed version of EcSeSybSecurity.
- EcSeUtilityDbStubbed -- This static Library is stub version of the EcSeUtilityDb library.
- EcTiTime -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUr -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUt -- EcUt is a utility library for all the ECS applications.
- EcUtFactory -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtMisc -- This library contains miscellaneous utilities.
- event -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- Gl -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.
- IoAdCore -- The CoreLib CSC provides a set of functionalities for describing a generic advertisement, parsing and validating attributes that support the ECS Core meta data model, and requesting and moderating advertisements.

- IoAdProxy -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSearch -- The SearchLib CSC provides a set of searching capabilities for approved advertisements, for the administration of groups, and for moderation of requests.
- IoAdServer -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSubs -- The SubsLib CSC provides a set of derived classes which represent different types of advertisements: products, services, and providers.
- plac -- Activities.
- PlCore1 -- This library contains the first half of Planning's core functionality. The CoreLib provides functionality for all areas of Planning. It was divided in half due to its large size...
- PlCore2 -- This library contains the second half of Planning's core functionality. The CoreLib provides functionality for all areas of Planning. It was divided in half due to its large size...
- plip -- Interprocess Communication Agent.
- plmi -- Miscellaneous.
- plpl -- Plans.
- PIRpAc -- Manages the scheduling activities.
- PIRpCl -- Manages the resource model clients.
- PIRpDb -- Accesses and modifies the database.
- PIRpRc -- Manages resources.
- PIRpSc -- Manages schedulable resources.
- PIRpTl -- Manages the scheduled Resources' Timeline GUI.
- PISSIT -- This library manages the Science Software Integration & Test PDPS DB interfaces.
- PIUtil -- This library contains utilities dealing with current time, time periods, time boundaries, time windows, time intervals, spacecraft, orbit, instruments, and also manages their DB interfaces.

process EcPISubMgr

/ecs/formal/PDPS/PLS/PLANG/src/SubsMgr

The Subscription Manager (EcPISubMgr) is used to manage the receipt of subscription notifications from the Data Server.

These notifications inform Planning of the arrival of input data required by a given PGE through Universal References to the data which is stored on the Data Server. The Subscription Manager updates data availability information within the PDPS database based on this notification, and releases jobs defined by Data Processing Request to the Processing Subsystem when all input data for a job becomes available. The Subscription Manager can also resubmit a subscription when a cancellation notification for that subscription is received, if the PDPS database indicate this data is still in need.

The Subscription Manager also has a "delayed query" feature which allows it to set up a timer for a query if the data is not available at the moment. Then when the timer goes off, the tool will query the Data Server for the data. The Subscription Manager can also support various production rules.

Classes

- PINotification -- This object encapsulates the persistent storage of Subscription notification for PDPS.
- PISubMsgCb -- This class provides the main command logic to the subscription manager.
- PISubscriptionManager -- This class is the main application class for the subscription manager.

Libraries Linked

- agentevent -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsFtFTPRelA -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObj -- This library provides functions to use FTP at a scheduled time by the User.
- DpDeletionClient -- The library containing the client side operations to issue requests to the deletion server.
- DpPrDbPf -- This library contains the PDPS database interface classes for use with the Process Framework access to the database.
- DpPrDM -- This library supplies utility operations to manage data within DPS.
- DpPrDssIF -- This library contains the helper object for PDPS to interact with science data server.
- DpPrEM -- This library supplies utility operations to manage PGE execution within PRONG.
- DpPrException -- This library provides APIs to catch and handle signals.
- DpPrRM -- This library supplies utility operations to manage computer resources for PDPS.
- DpPrTools -- This library contains global utility functions.
- DsCl -- This library contains classes which make up the Science Data Server's (SDSRV) public interface. These classes are used by clients to connect, build commands, and submit requests to the SDSRV.
- DsCn -- This library is used to access a server specific configuration file.
- DsSh -- This library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.

- EcCf -- The Config library (CF) is a static library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistry
- EcDcMsgPsnng1 -- This library consists of message passing objects used by both the client and server side.
- EcDnDir -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcDpJobMgmtClient -- The Job Management Client library provides the following public interfaces to the Job Management Server.
- EcFh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLoc -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcNsServiceLocator -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcPf -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPo -- The Persistent CSC provides a set of abstract and base classes for approved advertisements and requests.
- EcPoDbRW
- EcPtSpecialLock -- This library provides classes for mutex operations and thread IDs.
- EcSbCl -- This library contains all the classes for Subscription Server client.
- EcSbMsg -- This library contains all message classes used for the communication between Subscription Server and its client objects provided by Subscription Server client library.
- EcSeCmi -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeServerKeyMgmt -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbed -- This static Library is the stubbed version of EcSeSybSecurity.
- EcSeUtilityDbStubbed -- This static Library is stub version of the EcSeUtilityDb library.
- EcTiTime -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUr -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUt -- EcUt is a utility library for all the ECS applications.
- EcUtFactory -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtMisc -- This library contains miscellaneous utilities.

- event -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- GI -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.
- IoAdCore -- The CoreLib CSC provides a set of functionalities for describing a generic advertisement, parsing and validating attributes that support the ECS Core meta data model, and requesting and moderating advertisements.
- IoAdProxy -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSearch -- The SearchLib CSC provides a set of searching capabilities for approved advertisements, for the administration of groups, and for moderation of requests.
- IoAdServer -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSubs -- The SubsLib CSC provides a set of derived classes which represent different types of advertisements: products, services, and providers.
- MsAcCInt -- The Accountability Management Service makes the user profile available to the various subsystems, such as the Data Server subsystem, information such as the user's electronic mail address and the shipping address, which are used for the distribution of
- MsAcComm -- This library contains class used for both Accountability Server and Client
- PICore1IF -- This library contains the Science Data Server, advertisement, and subscription server interfaces that are needed to run the Production request editor.
- PICore2 -- This library contains the second half of Planning's core functionality. The CoreLib provides functionality for all areas of Planning. It was divided in half due to its large size...
- PISSIT -- This library manages the Science Software Integration & Test PDPS DB interfaces.
- PIUtil -- This library contains utilities dealing with current time, time periods, time boundaries, time windows, time intervals, spacecraft, orbit, instruments, and also manages their DB interfaces.
- srf -- The SRF library provides the necessary mechanism for the application to communicate asynchronously with another application.

process EcPISubsEdit

/ecs/formal/PDPS/PLS/PLANG/src/SubsEdit

The Subscription Editor is an PDPS/PLS tool for submitting the subscriptions to the Subscription Server.

The Subscription Editor(EcPISubsEdit) can submit subscriptions for the Subscription Manager or a general user who would like to be notified through e-mail. This tool looks for the advertisement of subscribable events through the Advertisement Server and then submit the subscription for that event to the Subscription Server. This is a command-line tool used as a backup for automatic submission of subscription by the Production Request Editor.

Classes

- PISubsEditProc -- This is the only class for program Subscription Editor, and it carries out all the required functionalities.

Libraries Linked

- agentevent -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsFtFTPRelA -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObj -- This library provides functions to use FTP at a scheduled time by the User.
- DpDeletionClient -- The library containing the client side operations to issue requests to the deletion server.
- DpPrDbPf -- This library contains the PDPS database interface classes for use with the Process Framework access to the database.
- DpPrDM -- This library supplies utility operations to manage data within DPS.
- DpPrDssIF -- This library contains the helper object for PDPS to interact with science data server.
- DpPrEM -- This library supplies utility operations to manage PGE execution within PRONG.
- DpPrException -- This library provides APIs to catch and handle signals.
- DpPrRM -- This library supplies utility operations to manage computer resources for PDPS.
- DpPrTools -- This library contains global utility functions.
- DsCl -- This library contains classes which make up the Science Data Server's (SDSRV) public interface. These classes are used by clients to connect, build commands, and submit requests to the SDSRV.
- DsCn -- This library is used to access a server specific configuration file.
- DsSh -- This library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- EcCf -- The Config library (CF) is a static library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistry
- EcDcMsgPsgn1 -- This library consists of message passing objects used by both the client and server side.
- EcDnDir -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.

- EcDpJobMgmtClient -- The Job Management Client library provides the following public interfaces to the Job Management Server.
- EcFh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLoc -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcNsServiceLocator -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcPf -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPo -- The Persistent CSC provides a set of abstract and base classes for approved advertisements and requests.
- EcPoDbRW
- EcPtSpecialLock -- This library provides classes for mutex operations and thread IDs.
- EcSbCl -- This library contains all the classes for Subscription Server client.
- EcSbMsg -- This library contains all message classes used for the communication between Subscription Server and its client objects provided by Subscription Server client library.
- EcSeCmi -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeServerKeyMgmt -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbed -- This static Library is the stubbed version of EcSeSybSecurity.
- EcSeUtilityDbStubbed -- This static Library is stub version of the EcSeUtilityDb library.
- EcTiTime -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUr -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUt -- EcUt is a utility library for all the ECS applications.
- EcUtFactory -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtMisc -- This library contains miscellaneous utilities.
- event -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- Gl -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.
- IoAdCore -- The CoreLib CSC provides a set of functionalities for describing a generic advertisement, parsing and validating attributes that support the ECS Core meta data model, and requesting and moderating advertisements.
- IoAdProxy -- The ServerLib CSC provides classes for process framework DCE server and client.

- IoAdSearch -- The SearchLib CSC provides a set of searching capabilities for approved advertisements, for the administration of groups, and for moderation of requests.
- IoAdServer -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSubs -- The SubsLib CSC provides a set of derived classes which represent different types of advertisements: products, services, and providers.
- MsAcClnt -- The Accountability Management Service makes the user profile available to the various subsystems, such as the Data Server subsystem, information such as the user's electronic mail address and the shipping address, which are used for the distribution of
- MsAcComm -- This library contains class used for both Accountability Server and Client
- PICore1IF -- This library contains the Science Data Server, advertisement, and subscription server interfaces that are needed to run the Production request editor.
- PICore2 -- This library contains the second half of Planning's core functionality. The CoreLib provides functionality for all areas of Planning. It was divided in half due to its large size...
- PISSIT -- This library manages the Science Software Integration & Test PDPS DB interfaces.
- PIUtil -- This library contains utilities dealing with current time, time periods, time boundaries, time windows, time intervals, spacecraft, orbit, instruments, and also manages their DB interfaces.
- srf -- The SRF library provides the necessary mechanism for the application to communicate asynchronously with another application.

process EcPITI

/ecs/formal/PDPS/PLS/PLANG/src/PWB/tl/src

The Timeline GUI is a tool to visualize the schedule of pre-selected resources for different kinds of activities which will eventually be sent to DPS for processing.

The appearance of a visualized plan can be customized by users through changing the time range and selecting the zoom options. Accordingly the configuration can be saved for future reuse. And also the colors of the activities lined-up for each resource can be customized for distinguishing the different PRs and Ground Events. The Timeline GUI is also capable of buffering customized plans, which enables users to quickly switch from one plan to another.

Libraries Linked

- agentevent -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsFtFTPRelA -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObj -- This library provides functions to use FTP at a scheduled time by the User.
- DpDeletionClient -- The library containing the client side operations to issue requests to the deletion server.

- DpPrDbPf -- This library contains the PDPS database interface classes for use with the Process Framework access to the database.
- DpPrDM -- This library supplies utility operations to manage data within DPS.
- DpPrDssIF -- This library contains the helper object for PDPS to interact with science data server.
- DpPrEM -- This library supplies utility operations to manage PGE execution within PRONG.
- DpPrException -- This library provides APIs to catch and handle signals.
- DpPrRM -- This library supplies utility operations to manage computer resources for PDPS.
- DpPrTools -- This library contains global utility functions.
- DsCl -- This library contains classes which make up the Science Data Server's (SDSRV) public interface. These classes are used by clients to connect, build commands, and submit requests to the SDSRV.
- DsCn -- This library is used to access a server specific configuration file.
- DsSh -- This library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- EcCf -- The Config library (CF) is a static library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistry
- EcDcMsgPsngr1 -- This library consists of message passing objects used by both the client and server side.
- EcDnDir -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcDpJobMgmtClient -- The Job Management Client library provides the following public interfaces to the Job Management Server.
- EcFh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLoc -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcNsServiceLocator -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcPf -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPo -- The Persistent CSC provides a set of abstract and base classes for approved advertisements and requests.
- EcPoDbRW
- EcPtSpecialLock -- This library provides classes for mutex operations and thread IDs.

- EcSeCmi -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeServerKeyMgmt -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbed -- This static Library is the stubbed version of EcSeSybSecurity.
- EcSeUtilityDbStubbed -- This static Library is stub version of the EcSeUtilityDb library.
- EcTiTime -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUr -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUt -- EcUt is a utility library for all the ECS applications.
- EcUtFactory -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtMisc -- This library contains miscellaneous utilities.
- event -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- Gl -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.
- IoAdCore -- The CoreLib CSC provides a set of functionalities for describing a generic advertisement, parsing and validating attributes that support the ECS Core meta data model, and requesting and moderating advertisements.
- IoAdProxy -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSearch -- The SearchLib CSC provides a set of searching capabilities for approved advertisements, for the administration of groups, and for moderation of requests.
- IoAdServer -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSubs -- The SubsLib CSC provides a set of derived classes which represent different types of advertisements: products, services, and providers.
- plac -- Activities.
- plcl -- Client resource model (rm) messages, and noid.
- PlCore1 -- This library contains the first half of Planning's core functionality. The CoreLib provides functionality for all areas of Planning. It was divided in half due to its large size...
- PlCore2 -- This library contains the second half of Planning's core functionality. The CoreLib provides functionality for all areas of Planning. It was divided in half due to its large size...
- pldb -- Database Interface.
- pldi -- Common Displayable (motif) components.
- plip -- Interprocess Communication Agent.

- plmi -- Miscellaneous.
- plpl -- Plans.
- plrc -- Resources.
- plrm -- Resource Model.
- plsc -- Schedulable Resources.
- PISSIT -- This library manages the Science Software Integration & Test PDPS DB interfaces.
- pltl -- Timeline.
- PIUtil -- This library contains utilities dealing with current time, time periods, time boundaries, time windows, time intervals, spacecraft, orbit, instruments, and also manages their DB interfaces.

script EcPIStartProdStrat

/ecs/formal/PDPS/PLS/PLANG/src/PIGui

script RunReportDaily

/ecs/formal/PDPS/PLS/PLANG/src/InsertReport

Change working directory to the data directory, this is where the data files to generate the reports live, and where the reports will be generated also.

script RunReports

/ecs/formal/PDPS/PLS/PLANG/src/InsertReport

Setup batch jobs for RunReportDaily and RunReportWeekly.

script RunReportWeekly

/ecs/formal/PDPS/PLS/PLANG/src/InsertReport

Change working directory to the data directory, this is where the data files to generate the reports live, and where the reports will be generated also.

Subsystem DPS

The Data Processing Subsystem (DPS) executes Data Processing actions and manages the data processing resources at a provider site.

process EcDpAtBadFunc

/ecs/formal/PDPS/DPS/SSIT/src/PRO

This program is the command-line version of the Prohibited Function Checker tool. It allows the user to specify a source code file and checks for any prohibited functions within that file.

The Prohibited Function Checker Tool (GUI or command line) uses the files named "prohibitedFunctions" (with the language appended) to determine the list of prohibited functions

for a given source code file. It parses the source file, and compares non-commented code against the prohibited function files.

The output file from the command-line version of the Prohibited Function Checker Tool is placed in the destination specified in the Process Control File (PCF) for SSIT.

To learn how to run the Prohibited Function Checker, see the file DpAtMgr_pro.html in ClearCase under SSIT/src/PRO, or on a machine where SSIT is installed under /usr/ecs/<MODE>/CUSTOM/WWW/DPS.

Classes

- DpAtMgrDirectory -- This class manages directory information.
- DpAtMgrProhibited -- This class manages prohibited function data.
- DpAtMgrSource -- This class holds parsed source code information.

Libraries Linked

- agentevent -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsFtFTPReIA -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObj -- This library provides functions to use FTP at a scheduled time by the User.
- DpAt -- This DpAt library holds the SSIT classes that are called by various SSIT tools and programs.
- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- EcCf -- The Config library (CF) is a static library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistry
- EcDcMsgPsnng1 -- This library consists of message passing objects used by both the client and server side.
- EcDnDir -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcFh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLoc -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcNsServiceLocator -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcPf -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPoDbRW

- EcPtSpecialLock -- This library provides classes for mutex operations and thread IDs.
- EcSeCmi -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeServerKeyMgmt -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbed -- This static Library is the stubbed version of EcSeSybSecurity.
- EcSeUtilityDbStubbed -- This static Library is stub version of the EcSeUtilityDb library.
- EcTiTime -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUr -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUt -- EcUt is a utility library for all the ECS applications.
- EcUtFactory -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- event -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.

process EcDpAtBadFuncGui

/ecs/formal/PDPS/DPS/SSIT/src/PRO

This program is the graphical interface version of the Prohibited Function Checker tool. It allows the user to select one or more source code files and performs a check for any prohibited functions within those file(s).

The Prohibited Function Checker Tool (GUI or command line) uses the files named "prohibitedFunctions" (with the language appended) to determine the list of prohibited functions for a given source code file. It parses the source file, and compares non-commented code against the prohibited function files.

The output from the GUI version of the Prohibited Function Checker Tool appears in a window display and allows the user to cycle through any prohibited functions found. This output may also be written to a file.

To learn how to run the Prohibited Function Checker, see the file DpAtMgr_pro.html in ClearCase under SSIT/src/PRO, or on a machine where SSIT is installed under /usr/ecs/<MODE>/CUSTOM/WWW/DPS.

Classes

- DpAtMgrDirectory -- This class manages directory information.
- DpAtMgrProhibited -- This class manages prohibited function data.
- DpAtMgrProhibitedFunctionGui -- This class defines the SSIT Prohibited Function GUI.
- DpAtMgrSource -- This class holds parsed source code information.

Libraries Linked

- agentevent -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsFtFTPReLA -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObj -- This library provides functions to use FTP at a scheduled time by the User.
- DpAt -- This DpAt library holds the SSIT classes that are called by various SSIT tools and programs.
- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- EcCf -- The Config library (CF) is a static library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistry
- EcDcMsgPsngr1 -- This library consists of message passing objects used by both the client and server side.
- EcDnDir -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcFh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLoc -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcNsServiceLocator -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcPf -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPoDbRW
- EcPtSpecialLock -- This library provides classes for mutex operations and thread IDs.
- EcSeCmi -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeServerKeyMgmt -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbed -- This static Library is the stubbed version of EcSeSybSecurity.
- EcSeUtilityDbStubbed -- This static Library is stub version of the EcSeUtilityDb library.
- EcTiTime -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUr -- A Universal Reference (UR) is created as a logical reference to an extant ECS object.
- EcUt -- EcUt is a utility library for all the ECS applications.

- EcUtFactory -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- event -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.

process EcDpAtBinDiffGui

/ecs/formal/PDPS/DPS/SSIT/src/DIF

The Binary Difference Assistant GUI provides the SSIT operator with a graphical interface to create programs in C, FORTRAN, IDL and shell script for determining differences between binary files.

Templates for C, FORTRAN, IDL and shell scripts are provided with the program and are accessible through the interface. The GUI allows the user to create and compile programs to compare binary files of various formats.

To learn how to run the Binary Difference Assistant GUI, see the file DpAtMgr_bidiff.html in ClearCase under SSIT/src/DIF, or on a machine where SSIT is installed under /usr/ecs/<MODE>/CUSTOM/WWW/DPS.

Classes

- DpAtMgrBinDiffGuiEnterUniqueIDFORM
- DpAtMgrBinDiffGuihelpFORM -- This class defines the form for the help message on the SSIT Bin Diff GUI.
- DpAtMgrBinDiffGuiMainBBoard -- This class defines the Bulliten Board for the SSIT Bin Diff GUI.
- DpAtMgrBinDiffGuiScrollWindow -- This class defines the scroll bar for the SSIT Bin Diff GUI.

Libraries Linked

- agentevent -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsFtFTPRelA -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObj -- This library provides functions to use FTP at a scheduled time by the User.
- DpAt -- This DpAt library holds the SSIT classes that are called by various SSIT tools and programs.
- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- EcCf -- The Config library (CF) is a static library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistry

- EcDcMsgPsng1 -- This library consists of message passing objects used by both the client and server side.
- EcDnDir -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcFh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLoc -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcNsServiceLocator -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcPf -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPoDbRW
- EcPtSpecialLock -- This library provides classes for mutex operations and thread IDs.
- EcSeCmi -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeServerKeyMgmt -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbed -- This static Library is the stubbed version of EcSeSybSecurity.
- EcSeUtilityDbStubbed -- This static Library is stub version of the EcSeUtilityDb library.
- EcTiTime -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUr -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUt -- EcUt is a utility library for all the ECS applications.
- EcUtFactory -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- event -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.

process EcDpAtCheckODL

/ecs/formal/PDPS/DPS/SSIT/src/Metadata

The Check ODL tool is a program that takes in a PGE name, version and Profile ID, and checks the ODL for that PGE for errors.

The Check ODL Tool takes in information about the PGE: name, version and Profile ID, and searches the directories specified in the configuration file for ODL location, for PGE, ESDT and Production Rule specific ODL files. If the files are found they are are parsed and any errors displayed on the screen.

To learn how to run the Check ODL tool, see the file DpAtMgr_checkodl.html in ClearCase under SSIT/src/Metadata, or on a machine where SSIT is installed under /usr/ecs/<MODE>/CUSTOM/WWW/DPS.

Classes

- DpAtDatabase -- This class's provides methods to update the PDPS database with PGE, ESDT and Production Rule operational and science metadata..
- DpAtOperationalMd -- This class's methods are callbacks for the PDPS/SSIT Database Update GUI, which updates the database with PGE operational metadata..
- DpAtScienceMd -- This class provides methods to read and validate all types of Science Metadata (ODL), PGE ODL, ESDT ODL and the various types of specific Production Rule ODL files.

Libraries Linked

- agentevent -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsFtFTPRelA -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObj -- This library provides functions to use FTP at a scheduled time by the User.
- DpAt -- This DpAt library holds the SSIT classes that are called by various SSIT tools and programs.
- DpDeletionClient -- The library containing the client side operations to issue requests to the deletion server.
- DpPrDbPf -- This library contains the PDPS database interface classes for use with the Process Framework access to the database.
- DpPrDM -- This library supplies utility operations to manage data within DPS.
- DpPrDssIF -- This library contains the helper object for PDPS to interact with science data server.
- DpPrEM -- This library supplies utility operations to manage PGE execution within PRONG.
- DpPrException -- This library provides APIs to catch and handle signals.
- DpPrRM -- This library supplies utility operations to manage computer resources for PDPS.
- DpPrTools -- This library contains global utility functions.
- DsCl -- This library contains classes which make up the Science Data Server's (SDSRV) public interface. These classes are used by clients to connect, build commands, and submit requests to the SDSRV.
- DsCn -- This library is used to access a server specific configuration file.
- DsSh -- This library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.

- EcCf -- The Config library (CF) is a static library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistry
- EcDcMsgPsnng1 -- This library consists of message passing objects used by both the client and server side.
- EcDnDir -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcDpJobMgmtClient -- The Job Management Client library provides the following public interfaces to the Job Management Server.
- EcFh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLoc -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcNsServiceLocator -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcPf -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPo -- The Persistent CSC provides a set of abstract and base classes for approved advertisements and requests.
- EcPoDbRW
- EcPtSpecialLock -- This library provides classes for mutex operations and thread IDs.
- EcSbCl -- This library contains all the classes for Subscription Server client.
- EcSbMsg -- This library contains all message classes used for the communication between Subscription Server and its client objects provided by Subscription Server client library.
- EcSeCmi -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeServerKeyMgmt -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbed -- This static Library is the stubbed version of EcSeSybSecurity.
- EcSeUtilityDbStubbed -- This static Library is stub version of the EcSeUtilityDb library.
- EcTiTime -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUr -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUt -- EcUt is a utility library for all the ECS applications.
- EcUtFactory -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtMisc -- This library contains miscellaneous utilities.

- event -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- GI -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.
- IoAdCore -- The CoreLib CSC provides a set of functionalities for describing a generic advertisement, parsing and validating attributes that support the ECS Core meta data model, and requesting and moderating advertisements.
- IoAdProxy -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSearch -- The SearchLib CSC provides a set of searching capabilities for approved advertisements, for the administration of groups, and for moderation of requests.
- IoAdServer -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSubs -- The SubsLib CSC provides a set of derived classes which represent different types of advertisements: products, services, and providers.
- MsAcCInt -- The Accountability Management Service makes the user profile available to the various subsystems, such as the Data Server subsystem, information such as the user's electronic mail address and the shipping address, which are used for the distribution of
- MsAcComm -- This library contains class used for both Accountability Server and Client
- PICore1 -- This library contains the first half of Planning's core functionality. The CoreLib provides functionality for all areas of Planning. It was divided in half due to its large size...
- PICore1IF -- This library contains the Science Data Server, advertisement, and subscription server interfaces that are needed to run the Production request editor.
- PICore2 -- This library contains the second half of Planning's core functionality. The CoreLib provides functionality for all areas of Planning. It was divided in half due to its large size...
- PISSIT -- This library manages the Science Software Integration & Test PDPS DB interfaces.
- PIUtil -- This library contains utilities dealing with current time, time periods, time boundaries, time windows, time intervals, spacecraft, orbit, instruments, and also manages their DB interfaces.
- srf -- The SRF library provides the necessary mechanism for the application to communicate asynchronously with another application.

process EcDpAtCheckPCF

/ecs/formal/PDPS/DPS/SSIT/src/PCF

The PCF Checker tool is a GUI that allows the user to select a PGE's Process Control File (PCF) and have it checked for syntax errors. Any errors found are displayed to the screen or can be written to a file.

The PCF Checker uses a Toolkit program to actually perform the check of the user-selected PCF. The SSIT portion of the PCF Checker is the GUI interface and the ability for the user to select files to be "checked" and to have the output sent to a window or a file.

To learn how to run the PCF Checker, see the file DpAtMgr_pcf.html in ClearCase under SSIT/src/PCF, or on a machine where SSIT is installed under /usr/ecs/<MODE>/CUSTOM/WWW/DPS.

Classes

- DpAtMgrCheckPcfInputFORM -- This class provides the definition for the input window of the SSIT PCF Checker GUI.
- DpAtMgrCheckPcfOutputFORM -- Created by Builder Xcessory Version 5.0.3.

Libraries Linked

- agentevent -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsFtFTPRelA -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObj -- This library provides functions to use FTP at a scheduled time by the User.
- DpAt -- This DpAt library holds the SSIT classes that are called by various SSIT tools and programs.
- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- EcCf -- The Config library (CF) is a static library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistry
- EcDcMsgPsgn1 -- This library consists of message passing objects used by both the client and server side.
- EcDnDir -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcFh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLoc -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcNsServiceLocator -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcPf -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPoDbRW
- EcPtSpecialLock -- This library provides classes for mutex operations and thread IDs.
- EcSeCmi -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).

- EcSeServerKeyMgmt -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbed -- This static Library is the stubbed version of EcSeSybSecurity.
- EcSeUtilityDbStubbed -- This static Library is stub version of the EcSeUtilityDb library.
- EcTiTime -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUr -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUt -- EcUt is a utility library for all the ECS applications.
- EcUtFactory -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- event -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.

process EcDpAtCreateODLTemplate

/ecs/formal/PDPS/DPS/SSIT/src/Metadata

The Create ODL Template tool is a program that takes as an argument a Process Control File (PCF) and generates a template version of the PGE ODL file.

The Create ODL Template Tool takes in information about the PGE: name, version and Profile ID, along with the location of the PCF and where the output PGE ODL template file is to be placed. It then takes the inputs, outputs and runtime parameter information from the PCF and puts it in ODL format, leaving blank such things as ESDT names and versions, and scheduling information, anything that cannot be determined from the PCF. The user must then edit the produced template file to create a valid PGE ODL file.

To learn how to run the Create ODL Template tool, see the file DpAtMgr_createodl.html in ClearCase under SSIT/src/Metadata, or on a machine where SSIT is installed under /usr/ecs/<MODE>/CUSTOM/WWW/DPS.

Classes

- DpAtDatabase -- This class's provides methods to update the PDPS database with PGE, ESDT and Production Rule operational and science metadata..
- DpAtOperationalMd -- This class's methods are callbacks for the PDPS/SSIT Database Update GUI, which updates the database with PGE operational metadata..
- DpAtScienceMd -- This class provides methods to read and validate all types of Science Metadata (ODL), PGE ODL, ESDT ODL and the various types of specific Production Rule ODL files.

Libraries Linked

- agentevent -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsFtFTPReLA -- This library provides a Wrapper for FTP.

- CsFtFTPSchedObj -- This library provides functions to use FTP at a scheduled time by the User.
- DpAt -- This DpAt library holds the SSIT classes that are called by various SSIT tools and programs.
- DpDeletionClient -- The library containing the client side operations to issue requests to the deletion server.
- DpPrDbPf -- This library contains the PDPS database interface classes for use with the Process Framework access to the database.
- DpPrDM -- This library supplies utility operations to manage data within DPS.
- DpPrDssIF -- This library contains the helper object for PDPS to interact with science data server.
- DpPrEM -- This library supplies utility operations to manage PGE execution within PRONG.
- DpPrException -- This library provides APIs to catch and handle signals.
- DpPrRM -- This library supplies utility operations to manage computer resources for PDPS.
- DpPrTools -- This library contains global utility functions.
- DsCl -- This library contains classes which make up the Science Data Server's (SDSRV) public interface. These classes are used by clients to connect, build commands, and submit requests to the SDSRV.
- DsCn -- This library is used to access a server specific configuration file.
- DsSh -- This library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- EcCf -- The Config library (CF) is a static library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistry
- EcDcMsgPsngr1 -- This library consists of message passing objects used by both the client and server side.
- EcDnDir -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcDpJobMgmtClient -- The Job Management Client library provides the following public interfaces to the Job Management Server.
- EcFh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLoc -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcNsServiceLocator -- The Service Locator library provides an implementation independent mechanism for specifying service locations.

- EcPf -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPo -- The Persistent CSC provides a set of abstract and base classes for approved advertisements and requests.
- EcPoDbRW
- EcPtSpecialLock -- This library provides classes for mutex operations and thread IDs.
- EcSbCl -- This library contains all the classes for Subscription Server client.
- EcSbMsg -- This library contains all message classes used for the communication between Subscription Server and its client objects provided by Subscription Server client library.
- EcSeCmi -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeServerKeyMgmt -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbed -- This static Library is the stubbed version of EcSeSybSecurity.
- EcSeUtilityDbStubbed -- This static Library is stub version of the EcSeUtilityDb library.
- EcTiTime -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUr -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUt -- EcUt is a utility library for all the ECS applications.
- EcUtFactory -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtMisc -- This library contains miscellaneous utilities.
- event -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- Gl -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.
- IoAdCore -- The CoreLib CSC provides a set of functionalities for describing a generic advertisement, parsing and validating attributes that support the ECS Core meta data model, and requesting and moderating advertisements.
- IoAdProxy -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSearch -- The SearchLib CSC provides a set of searching capabilities for approved advertisements, for the administration of groups, and for moderation of requests.
- IoAdServer -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSubs -- The SubsLib CSC provides a set of derived classes which represent different types of advertisements: products, services, and providers.

- MsAcClnt -- The Accountability Management Service makes the user profile available to the various subsystems, such as the Data Server subsystem, information such as the user's electronic mail address and the shipping address, which are used for the distribution of
- MsAcComm -- This library contains class used for both Accountability Server and Client
- PlCore1 -- This library contains the first half of Planning's core functionality. The CoreLib provides functionality for all areas of Planning. It was divided in half due to its large size...
- PlCore1IF -- This library contains the Science Data Server, advertisement, and subscription server interfaces that are needed to run the Production request editor.
- PlCore2 -- This library contains the second half of Planning's core functionality. The CoreLib provides functionality for all areas of Planning. It was divided in half due to its large size...
- PlSSIT -- This library manages the Science Software Integration & Test PDPS DB interfaces.
- PlUtil -- This library contains utilities dealing with current time, time periods, time boundaries, time windows, time intervals, spacecraft, orbit, instruments, and also manages their DB interfaces.
- srf -- The SRF library provides the necessary mechanism for the application to communicate asynchronously with another application.

process EcDpAtGetMCF

/ecs/formal/PDPS/DPS/SSIT/src/Dsrv

The Get MCF tool is a program that acquires a Metadata Control File (MCF) from the Data Server for a given ESDT and version.

The Get MCF Tool takes in information about the ESDT for which the MCF is for, its name and version, along with the directory where the MCF is to be placed. The tool then contacts the Data Server and requests the MCF for the specified ESDT. The MCF is placed in the directory specified by the caller.

To learn how to run the Insert Exe Tar File tool, see the file `DpAtMgr_getMCF.html` in ClearCase under `SSIT/src/Dsrv`, or on a machine where SSIT is installed under `/usr/ecs/<MODE>/CUSTOM/WWW/DPS`.

Libraries Linked

- agentevent -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsFtFTPRelA -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObj -- This library provides functions to use FTP at a scheduled time by the User.
- DpAt -- This DpAt library holds the SSIT classes that are called by various SSIT tools and programs.
- DpAtDsrv -- This library holds the object through which almost all SSIT calls to interface with the Data Server.

- DpAtMetadata -- This library holds the objects (DpAtDatabase and DpAtOperationalMd) through which most SSIT PDPS database updates are performed.
- DpDeletionClient -- The library containing the client side operations to issue requests to the deletion server.
- DpPrDbPf -- This library contains the PDPS database interface classes for use with the Process Framework access to the database.
- DpPrDM -- This library supplies utility operations to manage data within DPS.
- DpPrDssIF -- This library contains the helper object for PDPS to interact with science data server.
- DpPrEM -- This library supplies utility operations to manage PGE execution within PRONG.
- DpPrException -- This library provides APIs to catch and handle signals.
- DpPrRM -- This library supplies utility operations to manage computer resources for PDPS.
- DpPrTools -- This library contains global utility functions.
- DsCl -- This library contains classes which make up the Science Data Server's (SDSRV) public interface. These classes are used by clients to connect, build commands, and submit requests to the SDSRV.
- DsCn -- This library is used to access a server specific configuration file.
- DsSh -- This library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- EcCf -- The Config library (CF) is a static library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistry
- EcDcMsgPsnng1 -- This library consists of message passing objects used by both the client and server side.
- EcDnDir -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcDpJobMgmtClient -- The Job Management Client library provides the following public interfaces to the Job Management Server.
- EcFh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLoc -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcNsServiceLocator -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcPf -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.

- EcPo -- The Persistent CSC provides a set of abstract and base classes for approved advertisements and requests.
- EcPoDbRW
- EcPtSpecialLock -- This library provides classes for mutex operations and thread IDs.
- EcSbCl -- This library contains all the classes for Subscription Server client.
- EcSbMsg -- This library contains all message classes used for the communication between Subscription Server and its client objects provided by Subscription Server client library.
- EcSeCmi -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeServerKeyMgmt -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbed -- This static Library is the stubbed version of EcSeSybSecurity.
- EcSeUtilityDbStubbed -- This static Library is stub version of the EcSeUtilityDb library.
- EcTiTime -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUr -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUt -- EcUt is a utility library for all the ECS applications.
- EcUtFactory -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtMisc -- This library contains miscellaneous utilities.
- event -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- Gl -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.
- IoAdCore -- The CoreLib CSC provides a set of functionalities for describing a generic advertisement, parsing and validating attributes that support the ECS Core meta data model, and requesting and moderating advertisements.
- IoAdProxy -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSearch -- The SearchLib CSC provides a set of searching capabilities for approved advertisements, for the administration of groups, and for moderation of requests.
- IoAdServer -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSubs -- The SubsLib CSC provides a set of derived classes which represent different types of advertisements: products, services, and providers.
- MsAcClnt -- The Accountability Management Service makes the user profile available to the various subsystems, such as the Data Server subsystem, information such as the user's electronic mail address and the shipping address, which are used for the distribution of

- MsAcComm -- This library contains class used for both Accountability Server and Client
- PICore1IF -- This library contains the Science Data Server, advertisement, and subscription server interfaces that are needed to run the Production request editor.
- PICore2 -- This library contains the second half of Planning's core functionality. The CoreLib provides functionality for all areas of Planning. It was divided in half due to its large size...
- PISSIT -- This library manages the Science Software Integration & Test PDPS DB interfaces.
- PIUtil -- This library contains utilities dealing with current time, time periods, time boundaries, time windows, time intervals, spacecraft, orbit, instruments, and also manages their DB interfaces.
- srf -- The SRF library provides the necessary mechanism for the application to communicate asynchronously with another application.

process EcDpAtInsertExeTarFile

/ecs/formal/PDPS/DPS/SSIT/src/Dsrv

The Exe Tar File tool is a program that inserts PGE Tar files (the executable and any required Toolkit message files) into the Data Server.

The Insert Exe Tar File Tool takes in information about the tar file and the PGE it is for, the PGE name and Science Software version, the name of executable within the tar file, and the name and location of the tar file and its metadata. It then checks the information, verifying that the PGE name and Science Software version exist in the PDPS database, that the file and metadata exist on the local disk and that the PGE executable exists in the tar file. If all information is valid, the tool contacts the Data Server and inserts the file. If the insert succeeds, the entry for the PGE Executable in the PDPS database (already created by another SSIT tool) is updated with the UR returned by Data Server. The PGE can then be acquired later when it is scheduled to run.

To learn how to run the Insert Exe Tar File tool, see the file DpAtMgr_exetar.html in ClearCase under SSIT/src/Dsrv, or on a machine where SSIT is installed under /usr/ecs/<MODE>/CUSTOM/WWW/DPS.

Libraries Linked

- agentevent -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsFtFTPReLA -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObj -- This library provides functions to use FTP at a scheduled time by the User.
- DpAt -- This DpAt library holds the SSIT classes that are called by various SSIT tools and programs.
- DpAtDsrv -- This library holds the object through which almost all SSIT calls to interface with the Data Server.
- DpAtMetadata -- This library holds the objects (DpAtDatabase and DpAtOperationalMd) through which most SSIT PDPS database updates are performed.

- DpDeletionClient -- The library containing the client side operations to issue requests to the deletion server.
- DpPrDbPf -- This library contains the PDPS database interface classes for use with the Process Framework access to the database.
- DpPrDM -- This library supplies utility operations to manage data within DPS.
- DpPrDssIF -- This library contains the helper object for PDPS to interact with science data server.
- DpPrEM -- This library supplies utility operations to manage PGE execution within PRONG.
- DpPrException -- This library provides APIs to catch and handle signals.
- DpPrRM -- This library supplies utility operations to manage computer resources for PDPS.
- DpPrTools -- This library contains global utility functions.
- DsCl -- This library contains classes which make up the Science Data Server's (SDSRV) public interface. These classes are used by clients to connect, build commands, and submit requests to the SDSRV.
- DsCn -- This library is used to access a server specific configuration file.
- DsSh -- This library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- EcCf -- The Config library (CF) is a static library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistry
- EcDcMsgPng1 -- This library consists of message passing objects used by both the client and server side.
- EcDnDir -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcDpJobMgmtClient -- The Job Management Client library provides the following public interfaces to the Job Management Server.
- EcFh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLoc -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcNsServiceLocator -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcPf -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPo -- The Persistent CSC provides a set of abstract and base classes for approved advertisements and requests.

- EcPoDbRW
- EcPtSpecialLock -- This library provides classes for mutex operations and thread IDs.
- EcSbCl -- This library contains all the classes for Subscription Server client.
- EcSbMsg -- This library contains all message classes used for the communication between Subscription Server and its client objects provided by Subscription Server client library.
- EcSeCmi -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeServerKeyMgmt -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbed -- This static Library is the stubbed version of EcSeSybSecurity.
- EcSeUtilityDbStubbed -- This static Library is stub version of the EcSeUtilityDb library.
- EcTiTime -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUr -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUt -- EcUt is a utility library for all the ECS applications.
- EcUtFactory -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtMisc -- This library contains miscellaneous utilities.
- event -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- Gl -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.
- IoAdCore -- The CoreLib CSC provides a set of functionalities for describing a generic advertisement, parsing and validating attributes that support the ECS Core meta data model, and requesting and moderating advertisements.
- IoAdProxy -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSearch -- The SearchLib CSC provides a set of searching capabilities for approved advertisements, for the administration of groups, and for moderation of requests.
- IoAdServer -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSubs -- The SubsLib CSC provides a set of derived classes which represent different types of advertisements: products, services, and providers.
- MsAcClnt -- The Accountability Management Service makes the user profile available to the various subsystems, such as the Data Server subsystem, information such as the user's electronic mail address and the shipping address, which are used for the distribution of
- MsAcComm -- This library contains class used for both Accountability Server and Client

- PICore1IF -- This library contains the Science Data Server, advertisement, and subscription server interfaces that are needed to run the Production request editor.
- PICore2 -- This library contains the second half of Planning's core functionality. The CoreLib provides functionality for all areas of Planning. It was divided in half due to its large size...
- PISSIT -- This library manages the Science Software Integration & Test PDPS DB interfaces.
- PIUtil -- This library contains utilities dealing with current time, time periods, time boundaries, time windows, time intervals, spacecraft, orbit, instruments, and also manages their DB interfaces.
- srf -- The SRF library provides the necessary mechanism for the application to communicate asynchronously with another application.

process EcDpAtInsertStaticFile

/ecs/formal/PDPS/DPS/SSIT/src/Dsrv

The Insert Static File tool is a program that inserts Static Files (files that do not usually change from one run of the PGE to the next) into the Data Server.

The Insert Static File Tool takes in information about the file, its ESDT name and version, the science group its associated with (how static files are linked with PGEs), the name and location of the file and its metadata. It then checks the information, verifying that the ESDT name and version, along with the science group exist in the PDPS database, and that the file and metadata exist on the local disk. If all information is validated, it contacts the Data Server and inserts the file. If the insert succeeds, a granule entry for the file will be created in the PDPS database. The file can then be acquired later when a PGE that requires it as input is scheduled to run.

To learn how to run the Insert Static File tool, see the file `DpAtMgr_static.html` in ClearCase under `SSIT/src/Dsrv`, or on a machine where SSIT is installed under `/usr/ecs/<MODE>/CUSTOM/WWW/DPS`.

Libraries Linked

- agentevent -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsFtFTPRelA -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObj -- This library provides functions to use FTP at a scheduled time by the User.
- DpAt -- This DpAt library holds the SSIT classes that are called by various SSIT tools and programs.
- DpAtDsrv -- This library holds the object through which almost all SSIT calls to interface with the Data Server.
- DpAtMetadata -- This library holds the objects (DpAtDatabase and DpAtOperationalMd) through which most SSIT PDPS database updates are performed.
- DpDeletionClient -- The library containing the client side operations to issue requests to the deletion server.

- DpPrDbPf -- This library contains the PDPS database interface classes for use with the Process Framework access to the database.
- DpPrDM -- This library supplies utility operations to manage data within DPS.
- DpPrDssIF -- This library contains the helper object for PDPS to interact with science data server.
- DpPrEM -- This library supplies utility operations to manage PGE execution within PRONG.
- DpPrException -- This library provides APIs to catch and handle signals.
- DpPrRM -- This library supplies utility operations to manage computer resources for PDPS.
- DpPrTools -- This library contains global utility functions.
- DsCl -- This library contains classes which make up the Science Data Server's (SDSRV) public interface. These classes are used by clients to connect, build commands, and submit requests to the SDSRV.
- DsCn -- This library is used to access a server specific configuration file.
- DsSh -- This library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- EcCf -- The Config library (CF) is a static library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistry
- EcDcMsgPsgn1 -- This library consists of message passing objects used by both the client and server side.
- EcDnDir -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcDpJobMgmtClient -- The Job Management Client library provides the following public interfaces to the Job Management Server.
- EcFh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLoc -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcNsServiceLocator -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcPf -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPo -- The Persistent CSC provides a set of abstract and base classes for approved advertisements and requests.
- EcPoDbRW
- EcPtSpecialLock -- This library provides classes for mutex operations and thread IDs.

- EcSbCl -- This library contains all the classes for Subscription Server client.
- EcSbMsg -- This library contains all message classes used for the communication between Subscription Server and its client objects provided by Subscription Server client library.
- EcSeCmi -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeServerKeyMgmt -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbed -- This static Library is the stubbed version of EcSeSybSecurity.
- EcSeUtilityDbStubbed -- This static Library is stub version of the EcSeUtilityDb library.
- EcTiTime -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUr -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUt -- EcUt is a utility library for all the ECS applications.
- EcUtFactory -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtMisc -- This library contains miscellaneous utilities.
- event -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- Gl -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.
- IoAdCore -- The CoreLib CSC provides a set of functionalities for describing a generic advertisement, parsing and validating attributes that support the ECS Core meta data model, and requesting and moderating advertisements.
- IoAdProxy -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSearch -- The SearchLib CSC provides a set of searching capabilities for approved advertisements, for the administration of groups, and for moderation of requests.
- IoAdServer -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSubs -- The SubsLib CSC provides a set of derived classes which represent different types of advertisements: products, services, and providers.
- MsAcClnt -- The Accountability Management Service makes the user profile available to the various subsystems, such as the Data Server subsystem, information such as the user's electronic mail address and the shipping address, which are used for the distribution of
- MsAcComm -- This library contains class used for both Accountability Server and Client
- PlCore1IF -- This library contains the Science Data Server, advertisement, and subscription server interfaces that are needed to run the Production request editor.

- PICore2 -- This library contains the second half of Planning's core functionality. The CoreLib provides functionality for all areas of Planning. It was divided in half due to its large size...
- PISSIT -- This library manages the Science Software Integration & Test PDPS DB interfaces.
- PIUtil -- This library contains utilities dealing with current time, time periods, time boundaries, time windows, time intervals, spacecraft, orbit, instruments, and also manages their DB interfaces.
- srf -- The SRF library provides the necessary mechanism for the application to communicate asynchronously with another application.

process EcDpAtInsertTestFile

/ecs/formal/PDPS/DPS/SSIT/src/Dsrv

The Insert Test Dynamic File tool is a program that inserts Dynamic Files (files based on time or space that differ from one run of the PGE to the next) into the Data Server.

The Insert Test Dynamic File Tool takes in information about the file, its ESDT name and version and then inserts it into the Data Server. The file can then be acquired as an input to a PGE. This tool is mostly used for test purposes (hence the "Test" in the title). Files will be inserted by Ingest or by DPS in the operational system, so that the Insert Test Dynamic Tool will not have to be used.

To learn how to run the Insert Static File tool, see the file DpAtMgr_dynamic.html in ClearCase under SSIT/src/Dsrv, or on a machine where SSIT is installed under /usr/ecs/<MODE>/CUSTOM/WWW/DPS.

Libraries Linked

- agentevent -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsFtFTPReLA -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObj -- This library provides functions to use FTP at a scheduled time by the User.
- DpAt -- This DpAt library holds the SSIT classes that are called by various SSIT tools and programs.
- DpAtDsrv -- This library holds the object through which almost all SSIT calls to interface with the Data Server.
- DpAtMetadata -- This library holds the objects (DpAtDatabase and DpAtOperationalMd) through which most SSIT PDPS database updates are performed.
- DpDeletionClient -- The library containing the client side operations to issue requests to the deletion server.
- DpPrDbPf -- This library contains the PDPS database interface classes for use with the Process Framework access to the database.
- DpPrDM -- This library supplies utility operations to manage data within DPS.

- DpPrDssIF -- This library contains the helper object for PDPS to interact with science data server.
- DpPrEM -- This library supplies utility operations to manage PGE execution within PRONG.
- DpPrException -- This library provides APIs to catch and handle signals.
- DpPrRM -- This library supplies utility operations to manage computer resources for PDPS.
- DpPrTools -- This library contains global utility functions.
- DsCl -- This library contains classes which make up the Science Data Server's (SDSRV) public interface. These classes are used by clients to connect, build commands, and submit requests to the SDSRV.
- DsCn -- This library is used to access a server specific configuration file.
- DsSh -- This library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- EcCf -- The Config library (CF) is a static library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistry
- EcDcMsgPng1 -- This library consists of message passing objects used by both the client and server side.
- EcDnDir -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcDpJobMgmtClient -- The Job Management Client library provides the following public interfaces to the Job Management Server.
- EcFh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLoc -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcNsServiceLocator -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcPf -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPo -- The Persistent CSC provides a set of abstract and base classes for approved advertisements and requests.
- EcPoDbRW
- EcPtSpecialLock -- This library provides classes for mutex operations and thread IDs.
- EcSbCl -- This library contains all the classes for Subscription Server client.
- EcSeCmi -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).

- EcSeServerKeyMgmt -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbed -- This static Library is the stubbed version of EcSeSybSecurity.
- EcSeUtilityDbStubbed -- This static Library is stub version of the EcSeUtilityDb library.
- EcTiTime -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUr -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUt -- EcUt is a utility library for all the ECS applications.
- EcUtFactory -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtMisc -- This library contains miscellaneous utilities.
- event -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- Gl -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.
- IoAdCore -- The CoreLib CSC provides a set of functionalities for describing a generic advertisement, parsing and validating attributes that support the ECS Core meta data model, and requesting and moderating advertisements.
- IoAdProxy -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSearch -- The SearchLib CSC provides a set of searching capabilities for approved advertisements, for the administration of groups, and for moderation of requests.
- IoAdServer -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSubs -- The SubsLib CSC provides a set of derived classes which represent different types of advertisements: products, services, and providers.
- MsAcClnt -- The Accountability Management Service makes the user profile available to the various subsystems, such as the Data Server subsystem, information such as the user's electronic mail address and the shipping address, which are used for the distribution of
- MsAcComm -- This library contains class used for both Accountability Server and Client
- PICore1IF -- This library contains the Science Data Server, advertisement, and subscription server interfaces that are needed to run the Production request editor.
- PICore2 -- This library contains the second half of Planning's core functionality. The CoreLib provides functionality for all areas of Planning. It was divided in half due to its large size...
- PISSIT -- This library manages the Science Software Integration & Test PDPS DB interfaces.
- PIUtil -- This library contains utilities dealing with current time, time periods, time boundaries, time windows, time intervals, spacecraft, orbit, instruments, and also manages their DB interfaces.

- srf -- The SRF library provides the necessary mechanism for the application to communicate asynchronously with another application.

process EcDpAtMgr

/ecs/formal/PDPS/DPS/SSIT/src/MGR

The SSIT Manager GUI is the primary interface to all SSIT tools. It is a graphic interface with an SSIT Checklist and menu choices for other SSIT programs.

There is no web page for the SSIT Manager itself, but under the Help menu there are pages for most other SSIT functions, including one on how to use the checklist.

Classes

- DpAtMgrLog -- This class manages SSIT Manager log information.
- DpAtMgrLogGuiMainWindow

Libraries Linked

- agentevent -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsFtFTPRelA -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObj -- This library provides functions to use FTP at a scheduled time by the User.
- DpAt -- This DpAt library holds the SSIT classes that are called by various SSIT tools and programs.
- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- EcCf -- The Config library (CF) is a static library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistry
- EcDcMsgPsngr1 -- This library consists of message passing objects used by both the client and server side.
- EcDnDir -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcFh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLoc -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcNsServiceLocator -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcPf -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.

- EcPoDbRW
- EcPtSpecialLock -- This library provides classes for mutex operations and thread IDs.
- EcSeCmi -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeServerKeyMgmt -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbed -- This static Library is the stubbed version of EcSeSybSecurity.
- EcSeUtilityDbStubbed -- This static Library is stub version of the EcSeUtilityDb library.
- EcTiTime -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUr -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUt -- EcUt is a utility library for all the ECS applications.
- EcUtFactory -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- event -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.

process EcDpAtMgrLogDump

/ecs/formal/PDPS/DPS/SSIT/src/MGR

The SSIT Manager Log Dump tool allows a user to dump the SSIT Manager GUI checklist entries to a file for documentation purposes. The checklist entries are listed in the upper window of the SSIT Manager GUI and any comments about those entries are displayed in the lower window of the same GUI.

The checklist is stored using the UNIX ndbm flat-file database utility, so the files that make up the checklist are not man-readable. The SSIT Manager Log Dump tool allows the user to dump the checklist information to an ASCII file that can be read, printed or stored to show the steps of SSIT that had been completed.

To learn how to run the SSIT Manager Log Dump Tool, see the file DpAtMgr_log.html in ClearCase under SSIT/src/MGR, or on a machine where SSIT is installed under /usr/ecs/<MODE>/CUSTOM/WWW/DPS.

Classes

- DpAtMgrLog -- This class manages SSIT Manager log information.

Libraries Linked

- agentevent -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsFtFTPReIA -- This library provides a Wrapper for FTP.

- CsFtFTPSchedObj -- This library provides functions to use FTP at a scheduled time by the User.
- DpAt -- This DpAt library holds the SSIT classes that are called by various SSIT tools and programs.
- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- EcCf -- The Config library (CF) is a static library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistry
- EcDcMsgPsng1 -- This library consists of message passing objects used by both the client and server side.
- EcDnDir -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcFh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLoc -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcNsServiceLocator -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcPf -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPoDbRW
- EcPtSpecialLock -- This library provides classes for mutex operations and thread IDs.
- EcSeCmi -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeServerKeyMgmt -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbed -- This static Library is the stubbed version of EcSeSybSecurity.
- EcSeUtilityDbStubbed -- This static Library is stub version of the EcSeUtilityDb library.
- EcTiTime -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUr -- A Universal Reference (UR) is created as a logical reference to an extant ECS object.
- EcUt -- EcUt is a utility library for all the ECS applications.
- EcUtFactory -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- event -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.

process EcDpAtOpDbGui

/ecs/formal/PDPS/DPS/SSIT/src/MdGui

The SSIT Operational Metadata GUI is a graphic interface that allows the user to enter and update information about the PGE, including performance and memory requirements and Toolkit initialization strings. It also provides a mechanism to delete a PGE and to view the ODL for a PGE and any ESDTs that it uses.

To learn how to run the SSIT Operational Metadata GUI, see the file `DpAtMgr_opnlupdate.html` in ClearCase under `SSIT/src/MdGui`, or on a machine where SSIT is installed under `/usr/ecs/<MODE>/CUSTOM/WWW/DPS`.

Classes

- `DpAtOpDbMW` -- This class defines the SSIT Operational Metadata GUI.
- `DpAtOpDbTextDisMW` -- Created by Builder Xcessory Version 5.0.3.
- `UIComponent` -- Base class for all C++/Motif UI components.

Libraries Linked

- `agentevent` -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- `CsEmMailRelA` -- This Library is used for the emails using sendmail utility and the nnpst for Bulletin board messages.
- `CsFtFTPRelA` -- This library provides a Wrapper for FTP.
- `CsFtFTPSchedObj` -- This library provides functions to use FTP at a scheduled time by the User.
- `DpAt` -- This `DpAt` library holds the SSIT classes that are called by various SSIT tools and programs.
- `DpAtMetadata` -- This library holds the objects (`DpAtDatabase` and `DpAtOperationalMd`) through which most SSIT PDPS database updates are performed.
- `DpDeletionClient` -- The library containing the client side operations to issue requests to the deletion server.
- `DpPrDbPf` -- This library contains the PDPS database interface classes for use with the Process Framework access to the database.
- `DpPrDM` -- This library supplies utility operations to manage data within DPS.
- `DpPrDssIF` -- This library contains the helper object for PDPS to interact with science data server.
- `DpPrEM` -- This library supplies utility operations to manage PGE execution within PRONG.
- `DpPrException` -- This library provides APIs to catch and handle signals.
- `DpPrJM` -- The Job Management library provides service routines for the Job Management Server to use to manage the flow of jobs in all AutoSys instances for a mode.

- DpPrRM -- This library supplies utility operations to manage computer resources for PDPS.
- DpPrTools -- This library contains global utility functions.
- DpPrUpdateStatus
- DsCl -- This library contains classes which make up the Science Data Server's (SDSRV) public interface. These classes are used by clients to connect, build commands, and submit requests to the SDSRV.
- DsCn -- This library is used to access a server specific configuration file.
- DsSh -- This library provides underlying DCE(ODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- EcCf -- The Config library (CF) is a static library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistry
- EcDcMsgPsgn1 -- This library consists of message passing objects used by both the client and server side.
- EcDnDir -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcDpJobMgmtClient -- The Job Management Client library provides the following public interfaces to the Job Management Server.
- EcFh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLoc -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcNsServiceLocator -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcPf -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPo -- The Persistent CSC provides a set of abstract and base classes for approved advertisements and requests.
- EcPoDbRW
- EcPtSpecialLock -- This library provides classes for mutex operations and thread IDs.
- EcSbCl -- This library contains all the classes for Subscription Server client.
- EcSbMsg -- This library contains all message classes used for the communication between Subscription Server and its client objects provided by Subscription Server client library.
- EcSeCmi -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).

- EcSeServerKeyMgmt -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbed -- This static Library is the stubbed version of EcSeSybSecurity.
- EcSeUtilityDbStubbed -- This static Library is stub version of the EcSeUtilityDb library.
- EcTiTime -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUr -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUt -- EcUt is a utility library for all the ECS applications.
- EcUtFactory -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtHelpg_mt_eh_tp
- EcUtMisc -- This library contains miscellaneous utilities.
- event -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- Gl -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.
- IoAdCore -- The CoreLib CSC provides a set of functionalities for describing a generic advertisement, parsing and validating attributes that support the ECS Core meta data model, and requesting and moderating advertisements.
- IoAdProxy -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSearch -- The SearchLib CSC provides a set of searching capabilities for approved advertisements, for the administration of groups, and for moderation of requests.
- IoAdServer -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSubs -- The SubsLib CSC provides a set of derived classes which represent different types of advertisements: products, services, and providers.
- MsAcClnt -- The Accountability Management Service makes the user profile available to the various subsystems, such as the Data Server subsystem, information such as the user's electronic mail address and the shipping address, which are used for the distribution of
- MsAcComm -- This library contains class used for both Accountability Server and Client
- PICore1IF -- This library contains the Science Data Server, advertisement, and subscription server interfaces that are needed to run the Production request editor.
- PICore2 -- This library contains the second half of Planning's core functionality. The CoreLib provides functionality for all areas of Planning. It was divided in half due to its large size...
- PIGUIError -- This library contains the objects needed for SSIT and QA Monitor GUIs to display error messages.
- PISIT -- This library manages the Science Software Integration & Test PDPS DB interfaces.

- PIUtil -- This library contains utilities dealing with current time, time periods, time boundaries, time windows, time intervals, spacecraft, orbit, instruments, and also manages their DB interfaces.
- srf -- The SRF library provides the necessary mechanism for the application to communicate asynchronously with another application.

process EcDpAtOrbitCalculator

/ecs/formal/PDPS/DPS/SSIT/src/Metadata

The Orbit Calculator tool is a non-delivered program that takes in information about the orbit of a satellite and calculates times, orbit numbers and path numbers for a sequence of orbits.

Libraries Linked

- agentevent -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsFtFTPRelA -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObj -- This library provides functions to use FTP at a scheduled time by the User.
- DpAt -- This DpAt library holds the SSIT classes that are called by various SSIT tools and programs.
- DpDeletionClient -- The library containing the client side operations to issue requests to the deletion server.
- DpPrDbPf -- This library contains the PDPS database interface classes for use with the Process Framework access to the database.
- DpPrDM -- This library supplies utility operations to manage data within DPS.
- DpPrDssIF -- This library contains the helper object for PDPS to interact with science data server.
- DpPrEM -- This library supplies utility operations to manage PGE execution within PRONG.
- DpPrException -- This library provides APIs to catch and handle signals.
- DpPrRM -- This library supplies utility operations to manage computer resources for PDPS.
- DpPrTools -- This library contains global utility functions.
- DsCl -- This library contains classes which make up the Science Data Server's (SDSRV) public interface. These classes are used by clients to connect, build commands, and submit requests to the SDSRV.
- DsCn -- This library is used to access a server specific configuration file.
- DsSh -- This library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.

- EcCf -- The Config library (CF) is a static library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistry
- EcDcMsgPsnng1 -- This library consists of message passing objects used by both the client and server side.
- EcDnDir -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcDpJobMgmtClient -- The Job Management Client library provides the following public interfaces to the Job Management Server.
- EcFh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLoc -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcNsServiceLocator -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcPf -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPo -- The Persistent CSC provides a set of abstract and base classes for approved advertisements and requests.
- EcPoDbRW
- EcPtSpecialLock -- This library provides classes for mutex operations and thread IDs.
- EcSbCl -- This library contains all the classes for Subscription Server client.
- EcSbMsg -- This library contains all message classes used for the communication between Subscription Server and its client objects provided by Subscription Server client library.
- EcSeCmi -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeServerKeyMgmt -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbed -- This static Library is the stubbed version of EcSeSybSecurity.
- EcSeUtilityDbStubbed -- This static Library is stub version of the EcSeUtilityDb library.
- EcTiTime -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUr -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUt -- EcUt is a utility library for all the ECS applications.
- EcUtFactory -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtMisc -- This library contains miscellaneous utilities.

- event -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- GI -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.
- IoAdCore -- The CoreLib CSC provides a set of functionalities for describing a generic advertisement, parsing and validating attributes that support the ECS Core meta data model, and requesting and moderating advertisements.
- IoAdProxy -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSearch -- The SearchLib CSC provides a set of searching capabilities for approved advertisements, for the administration of groups, and for moderation of requests.
- IoAdServer -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSubs -- The SubsLib CSC provides a set of derived classes which represent different types of advertisements: products, services, and providers.
- MsAcClnt -- The Accountability Management Service makes the user profile available to the various subsystems, such as the Data Server subsystem, information such as the user's electronic mail address and the shipping address, which are used for the distribution of
- MsAcComm -- This library contains class used for both Accountability Server and Client
- PICore1 -- This library contains the first half of Planning's core functionality. The CoreLib provides functionality for all areas of Planning. It was divided in half due to its large size...
- PICore1IF -- This library contains the Science Data Server, advertisement, and subscription server interfaces that are needed to run the Production request editor.
- PICore2 -- This library contains the second half of Planning's core functionality. The CoreLib provides functionality for all areas of Planning. It was divided in half due to its large size...
- PISSIT -- This library manages the Science Software Integration & Test PDPS DB interfaces.
- PIUtil -- This library contains utilities dealing with current time, time periods, time boundaries, time windows, time intervals, spacecraft, orbit, instruments, and also manages their DB interfaces.
- srf -- The SRF library provides the necessary mechanism for the application to communicate asynchronously with another application.

process EcDpAtPrologs

/ecs/formal/PDPS/DPS/SSIT/src/PRO

The Prolog Extractor takes a source code file as input and extracts from it the comment prolog and places this prolog in a separate file.

The Prolog Extractor expects the prolog to be in a very specific format. See the html page mentioned below for where that format is specified.

To learn how to run the Prolog Extractor, see the file `DpAtMgr_prolog.html` in ClearCase under `SSIT/src/PRO`, or on a machine where SSIT is installed under `/usr/ecs/<MODE>/CUSTOM/WWW/DPS`.

Classes

- `DpAtMgrDirectory` -- This class manages directory information.
- `DpAtMgrSource` -- This class holds parsed source code information.

Libraries Linked

- `agentevent` -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- `CsFtFTPRelA` -- This library provides a Wrapper for FTP.
- `CsFtFTPSchedObj` -- This library provides functions to use FTP at a scheduled time by the User.
- `DpAt` -- This `DpAt` library holds the SSIT classes that are called by various SSIT tools and programs.
- `EcAgInstrm` -- This library contains the instrumentation code which is linked into all ECS managed servers.
- `EcCf` -- The Config library (CF) is a static library provides the necessary software for the `PF_Client` & the `PF_Server` applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- `EcCsRegistry`
- `EcDcMsgPsnng1` -- This library consists of message passing objects used by both the client and server side.
- `EcDnDir` -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- `EcFh` -- This library provides fault handling capabilities to ECS applications.
- `EcNsServiceLoc` -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- `EcNsServiceLocator` -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- `EcPf` -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- `EcPoDbRW`
- `EcPtSpecialLock` -- This library provides classes for mutex operations and thread IDs.
- `EcSeCmi` -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).

- EcSeServerKeyMgmt -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbed -- This static Library is the stubbed version of EcSeSybSecurity.
- EcSeUtilityDbStubbed -- This static Library is stub version of the EcSeUtilityDb library.
- EcTiTime -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUr -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUt -- EcUt is a utility library for all the ECS applications.
- EcUtFactory -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- event -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.

process EcDpAtRegisterPGE

/ecs/formal/PDPS/DPS/SSIT/src/Metadata

The Register PGE tool is a program that takes in a PGE name, version and Profile ID, and parses the ODL for that PGE. If no errors are found it stores the information in the PDPS database.

The Register PGE Tool takes in information about the PGE: name, version and Profile ID, and searches the directories specified in the configuration file for ODL location, for PGE, ESDT and Production Rule specific ODL files. If the files are found they are are parsed and any errors displayed on the screen. If no errors are found, the information is stored in the PDPS database.

To learn how to run the Register PGE tool, see the file DpAtMgr_sciupdate.html in ClearCase under SSIT/src/Metadata, or on a machine where SSIT is installed under /usr/ecs/<MODE>/CUSTOM/WWW/DPS.

Classes

- DpAtDatabase -- This class's provides methods to update the PDPS database with PGE, ESDT and Production Rule operational and science metadata..
- DpAtOperationalMd -- This class's methods are callbacks for the PDPS/SSIT Database Update GUI, which updates the database with PGE operational metadata..
- DpAtScienceMd -- This class provides methods to read and validate all types of Science Metadata (ODL), PGE ODL, ESDT ODL and the various types of specific Production Rule ODL files.

Libraries Linked

- agentevent -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsFtFTPReIA -- This library provides a Wrapper for FTP.

- CsFtFTPSchedObj -- This library provides functions to use FTP at a scheduled time by the User.
- DpAt -- This DpAt library holds the SSIT classes that are called by various SSIT tools and programs.
- DpDeletionClient -- The library containing the client side operations to issue requests to the deletion server.
- DpPrDbPf -- This library contains the PDPS database interface classes for use with the Process Framework access to the database.
- DpPrDM -- This library supplies utility operations to manage data within DPS.
- DpPrDssIF -- This library contains the helper object for PDPS to interact with science data server.
- DpPrEM -- This library supplies utility operations to manage PGE execution within PRONG.
- DpPrException -- This library provides APIs to catch and handle signals.
- DpPrRM -- This library supplies utility operations to manage computer resources for PDPS.
- DpPrTools -- This library contains global utility functions.
- DsCl -- This library contains classes which make up the Science Data Server's (SDSRV) public interface. These classes are used by clients to connect, build commands, and submit requests to the SDSRV.
- DsCn -- This library is used to access a server specific configuration file.
- DsSh -- This library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- EcCf -- The Config library (CF) is a static library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistry
- EcDcMsgPsngr1 -- This library consists of message passing objects used by both the client and server side.
- EcDnDir -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcDpJobMgmtClient -- The Job Management Client library provides the following public interfaces to the Job Management Server.
- EcFh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLoc -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcNsServiceLocator -- The Service Locator library provides an implementation independent mechanism for specifying service locations.

- EcPf -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPo -- The Persistent CSC provides a set of abstract and base classes for approved advertisements and requests.
- EcPoDbRW
- EcPtSpecialLock -- This library provides classes for mutex operations and thread IDs.
- EcSbCl -- This library contains all the classes for Subscription Server client.
- EcSbMsg -- This library contains all message classes used for the communication between Subscription Server and its client objects provided by Subscription Server client library.
- EcSeCmi -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeServerKeyMgmt -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbed -- This static Library is the stubbed version of EcSeSybSecurity.
- EcSeUtilityDbStubbed -- This static Library is stub version of the EcSeUtilityDb library.
- EcTiTime -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUr -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUt -- EcUt is a utility library for all the ECS applications.
- EcUtFactory -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtMisc -- This library contains miscellaneous utilities.
- event -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- Gl -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.
- IoAdCore -- The CoreLib CSC provides a set of functionalities for describing a generic advertisement, parsing and validating attributes that support the ECS Core meta data model, and requesting and moderating advertisements.
- IoAdProxy -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSearch -- The SearchLib CSC provides a set of searching capabilities for approved advertisements, for the administration of groups, and for moderation of requests.
- IoAdServer -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSubs -- The SubsLib CSC provides a set of derived classes which represent different types of advertisements: products, services, and providers.

- MsAcClnt -- The Accountability Management Service makes the user profile available to the various subsystems, such as the Data Server subsystem, information such as the user's electronic mail address and the shipping address, which are used for the distribution of
- MsAcComm -- This library contains class used for both Accountability Server and Client
- PICore1 -- This library contains the first half of Planning's core functionality. The CoreLib provides functionality for all areas of Planning. It was divided in half due to its large size...
- PICore1IF -- This library contains the Science Data Server, advertisement, and subscription server interfaces that are needed to run the Production request editor.
- PICore2 -- This library contains the second half of Planning's core functionality. The CoreLib provides functionality for all areas of Planning. It was divided in half due to its large size...
- PISSIT -- This library manages the Science Software Integration & Test PDPS DB interfaces.
- PIUtil -- This library contains utilities dealing with current time, time periods, time boundaries, time windows, time intervals, spacecraft, orbit, instruments, and also manages their DB interfaces.
- srf -- The SRF library provides the necessary mechanism for the application to communicate asynchronously with another application.

process EcDpAtStageDAP

/ecs/formal/PDPS/DPS/SSIT/src/Dsrv

The Stage DAP tool is a program that acquires a granule (usually a DAP, but the tool will acquire anything) given the location of a flat file with a UR for that granule and a location where the granule is to be staged.

The Stage DAP tool takes in a file and parses it for the Universal Reference (UR) of a granule. It then contacts the Data Server and gets the granule (along with its metadata) copied to the command-line specified directory. The tool will check to make sure that the directory exists and is writeable.

To learn how to run the Stage DAP, see the file DpAtMgr_dap.html in ClearCase under SSIT/src/Dsrv, or on a machine where SSIT is installed under /usr/ecs/<MODE>/CUSTOM/WWW/DPS.

Classes

- DpAtDsrv -- This class's methods are the interface between the SSIT environment and the Data Server..

Libraries Linked

- agentevent -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsFtFTPReIA -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObj -- This library provides functions to use FTP at a scheduled time by the User.

- DpAt -- This DpAt library holds the SSIT classes that are called by various SSIT tools and programs.
- DpAtDsrv -- This library holds the object through which almost all SSIT calls to interface with the Data Server.
- DpAtMetadata -- This library holds the objects (DpAtDatabase and DpAtOperationalMd) through which most SSIT PDPS database updates are performed.
- DpDeletionClient -- The library containing the client side operations to issue requests to the deletion server.
- DpPrDbPf -- This library contains the PDPS database interface classes for use with the Process Framework access to the database.
- DpPrDM -- This library supplies utility operations to manage data within DPS.
- DpPrDssIF -- This library contains the helper object for PDPS to interact with science data server.
- DpPrEM -- This library supplies utility operations to manage PGE execution within PRONG.
- DpPrException -- This library provides APIs to catch and handle signals.
- DpPrRM -- This library supplies utility operations to manage computer resources for PDPS.
- DpPrTools -- This library contains global utility functions.
- DsCl -- This library contains classes which make up the Science Data Server's (SDSRV) public interface. These classes are used by clients to connect, build commands, and submit requests to the SDSRV.
- DsCn -- This library is used to access a server specific configuration file.
- DsSh -- This library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- EcCf -- The Config library (CF) is a static library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistry
- EcDcMsgPsgn1 -- This library consists of message passing objects used by both the client and server side.
- EcDnDir -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcDpJobMgmtClient -- The Job Management Client library provides the following public interfaces to the Job Management Server.
- EcFh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLoc -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.

- EcNsServiceLocator -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcPf -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPo -- The Persistent CSC provides a set of abstract and base classes for approved advertisements and requests.
- EcPoDbRW
- EcPtSpecialLock -- This library provides classes for mutex operations and thread IDs.
- EcSbCl -- This library contains all the classes for Subscription Server client.
- EcSbMsg -- This library contains all message classes used for the communication between Subscription Server and its client objects provided by Subscription Server client library.
- EcSeCmi -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeServerKeyMgmt -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbed -- This static Library is the stubbed version of EcSeSybSecurity.
- EcSeUtilityDbStubbed -- This static Library is stub version of the EcSeUtilityDb library.
- EcTiTime -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUr -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUt -- EcUt is a utility library for all the ECS applications.
- EcUtFactory -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtMisc -- This library contains miscellaneous utilities.
- event -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- Gl -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.
- IoAdCore -- The CoreLib CSC provides a set of functionalities for describing a generic advertisement, parsing and validating attributes that support the ECS Core meta data model, and requesting and moderating advertisements.
- IoAdProxy -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSearch -- The SearchLib CSC provides a set of searching capabilities for approved advertisements, for the administration of groups, and for moderation of requests.
- IoAdServer -- The ServerLib CSC provides classes for process framework DCE server and client.

- IoAdSubs -- The SubsLib CSC provides a set of derived classes which represent different types of advertisements: products, services, and providers.
- MsAcClnt -- The Accountability Management Service makes the user profile available to the various subsystems, such as the Data Server subsystem, information such as the user's electronic mail address and the shipping address, which are used for the distribution of
- MsAcComm -- This library contains class used for both Accountability Server and Client
- PICore1IF -- This library contains the Science Data Server, advertisement, and subscription server interfaces that are needed to run the Production request editor.
- PICore2 -- This library contains the second half of Planning's core functionality. The CoreLib provides functionality for all areas of Planning. It was divided in half due to its large size...
- PISSIT -- This library manages the Science Software Integration & Test PDPS DB interfaces.
- PIUtil -- This library contains utilities dealing with current time, time periods, time boundaries, time windows, time intervals, spacecraft, orbit, instruments, and also manages their DB interfaces.
- srf -- The SRF library provides the necessary mechanism for the application to communicate asynchronously with another application.

process EcDpPrAm1AncillaryDPREP

/ecs/formal/PDPS/DPS/PRONG/src/PreProcess

The primary executable in Step 1 DPREP, which takes in L0 data and creates Ephemeris output.

Classes

- DpPrAm1AncillaryPacket -- Data type representing an EOS-AM1 telemetry packet having an APID = 4 This type of packet contains ephemeris and attitude data for the AM1 spacecraft.
- DpPrAm1AncPacketProcessor -- This class coordinates quality checking and the generation of HDF and native data sets for ephemeris and attitude data from the AM1 ancillary packets.
- DpPrAm1AncQaParameters -- QA Parameters used for EOS-AM1 ephemeris and attitude preprocessing.
- DpPrAm1DataQualityFlags -- DpPrAm1DataQualityFlags handles the data quality flags for ephemeris and attitude preprocessing for the EOS-AM1 spacecraft.
- DpPrAttitudeDataSet -- This class creates the HDF and native data sets and associated metadata created from the AM1 ancillary packet attitude data.
- DpPrCcsdsPacket -- This is an abstract class for telemetry packets that conform to the Consultive Committee for Space Data Systems standard for the Version 1 Telemetry Source Packet format.
- DpPrDataQualityFlags -- The class DpPrDataQualityFlags encapsulates the data quality flags used in ephemeris and attitude preprocessing.
- DpPrEphemerisDataSet -- This class creates the HDF and native data sets and associated metadata created from the AM1 ancillary packet ephemeris data.

- DpPrEphemerisRecord -- This class represents the time-ordered set of reformatted ephemeris records parsed from the FDF Ephemeris Dataset EPHEM format record.
- DpPrPcfParameters -- Retrieves Runtime parameters from the current PCF.

Templates

- DpPrPacketVector -- DpPrPacketVector interface .

process EcDpPrAm1EphemerisGapFillDPREP

/ecs/formal/PDPS/DPS/PRONG/src/PreProcess

The executable is part of Step 1 DPREP, and fills in any small gaps in the Ephemeris data created by EcDpPrAm1AncillaryDPREP.

Classes

- DpPrAttitudeDataSet -- This class creates the HDF and native data sets and associated metadata created from the AM1 ancillary packet attitude data.
- DpPrCcsdsPacket -- This is an abstract class for telemetry packets that conform to the Consultive Committee for Space Data Systems standard for the Version 1 Telemetry Source Packet format.
- DpPrDataGaps -- This class represents the time-ordered set of reformatted ephemeris records, parsed from the TRMM L0 Ancillary Dataset ephemeris packet, undergoing gap filling.
- DpPrDataQualityFlags -- The class DpPrDataQualityFlags encapsulates the data quality flags used in ephemeris and attitude preprocessing.
- DpPrEphemerisDataSet -- This class creates the HDF and native data sets and associated metadata created from the AM1 ancillary packet ephemeris data.
- DpPrEphemerisRecord -- This class represents the time-ordered set of reformatted ephemeris records parsed from the FDF Ephemeris Dataset EPHEM format record.
- DpPrGapProcessingSet -- This class represents the set of ephemeris datasets involved in data gap filling.
- DpPrPcfParameters -- Retrieves Runtime parameters from the current PCF.

Templates

- DpPrPacketVector -- DpPrPacketVector interface .

process EcDpPrAm1FddAttitudeDPREP

/ecs/formal/PDPS/DPS/PRONG/src/PreProcess

The executable for Step 2 DPREP, which takes in FDD data and create attitude data sets.

Classes

- DpPrAm1DataQualityFlags -- DpPrAm1DataQualityFlags handles the data quality flags for ephemeris and attitude preprocessing for the EOS-AM1 spacecraft.
- DpPrAm1FddAttitudeRecord -- Data type representing an FDD definitive attitude record.
- DpPrAm1FddQaParameters -- Parameters used for EOS-AM1 attitude preprocessing.
- DpPrAm1FddRecordProcessor -- This class coordinates quality checking and the generation of HDF and native data sets for ephemeris and attitude data from the AM1 ancillary records.
- DpPrAttitudeDataSet -- This class creates the HDF and native data sets and associated metadata created from the AM1 ancillary packet attitude data.
- DpPrCcsdsPacket -- This is an abstract class for telemetry packets that conform to the Consultive Committee for Space Data Systems standard for the Version 1 Telemetry Source Packet format.
- DpPrDataQualityFlags -- The class DpPrDataQualityFlags encapsulates the data quality flags used in ephemeris and attitude preprocessing.
- DpPrEphemerisDataSet -- This class creates the HDF and native data sets and associated metadata created from the AM1 ancillary packet ephemeris data.
- DpPrEphemerisRecord -- This class represents the time-ordered set of reformatted ephemeris records parsed from the FDF Ephemeris Dataset EPHEM format record.
- DpPrFddAttRecordVector -- This class handles a vector of DpPrCcsdsRecords.
- DpPrPcfParameters -- Retrieves Runtime parameters from the current PCF.

Templates

- DpPrPacketVector -- DpPrPacketVector interface .

process EcDpPrAm1FddReplaceEphemerisDPREP

/ecs/formal/PDPS/DPS/PRONG/src/PreProcess

The executable for Step 3 DPREP, which takes in FDD data and repairs any Ephemeris data for same time period.

Classes

- DpPrAttitudeDataSet -- This class creates the HDF and native data sets and associated metadata created from the AM1 ancillary packet attitude data.
- DpPrCcsdsPacket -- This is an abstract class for telemetry packets that conform to the Consultive Committee for Space Data Systems standard for the Version 1 Telemetry Source Packet format.
- DpPrDataQualityFlags -- The class DpPrDataQualityFlags encapsulates the data quality flags used in ephemeris and attitude preprocessing.
- DpPrEphemerisDataSet -- This class creates the HDF and native data sets and associated metadata created from the AM1 ancillary packet ephemeris data.

- DpPrEphemerisMetadata -- This class represents the ephemeris metadata that are associated with the native and HDF format ephemeris datasets.
- DpPrEphemerisRecord -- This class represents the time-ordered set of reformatted ephemeris records parsed from the FDF Ephemeris Dataset EPHEM format record.
- DpPrEphemRecord -- This class represents the time-ordered set of FDF Ephemeris Dataset EPHEM format records.
- DpPrFdfProcessingSet -- This class represents the FDF Ephemeris Dataset from which the ephemeris dataset is derived and the set of derived ephemeris datasets.
- DpPrPcfParameters -- Retrieves Runtime parameters from the current PCF.

Templates

- DpPrPacketVector -- DpPrPacketVector interface .

process EcDpPrAm1ToolkitToHdfDPREP

/ecs/formal/PDPS/DPS/PRONG/src/PreProcess

An executable for Step 1 DPREP, which converts the output of the other Step 1 programs from Toolkit native format to HDF.

Classes

- DpPrAttitudeDataSet -- This class creates the HDF and native data sets and associated metadata created from the AM1 ancillary packet attitude data.
- DpPrCcsdsPacket -- This is an abstract class for telemetry packets that conform to the Consultive Committee for Space Data Systems standard for the Version 1 Telemetry Source Packet format.
- DpPrDataQualityFlags -- The class DpPrDataQualityFlags encapsulates the data quality flags used in ephemeris and attitude preprocessing.
- DpPrEphemerisDataSet -- This class creates the HDF and native data sets and associated metadata created from the AM1 ancillary packet ephemeris data.
- DpPrEphemerisRecord -- This class represents the time-ordered set of reformatted ephemeris records parsed from the FDF Ephemeris Dataset EPHEM format record.
- DpPrPcfParameters -- Retrieves Runtime parameters from the current PCF.

Templates

- DpPrPacketVector -- DpPrPacketVector interface .

process EcDpPrDeletion

/ecs/formal/PDPS/DPS/PRONG/src/DataMgmt/DeletionPF

This DCE server accepts delete requests from clients and either issues delete requests to science data server upon expiration of the timer or deletes the specified granules from the disk and the PDPS database..

The server fulfills a function to remove interim granules after a specified period of time. It handles both long and short delete request in exactly the same manner, and has a single time checker thread that sleeps for the most part, but wakes periodically to check to see if a granule's time has expired. The destaging process is the only client to the deletion server, as that is where granules are checked to see if they are interim, and if so, the DPR checks to see if it needs to issue a delete request.

The server also fulfills a function to remove granules when the Production Request Editor is deleting Production Requests. When a Production Request is deleted, all granules associated with the underlying DPRs are deleted (excluding some specific types of data). Deletion Server accepts a list of such associated granules and removes them from the PDPS database and the disks on the science processors.

Classes

- Deletion_1_0
- Deletion_1_0_ABS
- Deletion_1_0_Mgr -- This is a class that is used for communications with other servers.
- DpDeletion -- This class is a dummy definition for the interface methods for Deletion Server.
- DpDeletionProxy -- Converts the data types into the required OODCE formats before calling the underlying OODCE client-side function and converts the return DCE data back to what's required.
- DpDeletionServer

Libraries Linked

- agentevent -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsEmMailRelA -- This Library is used for the emails using sendmail utility and the nnpst for Bulletin board messages.
- CsFtFTPRelA -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObj -- This library provides functions to use FTP at a scheduled time by the User.
- DpDeletionClient -- The library containing the client side operations to issue requests to the deletion server.
- DpPrDbPf -- This library contains the PDPS database interface classes for use with the Process Framework access to the database.
- DpPrDM -- This library supplies utility operations to manage data within DPS.
- DpPrDssIF -- This library contains the helper object for PDPS to interact with science data server.
- DpPrEM -- This library supplies utility operations to manage PGE execution within PRONG.
- DpPrException -- This library provides APIs to catch and handle signals.

- DpPrRM -- This library supplies utility operations to manage computer resources for PDPS.
- DpPrTools -- This library contains global utility functions.
- DsCl -- This library contains classes which make up the Science Data Server's (SDSRV) public interface. These classes are used by clients to connect, build commands, and submit requests to the SDSRV.
- DsCn -- This library is used to access a server specific configuration file.
- DsSh -- This library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- EcCf -- The Config library (CF) is a static library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistry
- EcDcMsgPsngr1 -- This library consists of message passing objects used by both the client and server side.
- EcDnDir -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcDpJobMgmtClient -- The Job Management Client library provides the following public interfaces to the Job Management Server.
- EcFh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLoc -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcNsServiceLocator -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcPf -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPo -- The Persistent CSC provides a set of abstract and base classes for approved advertisements and requests.
- EcPoDbRW
- EcPtSpecialLock -- This library provides classes for mutex operations and thread IDs.
- EcSeCmi -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeServerKeyMgmt -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbed -- This static Library is the stubbed version of EcSeSybSecurity.
- EcSeUtilityDbStubbed -- This static Library is stub version of the EcSeUtilityDb library.

- EcTiTime -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUr -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUt -- EcUt is a utility library for all the ECS applications.
- EcUtFactory -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtMisc -- This library contains miscellaneous utilities.
- event -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- Gl -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.
- IoAdCore -- The CoreLib CSC provides a set of functionalities for describing a generic advertisement, parsing and validating attributes that support the ECS Core meta data model, and requesting and moderating advertisements.
- IoAdProxy -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSearch -- The SearchLib CSC provides a set of searching capabilities for approved advertisements, for the administration of groups, and for moderation of requests.
- IoAdServer -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSubs -- The SubsLib CSC provides a set of derived classes which represent different types of advertisements: products, services, and providers.
- MsAcClnt -- The Accountability Management Service makes the user profile available to the various subsystems, such as the Data Server subsystem, information such as the user's electronic mail address and the shipping address, which are used for the distribution of
- MsAcComm -- This library contains class used for both Accountability Server and Client
- PlCore1 -- This library contains the first half of Planning's core functionality. The CoreLib provides functionality for all areas of Planning. It was divided in half due to its large size...
- PlCore2 -- This library contains the second half of Planning's core functionality. The CoreLib provides functionality for all areas of Planning. It was divided in half due to its large size...
- PlSSIT -- This library manages the Science Software Integration & Test PDPS DB interfaces.
- PlUtil -- This library contains utilities dealing with current time, time periods, time boundaries, time windows, time intervals, spacecraft, orbit, instruments, and also manages their DB interfaces.

process EcDpPrDM

/ecs/formal/PDPS/DPS/PRONG/src/DataMgmt

The executable run by autosys for staging or destaging within a DPR.

This executable expects a number of command line arguments, and not only stages granules needed for the run, but also takes care of allocation of those granules, and inserting the output granules into the science data server.

The process runs in autosys as two of the job components on a DPR box - the ones ending in 'S' and 'I'. ('S'tage and 'I'nsert). Allocation occurs through calls to the resource manager library, and interaction with science data server is handled through calls to the DSS interfaces library. This process also connects with the deletion server when it needs to signal a particular interim granule for short or long delete.

Libraries Linked

- agentevent -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsEmMailRelA -- This Library is used for the emails using sendmail utility and the nnpst for Bulletin board messages.
- CsFtFTPRelA -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObj -- This library provides functions to use FTP at a scheduled time by the User.
- DpDeletionClient -- The library containing the client side operations to issue requests to the deletion server.
- DpPrDbPf -- This library contains the PDPS database interface classes for use with the Process Framework access to the database.
- DpPrDM -- This library supplies utility operations to manage data within DPS.
- DpPrDssIF -- This library contains the helper object for PDPS to interact with science data server.
- DpPrEM -- This library supplies utility operations to manage PGE execution within PRONG.
- DpPrException -- This library provides APIs to catch and handle signals.
- DpPrJM -- The Job Management library provides service routines for the Job Management Server to use to manage the flow of jobs in all AutoSys instances for a mode.
- DpPrRM -- This library supplies utility operations to manage computer resources for PDPS.
- DpPrTools -- This library contains global utility functions.
- DpPrUpdateStatus
- DsCl -- This library contains classes which make up the Science Data Server's (SDSRV) public interface. These classes are used by clients to connect, build commands, and submit requests to the SDSRV.
- DsCn -- This library is used to access a server specific configuration file.

- DsSh -- This library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- EcCf -- The Config library (CF) is a static library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistry
- EcDcMsgPsnng1 -- This library consists of message passing objects used by both the client and server side.
- EcDnDir -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcDpJobMgmtClient -- The Job Management Client library provides the following public interfaces to the Job Management Server.
- EcFh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLoc -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcNsServiceLocator -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcPf -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPo -- The Persistent CSC provides a set of abstract and base classes for approved advertisements and requests.
- EcPoDbRW
- EcPtSpecialLock -- This library provides classes for mutex operations and thread IDs.
- EcSbCl -- This library contains all the classes for Subscription Server client.
- EcSbMsg -- This library contains all message classes used for the communication between Subscription Server and its client objects provided by Subscription Server client library.
- EcSeCmi -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeServerKeyMgmt -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbed -- This static Library is the stubbed version of EcSeSybSecurity.
- EcSeUtilityDbStubbed -- This static Library is stub version of the EcSeUtilityDb library.
- EcTiTime -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUr -- A Universal Reference (UR) is created as a logical reference to an extant ECS object.
- EcUt -- EcUt is a utility library for all the ECS applications.

- EcUtFactory -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtMisc -- This library contains miscellaneous utilities.
- event -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- Gl -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.
- IoAdCore -- The CoreLib CSC provides a set of functionalities for describing a generic advertisement, parsing and validating attributes that support the ECS Core meta data model, and requesting and moderating advertisements.
- IoAdProxy -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSearch -- The SearchLib CSC provides a set of searching capabilities for approved advertisements, for the administration of groups, and for moderation of requests.
- IoAdServer -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSubs -- The SubsLib CSC provides a set of derived classes which represent different types of advertisements: products, services, and providers.
- MsAcClnt -- The Accountability Management Service makes the user profile available to the various subsystems, such as the Data Server subsystem, information such as the user's electronic mail address and the shipping address, which are used for the distribution of
- MsAcComm -- This library contains class used for both Accountability Server and Client
- PICore1IF -- This library contains the Science Data Server, advertisement, and subscription server interfaces that are needed to run the Production request editor.
- PICore2 -- This library contains the second half of Planning's core functionality. The CoreLib provides functionality for all areas of Planning. It was divided in half due to its large size...
- PISSIT -- This library manages the Science Software Integration & Test PDPS DB interfaces.
- PIUtil -- This library contains utilities dealing with current time, time periods, time boundaries, time windows, time intervals, spacecraft, orbit, instruments, and also manages their DB interfaces.
- srf -- The SRF library provides the necessary mechanism for the application to communicate asynchronously with another application.

process EcDpPrDumpEphemerisDPREP

/ecs/formal/PDPS/DPS/PRONG/src/PreProcess

This is a test program and is not used in any of our delivered code.

Classes

- DpPrAttitudeDataSet -- This class creates the HDF and native data sets and associated metadata created from the AM1 ancillary packet attitude data.
- DpPrCcsdsPacket -- This is an abstract class for telemetry packets that conform to the Consultive Committee for Space Data Systems standard for the Version 1 Telemetry Source Packet format.
- DpPrDataQualityFlags -- The class DpPrDataQualityFlags encapsulates the data quality flags used in ephemeris and attitude preprocessing.
- DpPrEphemerisDataSet -- This class creates the HDF and native data sets and associated metadata created from the AM1 ancillary packet ephemeris data.
- DpPrEphemerisRecord -- This class represents the time-ordered set of reformatted ephemeris records parsed from the FDF Ephemeris Dataset EPHEM format record.
- DpPrPcfParameters -- Retrieves Runtime parameters from the current PCF.

Templates

- DpPrPacketVector -- DpPrPacketVector interface .

process EcDpPrEM

/ecs/formal/PDPS/DPS/PRONG/src/ExecMgmt

This program is responsible to manage pge execution.

This program has various command line options. Option "-alloc" is exercised by the allocation job (the first job in the job box in autosys, the one that ends with 'A'). This option will allocate the necessary computer resources to run the pge, and stage the pge executable to the machine where the pge is scheduled to run (if needed).

Option "-prep" is exercised by the Pre-Processing job (the third job in the job box in autosys, the one that ends with 'P'). This option creates the Process Control File (PCF), (See Toolkit's user manual for more information on PCF) obtains the MCF (Metadata Control File) from Science data server for each expected output of the pge. Also, other necessary files used by the PGE Wrapper executable are created. This job is run right before the pge is executed.

Option "-post" is exercised by the Post-Processing job (the fifth job in the job box in autosys, the one that ends with 'p'). This job is executed right after the pge is executed. It checks for the success/failure of the pge execution, records pge's resource usage information in the database. If the pge succeeds, then it creates production history file (which has information on the data lineage). If the pge fails, it creates a tar file which consists of pge's logs and pge's core file. This file is then archived through science data server.

Option "-dealloc" is the last job in the job box in autosys. (This ends with 'D'). This job is responsible for deallocating computer resources allocated and destroying any temporary directories/files created (such as the runtime directory). Also notifies job management server that the job box is complete and can be removed from autosys.

Libraries Linked

- agentevent -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsEmMailRelA -- This Library is used for the emails using sendmail utility and the nnpst for Bulletin board messages.
- CsFtFTPRelA -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObj -- This library provides functions to use FTP at a scheduled time by the User.
- DpDeletionClient -- The library containing the client side operations to issue requests to the deletion server.
- DpPrDbPf -- This library contains the PDPS database interface classes for use with the Process Framework access to the database.
- DpPrDM -- This library supplies utility operations to manage data within DPS.
- DpPrDssIF -- This library contains the helper object for PDPS to interact with science data server.
- DpPrEM -- This library supplies utility operations to manage PGE execution within PRONG.
- DpPrException -- This library provides APIs to catch and handle signals.
- DpPrJM -- The Job Management library provides service routines for the Job Management Server to use to manage the flow of jobs in all AutoSys instances for a mode.
- DpPrRM -- This library supplies utility operations to manage computer resources for PDPS.
- DpPrTools -- This library contains global utility functions.
- DpPrUpdateStatus
- DsCl -- This library contains classes which make up the Science Data Server's (SDSRV) public interface. These classes are used by clients to connect, build commands, and submit requests to the SDSRV.
- DsCn -- This library is used to access a server specific configuration file.
- DsSh -- This library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- EcCf -- The Config library (CF) is a static library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistry
- EcDcMsgPsgng1 -- This library consists of message passing objects used by both the client and server side.
- EcDnDir -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.

- EcDpJobMgmtClient -- The Job Management Client library provides the following public interfaces to the Job Management Server.
- EcFh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLoc -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcNsServiceLocator -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcPf -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPo -- The Persistent CSC provides a set of abstract and base classes for approved advertisements and requests.
- EcPoDbRW
- EcPtSpecialLock -- This library provides classes for mutex operations and thread IDs.
- EcSbCl -- This library contains all the classes for Subscription Server client.
- EcSbMsg -- This library contains all message classes used for the communication between Subscription Server and its client objects provided by Subscription Server client library.
- EcSeCmi -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeServerKeyMgmt -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbed -- This static Library is the stubbed version of EcSeSybSecurity.
- EcSeUtilityDbStubbed -- This static Library is stub version of the EcSeUtilityDb library.
- EcTiTime -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUr -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUt -- EcUt is a utility library for all the ECS applications.
- EcUtFactory -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtMisc -- This library contains miscellaneous utilities.
- event -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- Gl -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.
- IoAdCore -- The CoreLib CSC provides a set of functionalities for describing a generic advertisement, parsing and validating attributes that support the ECS Core meta data model, and requesting and moderating advertisements.
- IoAdProxy -- The ServerLib CSC provides classes for process framework DCE server and client.

- IoAdSearch -- The SearchLib CSC provides a set of searching capabilities for approved advertisements, for the administration of groups, and for moderation of requests.
- IoAdServer -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSubs -- The SubsLib CSC provides a set of derived classes which represent different types of advertisements: products, services, and providers.
- MsAcClnt -- The Accountability Management Service makes the user profile available to the various subsystems, such as the Data Server subsystem, information such as the user's electronic mail address and the shipping address, which are used for the distribution of
- MsAcComm -- This library contains class used for both Accountability Server and Client
- PICore1IF -- This library contains the Science Data Server, advertisement, and subscription server interfaces that are needed to run the Production request editor.
- PICore2 -- This library contains the second half of Planning's core functionality. The CoreLib provides functionality for all areas of Planning. It was divided in half due to its large size...
- PISSIT -- This library manages the Science Software Integration & Test PDPS DB interfaces.
- PIUtil -- This library contains utilities dealing with current time, time periods, time boundaries, time windows, time intervals, spacecraft, orbit, instruments, and also manages their DB interfaces.
- srf -- The SRF library provides the necessary mechanism for the application to communicate asynchronously with another application.

process EcDpPrGE

/ecs/formal/PDPS/DPS/PRONG/src/ExecMgmt

This executable is the ground event executable.

A ground event takes a specified computer resource offline (unavailable for pges) for a specified period of time. This is accomplished by marking in the database that the resource is offline, then executing a system sleep command for the specified duration, and updating the database to reflect that the specified resource is now available.

This program has signal handling functionality built in, so that if a ground event is cancelled, then the database is updated to mark the resources online before exiting.

Libraries Linked

- agentevent -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsEmMailRelA -- This Library is used for the emails using sendmail utility and the nnpost for Bulletin board messages.
- CsFtFTPRelA -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObj -- This library provides functions to use FTP at a scheduled time by the User.

- DpDeletionClient -- The library containing the client side operations to issue requests to the deletion server.
- DpPrDbPf -- This library contains the PDPS database interface classes for use with the Process Framework access to the database.
- DpPrDM -- This library supplies utility operations to manage data within DPS.
- DpPrDssIF -- This library contains the helper object for PDPS to interact with science data server.
- DpPrEM -- This library supplies utility operations to manage PGE execution within PRONG.
- DpPrException -- This library provides APIs to catch and handle signals.
- DpPrJM -- The Job Management library provides service routines for the Job Management Server to use to manage the flow of jobs in all AutoSys instances for a mode.
- DpPrRM -- This library supplies utility operations to manage computer resources for PDPS.
- DpPrTools -- This library contains global utility functions.
- DpPrUpdateStatus
- DsCl -- This library contains classes which make up the Science Data Server's (SDSRV) public interface. These classes are used by clients to connect, build commands, and submit requests to the SDSRV.
- DsCn -- This library is used to access a server specific configuration file.
- DsSh -- This library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- EcCf -- The Config library (CF) is a static library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistry
- EcDcMsgPsgn1 -- This library consists of message passing objects used by both the client and server side.
- EcDnDir -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcDpJobMgmtClient -- The Job Management Client library provides the following public interfaces to the Job Management Server.
- EcFh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLoc -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcNsServiceLocator -- The Service Locator library provides an implementation independent mechanism for specifying service locations.

- EcPf -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPo -- The Persistent CSC provides a set of abstract and base classes for approved advertisements and requests.
- EcPoDbRW
- EcPtSpecialLock -- This library provides classes for mutex operations and thread IDs.
- EcSbCl -- This library contains all the classes for Subscription Server client.
- EcSbMsg -- This library contains all message classes used for the communication between Subscription Server and its client objects provided by Subscription Server client library.
- EcSeCmi -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeServerKeyMgmt -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbed -- This static Library is the stubbed version of EcSeSybSecurity.
- EcSeUtilityDbStubbed -- This static Library is stub version of the EcSeUtilityDb library.
- EcTiTime -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUr -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUt -- EcUt is a utility library for all the ECS applications.
- EcUtFactory -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtMisc -- This library contains miscellaneous utilities.
- event -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- Gl -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.
- IoAdCore -- The CoreLib CSC provides a set of functionalities for describing a generic advertisement, parsing and validating attributes that support the ECS Core meta data model, and requesting and moderating advertisements.
- IoAdProxy -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSearch -- The SearchLib CSC provides a set of searching capabilities for approved advertisements, for the administration of groups, and for moderation of requests.
- IoAdServer -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSubs -- The SubsLib CSC provides a set of derived classes which represent different types of advertisements: products, services, and providers.

- MsAcClnt -- The Accountability Management Service makes the user profile available to the various subsystems, such as the Data Server subsystem, information such as the user's electronic mail address and the shipping address, which are used for the distribution of
- MsAcComm -- This library contains class used for both Accountability Server and Client
- PICore1IF -- This library contains the Science Data Server, advertisement, and subscription server interfaces that are needed to run the Production request editor.
- PICore2 -- This library contains the second half of Planning's core functionality. The CoreLib provides functionality for all areas of Planning. It was divided in half due to its large size...
- PISSIT -- This library manages the Science Software Integration & Test PDPS DB interfaces.
- PIUtil -- This library contains utilities dealing with current time, time periods, time boundaries, time windows, time intervals, spacecraft, orbit, instruments, and also manages their DB interfaces.
- srf -- The SRF library provides the necessary mechanism for the application to communicate asynchronously with another application.

process EcDpPrJobMgmt

/ecs/formal/PDPS/DPS/PRONG/src/JobMgmtPF

The Job Management Server is an ECS Managed Server program that provides services to create, cancel and release production and ground event jobs. This program accepts messages from the Job Management Client Proxy routines and provides the following services:

CreateDprJob - Creates a job directly in AutoSys, or on a queue if its data is not available.

ReleaseDprJob - Sets the state of a job to "Released" -- it is then eligible to be placed in AutoSys by the server if there is room.

CreateGEvtJob - Creates a ground event job directly in AutoSys.

CancelGEvtJob - Cancels a ground event job.

GetDprJobStatus- Gets the status of a job - started, success, failed,etc.

CancelDprJob - Cancels a job - either removes it from the queue or removes it from AutoSys if it is there, with database cleanup.

FreeAutoSys - Called whenever it is necessary to check the queue for jobs to put into Autosys -- this happens when a job is released, canceled, created or a job completes.

Classes

- DpPrSchedulerDObj_1_0_ABS
- DpPrSchedulerDObj_1_0_Mgr -- This is a class that is used for communications with other servers.
- MyManagedServer -- This is an example how an application can use Process Frame Work to create a managed server.

Libraries Linked

- agentevent -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsEmMailRelA -- This Library is used for the emails using sendmail utility and the nnpst for Bulletin board messages.
- CsFtFTPRelA -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObj -- This library provides functions to use FTP at a scheduled time by the User.
- DpDeletionClient -- The library containing the client side operations to issue requests to the deletion server.
- DpPrDbPf -- This library contains the PDPS database interface classes for use with the Process Framework access to the database.
- DpPrDM -- This library supplies utility operations to manage data within DPS.
- DpPrDssIF -- This library contains the helper object for PDPS to interact with science data server.
- DpPrEM -- This library supplies utility operations to manage PGE execution within PRONG.
- DpPrException -- This library provides APIs to catch and handle signals.
- DpPrJM -- The Job Management library provides service routines for the Job Management Server to use to manage the flow of jobs in all AutoSys instances for a mode.
- DpPrRM -- This library supplies utility operations to manage computer resources for PDPS.
- DpPrTools -- This library contains global utility functions.
- DpPrUpdateStatus
- DsCl -- This library contains classes which make up the Science Data Server's (SDSRV) public interface. These classes are used by clients to connect, build commands, and submit requests to the SDSRV.
- DsCn -- This library is used to access a server specific configuration file.
- DsSh -- This library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- EcCf -- The Config library (CF) is a static library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistry
- EcDcMsgPsgng1 -- This library consists of message passing objects used by both the client and server side.
- EcDnDir -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.

- EcDpJobMgmtClient -- The Job Management Client library provides the following public interfaces to the Job Management Server.
- EcFh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLoc -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcNsServiceLocator -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcPf -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPo -- The Persistent CSC provides a set of abstract and base classes for approved advertisements and requests.
- EcPoDbRW
- EcPtSpecialLock -- This library provides classes for mutex operations and thread IDs.
- EcSeCmi -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeServerKeyMgmt -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbed -- This static Library is the stubbed version of EcSeSybSecurity.
- EcSeUtilityDbStubbed -- This static Library is stub version of the EcSeUtilityDb library.
- EcTiTime -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUr -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUt -- EcUt is a utility library for all the ECS applications.
- EcUtFactory -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtMisc -- This library contains miscellaneous utilities.
- event -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- Gl -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.
- IoAdCore -- The CoreLib CSC provides a set of functionalities for describing a generic advertisement, parsing and validating attributes that support the ECS Core meta data model, and requesting and moderating advertisements.
- IoAdProxy -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSearch -- The SearchLib CSC provides a set of searching capabilities for approved advertisements, for the administration of groups, and for moderation of requests.

- IoAdServer -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSubs -- The SubsLib CSC provides a set of derived classes which represent different types of advertisements: products, services, and providers.
- MsAcClnt -- The Accountability Management Service makes the user profile available to the various subsystems, such as the Data Server subsystem, information such as the user's electronic mail address and the shipping address, which are used for the distribution of
- MsAcComm -- This library contains class used for both Accountability Server and Client
- PlCore1 -- This library contains the first half of Planning's core functionality. The CoreLib provides functionality for all areas of Planning. It was divided in half due to its large size...
- PlCore2 -- This library contains the second half of Planning's core functionality. The CoreLib provides functionality for all areas of Planning. It was divided in half due to its large size...
- PlSSIT -- This library manages the Science Software Integration & Test PDPS DB interfaces.
- PlUtil -- This library contains utilities dealing with current time, time periods, time boundaries, time windows, time intervals, spacecraft, orbit, instruments, and also manages their DB interfaces.

process EcDpPrJobMgmtClient

/ecs/formal/PDPS/DPS/PRONG/src/JobMgmtPF

The Job Management Client program is used as a test tool to test the operation of the Job Management Server, and is capable of creating, cancelling and releasing jobs. Normally, these services are requested by the Planning subsystem Production Request Editor and Planning Workbench.

This program uses routines from the Job Management Client Proxy Library.

Libraries Linked

- agentevent -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsEmMailRelA -- This Library is used for the emails using sendmail utility and the nnpst for Bulletin board messages.
- CsFtFTPRelA -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObj -- This library provides functions to use FTP at a scheduled time by the User.
- DpDeletionClient -- The library containing the client side operations to issue requests to the deletion server.
- DpPrDbPf -- This library contains the PDPS database interface classes for use with the Process Framework access to the database.
- DpPrDM -- This library supplies utility operations to manage data within DPS.

- DpPrDssIF -- This library contains the helper object for PDPS to interact with science data server.
- DpPrEM -- This library supplies utility operations to manage PGE execution within PRONG.
- DpPrException -- This library provides APIs to catch and handle signals.
- DpPrJM -- The Job Management library provides service routines for the Job Management Server to use to manage the flow of jobs in all AutoSys instances for a mode.
- DpPrRM -- This library supplies utility operations to manage computer resources for PDPS.
- DpPrTools -- This library contains global utility functions.
- DpPrUpdateStatus
- DsCl -- This library contains classes which make up the Science Data Server's (SDSRV) public interface. These classes are used by clients to connect, build commands, and submit requests to the SDSRV.
- DsCn -- This library is used to access a server specific configuration file.
- DsSh -- This library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- EcCf -- The Config library (CF) is a static library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistry
- EcDcMsgPsgn1 -- This library consists of message passing objects used by both the client and server side.
- EcDnDir -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcDpJobMgmtClient -- The Job Management Client library provides the following public interfaces to the Job Management Server.
- EcFh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLoc -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcNsServiceLocator -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcPf -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPo -- The Persistent CSC provides a set of abstract and base classes for approved advertisements and requests.
- EcPoDbRW
- EcPtSpecialLock -- This library provides classes for mutex operations and thread IDs.

- EcSeCmi -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeServerKeyMgmt -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbed -- This static Library is the stubbed version of EcSeSybSecurity.
- EcSeUtilityDbStubbed -- This static Library is stub version of the EcSeUtilityDb library.
- EcTiTime -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUr -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUt -- EcUt is a utility library for all the ECS applications.
- EcUtFactory -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtMisc -- This library contains miscellaneous utilities.
- event -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- Gl -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.
- IoAdCore -- The CoreLib CSC provides a set of functionalities for describing a generic advertisement, parsing and validating attributes that support the ECS Core meta data model, and requesting and moderating advertisements.
- IoAdProxy -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSearch -- The SearchLib CSC provides a set of searching capabilities for approved advertisements, for the administration of groups, and for moderation of requests.
- IoAdServer -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSubs -- The SubsLib CSC provides a set of derived classes which represent different types of advertisements: products, services, and providers.
- MsAcClnt -- The Accountability Management Service makes the user profile available to the various subsystems, such as the Data Server subsystem, information such as the user's electronic mail address and the shipping address, which are used for the distribution of
- MsAcComm -- This library contains class used for both Accountability Server and Client
- PlCore1 -- This library contains the first half of Planning's core functionality. The CoreLib provides functionality for all areas of Planning. It was divided in half due to its large size...
- PlCore2 -- This library contains the second half of Planning's core functionality. The CoreLib provides functionality for all areas of Planning. It was divided in half due to its large size...
- PlSSIT -- This library manages the Science Software Integration & Test PDPS DB interfaces.

- PIUtil -- This library contains utilities dealing with current time, time periods, time boundaries, time windows, time intervals, spacecraft, orbit, instruments, and also manages their DB interfaces.

process EcDpPrQaMonitorGUI

/ecs/formal/PDPS/DPS/PRONG/src/QaMonitorGUI

This is the name of the binary file for the QA Monitor GUI application. To invoke the QA Monitor GUI application requires five arguments: a) program name, b) the word "ConfigFile", c) the fullpathname of the configuration file which contains parameter names and values needed to run the QA Monitor GUI, the word "ecs_mode", and e) the mode the application will run in (i.e. operational, test, etc.).

Classes

- DpPrQaMmainWindow -- Created by Builder Xcessory Version 5.0.3.
- UIComponent -- Base class for all C++/Motif UI components.

Libraries Linked

- agentevent -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsFtFTPReLA -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObj -- This library provides functions to use FTP at a scheduled time by the User.
- DpDeletionClient -- The library containing the client side operations to issue requests to the deletion server.
- DpPrDbPf -- This library contains the PDPS database interface classes for use with the Process Framework access to the database.
- DpPrDM -- This library supplies utility operations to manage data within DPS.
- DpPrDssIF -- This library contains the helper object for PDPS to interact with science data server.
- DpPrEM -- This library supplies utility operations to manage PGE execution within PRONG.
- DpPrException -- This library provides APIs to catch and handle signals.
- DpPrQaMonitor -- This library holds the functions and attributes that all the QA Monitor GUI to perform its various functions.
- DpPrRM -- This library supplies utility operations to manage computer resources for PDPS.
- DpPrTools -- This library contains global utility functions.
- DsCl -- This library contains classes which make up the Science Data Server's (SDSRV) public interface. These classes are used by clients to connect, build commands, and submit requests to the SDSRV.
- DsCn -- This library is used to access a server specific configuration file.

- DsSh -- This library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- EcCf -- The Config library (CF) is a static library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistry
- EcDcMsgPsnng1 -- This library consists of message passing objects used by both the client and server side.
- EcDnDir -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcDpJobMgmtClient -- The Job Management Client library provides the following public interfaces to the Job Management Server.
- EcFh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLoc -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcNsServiceLocator -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcPf -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPo -- The Persistent CSC provides a set of abstract and base classes for approved advertisements and requests.
- EcPoDbRW
- EcPtSpecialLock -- This library provides classes for mutex operations and thread IDs.
- EcSbCl -- This library contains all the classes for Subscription Server client.
- EcSbMsg -- This library contains all message classes used for the communication between Subscription Server and its client objects provided by Subscription Server client library.
- EcSeCmi -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeServerKeyMgmt -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbed -- This static Library is the stubbed version of EcSeSybSecurity.
- EcSeUtilityDbStubbed -- This static Library is stub version of the EcSeUtilityDb library.
- EcTiTime -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUr -- A Universal Reference (UR) is created as a logical reference to an extant ECS object.
- EcUt -- EcUt is a utility library for all the ECS applications.

- EcUtFactory -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtGUIg_mt_eh_tp
- EcUtHelpg_mt_eh_tp
- EcUtMisc -- This library contains miscellaneous utilities.
- event -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- Gl -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.
- IoAdCore -- The CoreLib CSC provides a set of functionalities for describing a generic advertisement, parsing and validating attributes that support the ECS Core meta data model, and requesting and moderating advertisements.
- IoAdProxy -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSearch -- The SearchLib CSC provides a set of searching capabilities for approved advertisements, for the administration of groups, and for moderation of requests.
- IoAdServer -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSubs -- The SubsLib CSC provides a set of derived classes which represent different types of advertisements: products, services, and providers.
- MsAcClnt -- The Accountability Management Service makes the user profile available to the various subsystems, such as the Data Server subsystem, information such as the user's electronic mail address and the shipping address, which are used for the distribution of
- MsAcComm -- This library contains class used for both Accountability Server and Client
- PICore1IF -- This library contains the Science Data Server, advertisement, and subscription server interfaces that are needed to run the Production request editor.
- PICore2 -- This library contains the second half of Planning's core functionality. The CoreLib provides functionality for all areas of Planning. It was divided in half due to its large size...
- PIGUIError -- This library contains the objects needed for SSIT and QA Monitor GUIs to display error messages.
- PISSIT -- This library manages the Science Software Integration & Test PDPS DB interfaces.
- PIUtil -- This library contains utilities dealing with current time, time periods, time boundaries, time windows, time intervals, spacecraft, orbit, instruments, and also manages their DB interfaces.
- srf -- The SRF library provides the necessary mechanism for the application to communicate asynchronously with another application.

process EcDpPrRunPGE

/ecs/formal/PDPS/DPS/PRONG/src/PGEMgmt

This program monitors the growth of PGE output files and invokes the EcDpPrRusage program responsible for PGE invocation and collection of resource usage data.

process EcDpPrRusage

/ecs/formal/PDPS/DPS/PRONG/src/PGEMgmt

This program is responsible for PGE invocation and resource usage data collection.

process EcDpPrViewJobStates

/ecs/formal/PDPS/DPS/PRONG/src/JobMgmtPF/JMUserInterface

This program is responsible to extract the Job Names, and states from the database.

This program is run from the Job Management Client. It is in the Ops Console GUI. You can select the Jobs Completed and the Jobs Waiting Buttons. This will then go to the database and find the appropriate jobs. Then a xemacs window is displayed with the data about the jobs.

This program can also be run by the command line by using the appropriate arguments.

Classes

- DpPrListJobs -- This DpPrListJobs class is the interface class for obtaining lists of dprs requested from the Autosys Job Activity Console.

Libraries Linked

- agentevent -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsFtFTPRelA -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObj -- This library provides functions to use FTP at a scheduled time by the User.
- DpDeletionClient -- The library containing the client side operations to issue requests to the deletion server.
- DpPrDbPf -- This library contains the PDPS database interface classes for use with the Process Framework access to the database.
- DpPrDM -- This library supplies utility operations to manage data within DPS.
- DpPrDssIF -- This library contains the helper object for PDPS to interact with science data server.
- DpPrEM -- This library supplies utility operations to manage PGE execution within PRONG.
- DpPrException -- This library provides APIs to catch and handle signals.
- DpPrJM -- The Job Management library provides service routines for the Job Management Server to use to manage the flow of jobs in all AutoSys instances for a mode.

- DpPrRM -- This library supplies utility operations to manage computer resources for PDPS.
- DpPrTools -- This library contains global utility functions.
- DsCl -- This library contains classes which make up the Science Data Server's (SDSRV) public interface. These classes are used by clients to connect, build commands, and submit requests to the SDSRV.
- DsCn -- This library is used to access a server specific configuration file.
- DsSh -- This library provides underlying DCE(ODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- EcCf -- The Config library (CF) is a static library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistry
- EcDcMsgPngl -- This library consists of message passing objects used by both the client and server side.
- EcDnDir -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcDpJobMgmtClient -- The Job Management Client library provides the following public interfaces to the Job Management Server.
- EcFh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLoc -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcNsServiceLocator -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcPf -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPo -- The Persistent CSC provides a set of abstract and base classes for approved advertisements and requests.
- EcPoDbRW
- EcPtSpecialLock -- This library provides classes for mutex operations and thread IDs.
- EcSbCl -- This library contains all the classes for Subscription Server client.
- EcSbMsg -- This library contains all message classes used for the communication between Subscription Server and its client objects provided by Subscription Server client library.
- EcSeCmi -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeServerKeyMgmt -- This library provides a mechanism for servers to read their DCE login key from a keytab file.

- EcSeSybSecurityStubbed -- This static Library is the stubbed version of EcSeSybSecurity.
- EcSeUtilityDbStubbed -- This static Library is stub version of the EcSeUtilityDb library.
- EcTiTime -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUr -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUt -- EcUt is a utility library for all the ECS applications.
- EcUtFactory -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtMisc -- This library contains miscellaneous utilities.
- event -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- Gl -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.
- IoAdCore -- The CoreLib CSC provides a set of functionalities for describing a generic advertisement, parsing and validating attributes that support the ECS Core meta data model, and requesting and moderating advertisements.
- IoAdProxy -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSearch -- The SearchLib CSC provides a set of searching capabilities for approved advertisements, for the administration of groups, and for moderation of requests.
- IoAdServer -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSubs -- The SubsLib CSC provides a set of derived classes which represent different types of advertisements: products, services, and providers.
- MsAcClnt -- The Accountability Management Service makes the user profile available to the various subsystems, such as the Data Server subsystem, information such as the user's electronic mail address and the shipping address, which are used for the distribution of
- MsAcComm -- This library contains class used for both Accountability Server and Client
- PlCore1 -- This library contains the first half of Planning's core functionality. The CoreLib provides functionality for all areas of Planning. It was divided in half due to its large size...
- PlCore1IF -- This library contains the Science Data Server, advertisement, and subscription server interfaces that are needed to run the Production request editor.
- PlCore2 -- This library contains the second half of Planning's core functionality. The CoreLib provides functionality for all areas of Planning. It was divided in half due to its large size...
- PlSSIT -- This library manages the Science Software Integration & Test PDPS DB interfaces.
- PlUtil -- This library contains utilities dealing with current time, time periods, time boundaries, time windows, time intervals, spacecraft, orbit, instruments, and also manages their DB interfaces.

- `srf` -- The SRF library provides the necessary mechanism for the application to communicate asynchronously with another application.

***process* hdiff**

/ecs/formal/PDPS/DPS/SSIT/src/DIF/HDIFF

This program supports the HDF Gui, and can be used standalone to compare HDF files.

Libraries Linked

- `hdiff` -- This library supports the program for the HDF Gui and command line version of the HDF comparison tool.

***script* acroread**

/ecs/formal/PDPS/DPS/SSIT/src/MGR

Shell script for launching Acrobat. This script determines what type of machine/os the user is running and then fires off the proper version of the software.

***script* AM1_DPREP_Step1**

/ecs/formal/PDPS/DPS/PRONG/src/PreProcess

***script* DpAtAcquireDAP**

/ecs/formal/PDPS/DPS/SSIT/src/Dsrv

Contains shell script to stage a Delivered Algorithm Package (DAP) file from the Data Server.

***script* DpAtAcquireMCF**

/ecs/formal/PDPS/DPS/SSIT/src/Dsrv

Contains shell script to request a copy of the MCF (Metadata Control File) for a specified ESĐT.

***script* DpAtCreateODLTpl**

/ecs/formal/PDPS/DPS/SSIT/src/Metadata

Contains shell script to run PDPS PGE SCIENCE metadata ODL template creation script.

***script* DpAtDefinePGE**

/ecs/formal/PDPS/DPS/SSIT/src/Metadata

Contains shell script to update PDPS/SSIT database with SCIENCE metadata.

***script* DpAtExtractPrologs**

/ecs/formal/PDPS/DPS/SSIT/src/PRO

Contains shell script to run source code prolog (header) extraction tool.

script DpAtHdiff

/ecs/formal/PDPS/DPS/SSIT/src/DIF

Contains shell script to run the HDF command-line file comparison tool.

script DpAtIDLStart

/ecs/formal/PDPS/DPS/SSIT/src/DIF

script DpAtInsertExe

/ecs/formal/PDPS/DPS/SSIT/src/Dsrv

Contains shell script to insert tar file of PGE executables to Data Server.

script DpAtInsertStatic

/ecs/formal/PDPS/DPS/SSIT/src/Dsrv

Contains shell script to insert a PGE static input file to Data Server.

script DpAtINSTALL

/ecs/formal/PDPS/DPS/SSIT/src/MGR

Install script for SSIT Manager. Checks that SDP Toolkit is installed; Makes a copy of the internal SSIT Manager Process Control File customized for the local environment.

script DpAtMgrBinDiffPrepareFiles

/ecs/formal/PDPS/DPS/SSIT/src/DIF

Contains script to do initialization of the binary file diff environment

script DpAtMgrCheckHdfFile

/ecs/formal/PDPS/DPS/SSIT/src/DIF

Contains IDL language here document shell script.

script DpAtMgrForcheck

/ecs/formal/PDPS/DPS/SSIT/src/MGR

Contains shell script to run FORCHECK FORTRAN 77 code checker.

script DpAtMgrXdiff

/ecs/formal/PDPS/DPS/SSIT/src/MGR

Contains shell script to run ASCII file comparison tool.

script DpAtReplaceString

/ecs/formal/PDPS/DPS/SSIT/src/DIF

Shell script to replace a string in many files

script DpAtTBD

/ecs/formal/PDPS/DPS/SSIT/src/MGR

Contains shell script for placeholder to TBD script.

script DpAtVerifyODL

/ecs/formal/PDPS/DPS/SSIT/src/Metadata

Contains shell script to chekc the PDPS Science ODL files.

script EcDpAtConfig

/ecs/formal/PDPS/DPS/SSIT/src/MGR

Generate config files.

script EcDpAtStartSSIT

/ecs/formal/PDPS/DPS/SSIT/src/MGR

script EcDpPrEMGetAncHeaders

/ecs/formal/PDPS/DPS/PRONG/src/PGEMgmt

This command utility is used to extract the header record of the Toolkit ancillary file which is pointed to by the Logical Unit Number. The results are written to the standard output.

script EcDpPrSMFCopy

/ecs/formal/PDPS/DPS/PRONG/src/ExecMgmt

This shell script copies SMFs file from toolkit message directory to PGE directory.

script EcDpPrStartDeletion

/ecs/formal/PDPS/DPS/PRONG/src/DataMgmt/DeletionPF

This script starts up the Deletion Server.

script EcDpPrStartQaMonitorGUI

/ecs/formal/PDPS/DPS/PRONG/src/QaMonitorGUI

Subsystem CSS

The Communications Subsystem (CSS) provides for the interconnection of users and service providers, transfer of information within the Earth Observing System Data and Information System (EOSDIS) Core System (ECS) and between ECS and many EOSDIS components and management of all ECS communications components. It supports and interacts with the Management Support Subsystem (MSS), Flight Operations Segment (FOS) and the other ECS subsystems.

process EcCsEmailParser

/ecs/formal/CSS/DOF/src/RELB_GATEWAY/EmailParser

EcCsEmailParser program is developed to support automated delivery of Expedited Data Set (EDS) from ECS to ASTER GDS.

EDS subscription is first issued from ECS side at GSFC DAAC on behalf of ASTER GDS. When EDS is ready, Subscription Server sends email notification to EmailParser Gateway which in turn sends EDN to ASTER GDS through email after retrieving all the necessary information from SDSRV using the granule UR parsed from email notification. Once ASTER GDS gets the EDN, they can request EDS by sending EDR to EmailParser Gateway through email. EmailParser Gateway then parse the EDR to get the granule UR, it then does Acquire to SDSRV which will FTP push the files together with a signal file to ASTER GDS.

Classes

- EcCsEmailParser -- This object class contains all the functionality of EmailParser.
- EcCsManagedServer -- This is a managed server created through Process Frame Work.

Libraries Linked

- agentevent -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsEmMailRelA -- This Library is used for the emails using sendmail utility and the nnpst for Bulletin board messages.
- CsFtFTPRelA -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObj -- This library provides functions to use FTP at a scheduled time by the User.
- DsCl -- This library contains classes which make up the Science Data Server's (SDSRV) public interface. These classes are used by clients to connect, build commands, and submit requests to the SDSRV.
- DsCn -- This library is used to access a server specific configuration file.
- DsSh -- This library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- EcCf -- The Config library (CF) is a static library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistry
- EcDcMsgPsnng1 -- This library consists of message passing objects used by both the client and server side.

- EcDnDir -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcFh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLoc -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcNsServiceLocator -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcPf -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPo -- The Persistent CSC provides a set of abstract and base classes for approved advertisements and requests.
- EcPoDbRW
- EcPtSpecialLock -- This library provides classes for mutex operations and thread IDs.
- EcSeCmi -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeServerKeyMgmt -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbed -- This static Library is the stubbed version of EcSeSybSecurity.
- EcSeUtilityCtStubbed -- This static Library is stub version of the EcSeUtilityCt library.
- EcTiTime -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUr -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUt -- EcUt is a utility library for all the ECS applications.
- EcUtFactory -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtMisc -- This library contains miscellaneous utilities.
- event -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- Gl -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.
- IoAdCore -- The CoreLib CSC provides a set of functionalities for describing a generic advertisement, parsing and validating attributes that support the ECS Core meta data model, and requesting and moderating advertisements.
- IoAdProxy -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSearch -- The SearchLib CSC provides a set of searching capabilities for approved advertisements, for the administration of groups, and for moderation of requests.

- IoAdServer -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSubs -- The SubsLib CSC provides a set of derived classes which represent different types of advertisements: products, services, and providers.
- MsAcClnt -- The Accountability Management Service makes the user profile available to the various subsystems, such as the Data Server subsystem, information such as the user's electronic mail address and the shipping address, which are used for the distribution of
- MsAcComm -- This library contains class used for both Accountability Server and Client

process EcCsLandsat7Gateway

/ecs/formal/CSS/DOF/src/RELB_GATEWAY/LANDSAT_GATEWAY

EcCsLandsat7Gateway program provides interoperability between socket based landsat Processing System(LPS) and DCE based Ingest Server within the ECS environment.

LPS and ECS work together to provide users access to data collected by the Enhanced Thematic Mapper Plus(ETM+) instrument flown on the Landsat7 satellite. The Landsat7 Project processes the raw instrument data into level 0R data and then provides the data to ECS for ingest, archive and distribution.

Landsat7 Gateway is used to pass control messages between LPS and Ingest which includes:

- * Authentication Request(TCP Session Authentication from LPS).
- * Authentication Response(Gateway decides if Authentication succeeds).
- * Data Availability Notice(DAN from LPS to Ingest).
- * Data Availability Acknowledgment(DAA from Ingest back to LPS).
- * Data Delivery Notice(DDN from Ingest to LPS, Gateway needs to authenticate itself to LPS before it can open an connection to pass DDN to LPS).
- * Data Delivery Acknowledgment(DDA from LPS to Ingest).

Classes

- CsGwELG -- ++ header files.
- CsGwLandsatMsg -- This derived class adds more functionality to the CsGwMessage class as needed in processing messages for landsat7 gateway.
- CsGwLEG -- ++ header files.
- CsGwManagedServer -- This is a managed server created through Process Frame Work.

Libraries Linked

- agentevent -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsFtFTPReIA -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObj -- This library provides functions to use FTP at a scheduled time by the User.

- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- EcCf -- The Config library (CF) is a static library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsGateway -- This static library may be used to send/receive gateway messages securely at a user specified level.
- EcCsRegistry
- EcDcMsgPsnng1 -- This library consists of message passing objects used by both the client and server side.
- EcDnDir -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcFh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLoc -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcNsServiceLocator -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcPf -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPtSpecialLock -- This library provides classes for mutex operations and thread IDs.
- EcSeCmi -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeServerKeyMgmt -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbed -- This static Library is the stubbed version of EcSeSybSecurity.
- EcSeUtilityCtStubbed -- This static Library is stub version of the EcSeUtilityCt library.
- EcTiTime -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUr -- A Universal Reference (UR) is created as a logical reference to an extant ECS object.
- EcUt -- EcUt is a utility library for all the ECS applications.
- EcUtFactory -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- event -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.

process EcCsMojoGateway

/ecs/formal/CSS/DOF/src/RELB_GATEWAY/MOJO/mojo

This program contains the MOJO Gateway Server. The MOJO Gateway provides a common interface and network address for all of the distributed ECS services accessible from the JAVA DAR Tool. The MOJO Gateway provides user session management, a secure gateway to DCE/OODCE security services, and the routing of user requests to the appropriate server.

Libraries Linked

- agentevent -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- Common -- This library contains classes for the EcsToV0Server and V0ToEcsServer executables.
- CsFtFTPReIA -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObj -- This library provides functions to use FTP at a scheduled time by the User.
- DmLmExtIf -- The DmLmExtIf library contains classes that allow the LIMGR to interface with external information managers.
- DmLmMsg -- The msg CSC provides classes for DM subsystem server and client.
- DmLmReqProc -- The reqproc CSC provides classes for DM subsystem server.
- DsCl -- This library contains classes which make up the Science Data Server's (SDSRV) public interface. These classes are used by clients to connect, build commands, and submit requests to the SDSRV.
- DsCn -- This library is used to access a server specific configuration file.
- DsSh -- This library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- EcCf -- The Config library (CF) is a static library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistry
- EcDcMsgPsg1 -- This library consists of message passing objects used by both the client and server side.
- EcDmLmClient
- EcDnDir -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcFh -- This library provides fault handling capabilities to ECS applications.

- EcGwDAR -- This library is the DAR Communications client library which client applications should link with to communicate with the DAR Gateway.
- EcNsServiceLoc -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcNsServiceLocator -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcPf -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPo -- The Persistent CSC provides a set of abstract and base classes for approved advertisements and requests.
- EcPoDbRW
- EcPtSpecialLock -- This library provides classes for mutex operations and thread IDs.
- EcSbCl -- This library contains all the classes for Subscription Server client.
- EcSbMsg -- This library contains all message classes used for the communication between Subscription Server and its client objects provided by Subscription Server client library.
- EcSeCmi -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeLoginContext -- This library uses the key obtained from either the EcSeServerKeyMgmt or EcSeAuthn library to establish a login context for a process.
- EcSeServerKeyMgmt -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbed -- This static Library is the stubbed version of EcSeSybSecurity.
- EcSeUtilityDbStubbed -- This static Library is stub version of the EcSeUtilityDb library.
- EcTiTime -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUr -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUt -- EcUt is a utility library for all the ECS applications.
- EcUtFactory -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtMisc -- This library contains miscellaneous utilities.
- event -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- Gl -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.
- IoAdCore -- The CoreLib CSC provides a set of functionalities for describing a generic advertisement, parsing and validating attributes that support the ECS Core meta data model, and requesting and moderating advertisements.

- IoAdProxy -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSearch -- The SearchLib CSC provides a set of searching capabilities for approved advertisements, for the administration of groups, and for moderation of requests.
- IoAdServer -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSubs -- The SubsLib CSC provides a set of derived classes which represent different types of advertisements: products, services, and providers.
- MsAcClnt -- The Accountability Management Service makes the user profile available to the various subsystems, such as the Data Server subsystem, information such as the user's electronic mail address and the shipping address, which are used for the distribution of
- MsAcComm -- This library contains class used for both Accountability Server and Client
- srf -- The SRF library provides the necessary mechanism for the application to communicate asynchronously with another application.

Shared Libraries Linked

- agenteventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsFtFTPRelASh -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObjSh -- This library provides functions to use FTP at a scheduled time by the User.
- EcCfSh -- The Config library (CF) is a shared library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistrySh
- EcDcMsgPsnng1Sh -- This library consists of message passing objects used by both the client and server side.
- EcDnDirSh -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcFhSh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLocatorSh -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcNsServiceLocSh -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcPfSh -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPoDbRWSH
- EcPoSh -- The Persistent CSC provides a set of abstract and base classes for approved advertisements and requests.

- EcPtSpecialLockSh -- This library provides classes for mutex operations and thread IDs.
- EcSeCmiSh -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeServerKeyMgmtSh -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbedSh -- This shared Library has only the methods for completing the successful compilation.
- EcSeUtilityDbStubbedSh -- This shared Library provides stubbed version of EcSeUtilityDb for successful compilation.
- EcTiTimeSh -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUrSh -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUtFactorySh -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtSh -- EcUt is a utility library for all the ECS applications.
- eventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- IoAdCoreSh -- The CoreLib CSC provides a set of functionalities for describing a generic advertisement, parsing and validating attributes that support the ECS Core meta data model, and requesting and moderating advertisements.
- IoAdProxySh -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdServerSh -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSubsSh -- The SubsLib CSC provides a set of derived classes which represent different types of advertisements: products, services, and providers.

process EcCsRegistry

/ecs/formal/CSS/DOF/src/REGISTRY/registry

Classes

- EcRgRegistry_1_0_ABS
- EcRgRegistry_1_0_Mgr
- EcRgRegistryServer_S
- EcRgRegistryServerLog
- EcRgTreeNode

Libraries Linked

- EcCf -- The Config library (CF) is a static library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcPtSpecialLock -- This library provides classes for mutex operations and thread IDs.
- EcSeCmi -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeServerKeyMgmt -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbed -- This static Library is the stubbed version of EcSeSybSecurity.
- EcSeUtilityDbStubbed -- This static Library is stub version of the EcSeUtilityDb library.
- EcUtFactory -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtNoPF -- EcUtNoPF is a utility library for all the ECS applications that do not use Process Framework.

process EcGwDARServer

/ecs/formal/CSS/DOF/src/RELB_GATEWAY/DAR/dar

This is the DAR Communications Gateway server executable, which will accept DAR submit, modify, and query requests and pass them on to GDS.

The main functionality of the ASTER DAR Gateway is to provide interoperability between the DAR Client GUI Tool and the DAR API which interfaces to the ASTER servers. The DAR Client GUI Tool is DCE compatible and based on X/Motif, while the DAR API is based on TCP/IP sockets. The DAR Communications Gateway receives calls from the DAR Client GUI Tool and dispatches them to the appropriate DAR API operations for remote services.

Classes

- EcGwDARGatewayDispatcher -- This class is the specialized dispatcher at the server side, which accepts a request and dispatches it to the appropriate method.
- EcGwDARGatewayManagedServer
- EcGwDARGatewayRequest_S -- This class represents the server side of DARGateway.
- getSubxARStatusSrfRequest -- This message class, which is derived from the EcUtStreamable class, is used to transport the getSubxARStatus request message by the Server Request Framework (SRF), which is utilized by the ASTER DAR Gateway client library and server for DCE .
- getSubxARStatusSrfResult -- This message class, which is derived from the EcUtStreamable class, is used to transport the getSubxARStatus result message by the Server Request Framework (SRF), which is utilized by the ASTER DAR Gateway client library and server for DCE .

- `getSubxARStatusSrfStatus` -- This message class, which is derived from the `EcUtStreamable` class, is used to transport the `getSubxARStatus` status message by the Server Request Framework (SRF), which is utilized by the ASTER DAR Gateway client library and server for DCE .
- `getxARStatusSrfRequest` -- This message class, which is derived from the `EcUtStreamable` class, is used to transport the `getxARStatus` request message by the Server Request Framework (SRF), which is utilized by the ASTER DAR Gateway client library and server for DCE communication.
- `getxARStatusSrfResult` -- This message class, which is derived from the `EcUtStreamable` class, is used to transport the `getxARStatus` result message by the Server Request Framework (SRF), which is utilized by the ASTER DAR Gateway client library and server for DCE communication.
- `getxARStatusSrfStatus` -- This message class, which is derived from the `EcUtStreamable` class, is used to transport the `getxARStatus` status message by the Server Request Framework (SRF), which is utilized by the ASTER DAR Gateway client library and server for DCE communication.
- `modifyDarSrfRequest` -- This message class, which is derived from the `EcUtStreamable` class, is used to transport the `modifyDar` request message by the Server Request Framework (SRF), which is utilized by the ASTER DAR Gateway client library and server for DCE communication.
- `modifyDarSrfResult` -- This message class, which is derived from the `EcUtStreamable` class, is used to transport the `modifyDar` result message by the Server Request Framework (SRF), which is utilized by the ASTER DAR Gateway client library and server for DCE communication.
- `modifyDarSrfStatus` -- This message class, which is derived from the `EcUtStreamable` class, is used to transport the `modifyDar` status message by the Server Request Framework (SRF), which is utilized by the ASTER DAR Gateway client library and server for DCE communication.
- `queryxARContentsSrfRequest` -- This message class, which is derived from the `EcUtStreamable` class, is used to transport the `queryxARContents` request message by the Server Request Framework (SRF), which is utilized by the ASTER DAR Gateway client library and server for DCE .
- `queryxARContentsSrfResult` -- This message class, which is derived from the `EcUtStreamable` class, is used to transport the `queryxARContents` result message by the Server Request Framework (SRF), which is utilized by the ASTER DAR Gateway client library and server for DCE .
- `queryxARContentsSrfStatus` -- This message class, which is derived from the `EcUtStreamable` class, is used to transport the `queryxARContents` status message by the Server Request Framework (SRF), which is utilized by the ASTER DAR Gateway client library and server for DCE .
- `queryxARScenesSrfRequest` -- This message class, which is derived from the `EcUtStreamable` class, is used to transport the `queryxARScenes` request message by the

Server Request Framework (SRF), which is utilized by the ASTER DAR Gateway client library and server for DCE .

- queryxARScenesSrfResult -- This message class, which is derived from the EcUtStreamable class, is used to transport the queryxARScenes result message by the Server Request Framework (SRF), which is utilized by the ASTER DAR Gateway client library and server for DCE .
- queryxARScenesSrfStatus -- This message class, which is derived from the EcUtStreamable class, is used to transport the queryxARScenes status message by the Server Request Framework (SRF), which is utilized by the ASTER DAR Gateway client library and server for DCE .
- queryxARSummarySrfRequest -- This message class, which is derived from the EcUtStreamable class, is used to transport the queryxARSummary request message by the Server Request Framework (SRF), which is utilized by the ASTER DAR Gateway client library and server for DCE .
- queryxARSummarySrfResult -- This message class, which is derived from the EcUtStreamable class, is used to transport the queryxARSummary result message by the Server Request Framework (SRF), which is utilized by the ASTER DAR Gateway client library and server for DCE .
- queryxARSummarySrfStatus -- This message class, which is derived from the EcUtStreamable class, is used to transport the queryxARSummary status message by the Server Request Framework (SRF), which is utilized by the ASTER DAR Gateway client library and server for DCE .
- submitDarSrfRequest -- This message class, which is derived from the EcUtStreamable class, is used to transport the submitDar request message by the Server Request Framework (SRF), which is utilized by the ASTER DAR Gateway client library and server for DCE communication.
- submitDarSrfResult -- This message class, which is derived from the EcUtStreamable class, is used to transport the submitDar result message by the Server Request Framework (SRF), which is utilized by the ASTER DAR Gateway client library and server for DCE communication.
- submitDarSrfStatus -- This message class, which is derived from the EcUtStreamable class, is used to transport the submitDar status message by the Server Request Framework (SRF), which is utilized by the ASTER DAR Gateway client library and server for DCE communication.

Libraries Linked

- agentevent -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsFtFTPReIA -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObj -- This library provides functions to use FTP at a scheduled time by the User.

- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- EcCf -- The Config library (CF) is a static library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistry
- EcDcMsgPsngr1 -- This library consists of message passing objects used by both the client and server side.
- EcDnDir -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcFh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLoc -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcNsServiceLocator -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcPf -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPoDbRW
- EcPtSpecialLock -- This library provides classes for mutex operations and thread IDs.
- EcSeCmi -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeServerKeyMgmt -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbed -- This static Library is the stubbed version of EcSeSybSecurity.
- EcSeUtilityDbStubbed -- This static Library is stub version of the EcSeUtilityDb library.
- EcTiTime -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUr -- A Universal Reference (UR) is created as a logical reference to an extant ECS object.
- EcUt -- EcUt is a utility library for all the ECS applications.
- EcUtFactory -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- event -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- IcDarApi -- This is the ASTER GDS client library which the DAR Communications Gateway links with to provide communication to the ASTER servers.
- MsAcClnt -- The Accountability Management Service makes the user profile available to the various subsystems, such as the Data Server subsystem, information such as the user's electronic mail address and the shipping address, which are used for the distribution of

- MsAcComm -- This library contains class used for both Accountability Server and Client
- srf -- The SRF library provides the necessary mechanism for the application to communicate asynchronously with another application.

process EcSbGui

/ecs/formal/CSS/DOF/src/SUBSCRIPTION/OperatorGui

The Subscription GUI provides an operator interface for submitting, updating and deleting subscriptions.

Classes

- EcSbGui -- Created by Builder Xcessory Version 5.0.3.
- EcSbGuiEvent -- Created by Builder Xcessory Version 5.0.3.
- EcSbGuiMW -- Created by Builder Xcessory Version 5.0.3.
- UIComponent -- Base class for all C++/Motif UI components.

Libraries Linked

- DsCl -- This library contains classes which make up the Science Data Server's (SDSRV) public interface. These classes are used by clients to connect, build commands, and submit requests to the SDSRV.
- DsCn -- This library is used to access a server specific configuration file.
- DsSh -- This library provides underlying DCE(ODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- EcFh -- This library provides fault handling capabilities to ECS applications.
- EcPoDbRW
- EcSbCl -- This library contains all the classes for Subscription Server client.
- EcSbMsg -- This library contains all message classes used for the communication between Subscription Server and its client objects provided by Subscription Server client library.
- EcUtGUIg_mt_eh_tp
- EcUtHelpg_mt_eh_tp
- EcUtMisc -- This library contains miscellaneous utilities.
- Gl -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.
- MsAcClnt -- The Accountability Management Service makes the user profile available to the various subsystems, such as the Data Server subsystem, information such as the user's electronic mail address and the shipping address, which are used for the distribution of
- MsAcComm -- This library contains class used for both Accountability Server and Client

- srf -- The SRF library provides the necessary mechanism for the application to communicate asynchronously with another application.

Shared Libraries Linked

- agenteventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsFtFTPRelASh -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObjSh -- This library provides functions to use FTP at a scheduled time by the User.
- EcCfSh -- The Config library (CF) is a shared library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistrySh
- EcDcMsgPsnng1Sh -- This library consists of message passing objects used by both the client and server side.
- EcDnDirSh -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcFhSh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLocatorSh -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcNsServiceLocSh -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcPfSh -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPoDbRWSH
- EcPoSh -- The Persistent CSC provides a set of abstract and base classes for approved advertisements and requests.
- EcPtSpecialLockSh -- This library provides classes for mutex operations and thread IDs.
- EcSeCmiSh -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeServerKeyMgmtSh -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbedSh -- This shared Library has only the methods for completing the successful compilation.
- EcSeUtilityDbStubbedSh -- This shared Library provides stubbed version of EcSeUtilityDb for successful compilation.
- EcTiTimeSh -- This library is used to obtain the current time in various formats, and manipulate the time.

- EcUrSh -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUtFactorySh -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtSh -- EcUt is a utility library for all the ECS applications.
- eventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- IoAdCoreSh -- The CoreLib CSC provides a set of functionalities for describing a generic advertisement, parsing and validating attributes that support the ECS Core meta data model, and requesting and moderating advertisements.
- IoAdProxySh -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSearchSh -- The SearchLib CSC provides a set of searching capabilities for approved advertisements, for the administration of groups, and for moderation of requests.
- IoAdServerSh -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSubsSh -- The SubsLib CSC provides a set of derived classes which represent different types of advertisements: products, services, and providers.

process EcSbSubServer

/ecs/formal/CSS/DOF/src/SUBSCRIPTION/sb

EcSbSubServer is subscription server program to provide subscription service. Subscription service defines three major roles for objects:

- 1) Publisher role: Publishers produce event data. Subscription server stored them persistently and made them available through Advertisement Service. Therefore, subscribers use event data to register interest in products and services.
- 2) Subscriber role: Accept subscription requests that specify an action to be taken and an event to initiate the action. Accept subscription update request to update stored subscriptions, validate subscription requests.
- 3) Process subscriptions upon Event Notification: Identify all subscriptions of the specified event. Process any actions defined in the subscriptions, then notify subscribers.

Libraries Linked

- CsEmMailRelA -- This Library is used for the emails using sendmail utility and the nnpst for Bulletin board messages.
- CsSeCryptoDes -- This library contains the APIs for the DES encryption algorithm.
- DmDdMsg -- This library defines messages to be passed to the Data Dictionary.
- DsCl -- This library contains classes which make up the Science Data Server's (SDSRV) public interface. These classes are used by clients to connect, build commands, and submit requests to the SDSRV.

- DsCn -- This library is used to access a server specific configuration file.
- DsSh -- This library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- DsSr -- This is an internal library for Science Data Server.
- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- EcDcMsgPsn1 -- This library consists of message passing objects used by both the client and server side.
- EcDmDdClient -- The library establishes and maintains a session with the DDICT server.
- EcFh -- This library provides fault handling capabilities to ECS applications.
- EcPoDbRW
- EcSbMsg -- This library contains all message classes used for the communication between Subscription Server and its client objects provided by Subscription Server client library.
- EcSbSr -- This library consists of all subscription server side class objects.
- EcUtMisc -- This library contains miscellaneous utilities.
- Gl -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.
- IoAdSearch -- The SearchLib CSC provides a set of searching capabilities for approved advertisements, for the administration of groups, and for moderation of requests.
- MsAcClnt -- The Accountability Management Service makes the user profile available to the various subsystems, such as the Data Server subsystem, information such as the user's electronic mail address and the shipping address, which are used for the distribution of
- MsAcComm -- This library contains class used for both Accountability Server and Client
- srf -- The SRF library provides the necessary mechanism for the application to communicate asynchronously with another application.

Shared Libraries Linked

- agenteventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsFtFTPRelASh -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObjSh -- This library provides functions to use FTP at a scheduled time by the User.
- EcCfSh -- The Config library (CF) is a shared library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistrySh
- EcDcMsgPsn1Sh -- This library consists of message passing objects used by both the client and server side.

- EcDnDirSh -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcFhSh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLocatorSh -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcNsServiceLocSh -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcPfSh -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPoDbRWSH
- EcPoSh -- The Persistent CSC provides a set of abstract and base classes for approved advertisements and requests.
- EcPtSpecialLockSh -- This library provides classes for mutex operations and thread IDs.
- EcSeCmiSh -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeServerKeyMgmtSh -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbedSh -- This shared Library has only the methods for completing the successful compilation.
- EcSeUtilityDbStubbedSh -- This shared Library provides stubbed version of EcSeUtilityDb for successful compilation.
- EcTiTimeSh -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUrSh -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUtFactorySh -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtSh -- EcUt is a utility library for all the ECS applications.
- eventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- IoAdCoreSh -- The CoreLib CSC provides a set of functionalities for describing a generic advertisement, parsing and validating attributes that support the ECS Core meta data model, and requesting and moderating advertisements.
- IoAdProxySh -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSearchSh -- The SearchLib CSC provides a set of searching capabilities for approved advertisements, for the administration of groups, and for moderation of requests.

- IoAdServerSh -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSubsSh -- The SubsLib CSC provides a set of derived classes which represent different types of advertisements: products, services, and providers.

process EcSeAuthnProg

/ecs/formal/CSS/DOF/src/AUTHN/authnprog

The AuthnProg GUI uses the EcSeCmi library to generate a randomized password for administration purposes. The GUI's only input is the seed. The tool is used primarily by administrators and M&O staff when setting up accounts for non-DCE components (i.e.: Sybase).

Classes

- Form -- This class implements a portion of the user interface.
- UIComponent -- Base class for all C++/Motif UI components.

Libraries Linked

- EcPtSpecialLock -- This library provides classes for mutex operations and thread IDs.
- EcSeCmi -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcUtFactory -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtNoPF -- EcUtNoPF is a utility library for all the ECS applications that do not use Process Framework.

process EcSeLoginProg

/ecs/formal/CSS/DOF/src/SEC/login/loginprog

This utility uses the EcSeLogin library to perform a DCE login.

Libraries Linked

- EcPtSpecialLock -- This library provides classes for mutex operations and thread IDs.
- EcSeLogin -- This library creates a DCE login context for a process.
- EcUtFactory -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtNoPF -- EcUtNoPF is a utility library for all the ECS applications that do not use Process Framework.

process EcTiDeltastore

/ecs/formal/CSS/DOF/src/TIME/time

This Program is used to create and store or change the Delta Time on CDS at the default location:

```
./.: /subsys/ecs/$(MODE)/DeltaTime
```

The CDS location should have insert permission to store the Delta Time. The Command Line inputs are: MODE Day Month Year. The Delta Time is calculated from the given Date (in Days)

Libraries Linked

- EcDnDir -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcPtSpecialLock -- This library provides classes for mutex operations and thread IDs.
- EcTiTime -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUtFactory -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtNoPF -- EcUtNoPF is a utility library for all the ECS applications that do not use Process Framework.

process EcUtCopyExec

/ecs/formal/COMMON/CSCI_Util/src/CopyProg

EcUtCopyExec is a binary for copying a source file to destination file. The source, destination files, block size for read/write, delay for retries are passed as arguments. This binary is called by the EcUtFileCopy Class.

Libraries Linked

- EcPtSpecialLock -- This library provides classes for mutex operations and thread IDs.
- EcUt -- EcUt is a utility library for all the ECS applications.
- EcUtFactory -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.

process ftp_popen

/ecs/formal/CSS/DOF/src/FTP/ftp_popen

This Executable is started by CsFtFTPReIA class for the FTP needs. This process acts as interface for the FTP Wrapper class and actual FTP process. FTP commands are read/write using socket.

Libraries Linked

- EcPtSpecialLock -- This library provides classes for mutex operations and thread IDs.
- EcUtFactory -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtNoPF -- EcUtNoPF is a utility library for all the ECS applications that do not use Process Framework.

***process* LoadingTool**

/ecs/formal/CSS/DOF/src/REGISTRY/PopulationTool

Classes

- EcCsConfigDbLoader -- >.

Libraries Linked

- EcUt -- EcUt is a utility library for all the ECS applications.
- EcUtFactory -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.

***process* modDar**

/ecs/formal/CSS/DOF/src/RELB_GATEWAY/DAR/gds/api

***process* queryCont**

/ecs/formal/CSS/DOF/src/RELB_GATEWAY/DAR/gds/api

***process* querySub**

/ecs/formal/CSS/DOF/src/RELB_GATEWAY/DAR/gds/api

***process* querySum**

/ecs/formal/CSS/DOF/src/RELB_GATEWAY/DAR/gds/api

***process* searchDar**

/ecs/formal/CSS/DOF/src/RELB_GATEWAY/DAR/gds/api

***process* subDar**

/ecs/formal/CSS/DOF/src/RELB_GATEWAY/DAR/gds/api

***process* subxarDar**

/ecs/formal/CSS/DOF/src/RELB_GATEWAY/DAR/gds/api

process update1900

/ecs/formal/CSS/DOF/src/SUBSCRIPTION/Update1900

This is a subscription server tool used by operator to convert all subscriptions' start and/or expiration date to Y2K compliance.

Classes

- Subscription -- This is the server side subscription representation.

Libraries Linked

- DsCl -- This library contains classes which make up the Science Data Server's (SDSRV) public interface. These classes are used by clients to connect, build commands, and submit requests to the SDSRV.
- DsCn -- This library is used to access a server specific configuration file.
- DsSh -- This library provides underlying DCE(OODCE) mechanism and fundamental implementation for both client and server side of SDSRV.
- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- EcSbMsg -- This library contains all message classes used for the communication between Subscription Server and its client objects provided by Subscription Server client library.
- EcUtMisc -- This library contains miscellaneous utilities.
- Gl -- This library is used by many subsystems to provide a general purpose list object for storing various scalar and complex datatypes.

Shared Libraries Linked

- agenteventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsFtFTPRelASh -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObjSh -- This library provides functions to use FTP at a scheduled time by the User.
- EcCfSh -- The Config library (CF) is a shared library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistrySh
- EcDcMsgPnglSh -- This library consists of message passing objects used by both the client and server side.
- EcDnDirSh -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcFhSh -- This library provides fault handling capabilities to ECS applications.

- EcNsServiceLocatorSh -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcNsServiceLocSh -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcPfSh -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPoDbRWSH
- EcPoSh -- The Persistent CSC provides a set of abstract and base classes for approved advertisements and requests.
- EcPtSpecialLockSh -- This library provides classes for mutex operations and thread IDs.
- EcSeCmiSh -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeServerKeyMgmtSh -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbedSh -- This shared Library has only the methods for completing the successful compilation.
- EcSeUtilityDbStubbedSh -- This shared Library provides stubbed version of EcSeUtilityDb for successful compilation.
- EcTiTimeSh -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUrSh -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUtFactorySh -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtSh -- EcUt is a utility library for all the ECS applications.
- eventSh -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- IoAdCoreSh -- The CoreLib CSC provides a set of functionalities for describing a generic advertisement, parsing and validating attributes that support the ECS Core meta data model, and requesting and moderating advertisements.
- IoAdProxySh -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSearchSh -- The SearchLib CSC provides a set of searching capabilities for approved advertisements, for the administration of groups, and for moderation of requests.
- IoAdServerSh -- The ServerLib CSC provides classes for process framework DCE server and client.
- IoAdSubsSh -- The SubsLib CSC provides a set of derived classes which represent different types of advertisements: products, services, and providers.

Subsystem MSS

The System Management Subsystem (MSS) provides support software services in the fault, configuration, accountability, performance, and security management areas. It is implemented using some custom software but relies heavily on standards-based COTS products. In many cases, a COTS product needs no custom software to meet requirements. Where custom software is required it is saved in these directories.

process EcAcRequestClientUpdate

/ecs/formal/MSS/MCI/Ac/src

Libraries Linked

- agentevent -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsEmMailRelA -- This Library is used for the emails using sendmail utility and the nnpst for Bulletin board messages.
- CsFtFTPRelA -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObj -- This library provides functions to use FTP at a scheduled time by the User.
- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- EcCf -- The Config library (CF) is a static library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistry
- EcDcMsgPsnng1 -- This library consists of message passing objects used by both the client and server side.
- EcDnDir -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcFh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLoc -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcNsServiceLocator -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcPf -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPoDbRW
- EcPtSpecialLock -- This library provides classes for mutex operations and thread IDs.
- ECSAuthn

- EcSeCmi -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeServerKeyMgmt -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbed -- This static Library is the stubbed version of EcSeSybSecurity.
- EcSeUtilityDbStubbed -- This static Library is stub version of the EcSeUtilityDb library.
- EcTiTime -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUr -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUt -- EcUt is a utility library for all the ECS applications.
- EcUtFactory -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- event -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- MD5Encrypt

process EcMsAcDAACRegUserGUI

/ecs/formal/MSS/MCI/Ac/src/MsAcDAACRegUserGUI

Classes

- EcAcTabState -- Create one instance of this for each tab in a tabstack.
- MsAcErrorMsgBox -- Created by Builder Xcessory Version 5.0.3.
- MsAcErrorMsgBoxDerived
- MsAcInfoMsgBox -- Created by Builder Xcessory Version 5.0.3.
- MsAcInformation
- MsAcInformationDerived
- MsAcManageExistingAcctMW
- MsAcManageExistingAcctMWDerived -- This class does all the operations that needs to manage the existing accounts.
- MsAcProcessAcctReqMW
- MsAcProcessAcctReqMWDerived -- This class does all the operations that needs to process an request acct.
- MsAcRegUsrUtl -- The MsAcRegUsrUtl class is a set of static functions of general utility to the Regsiter User GUI.
- MsAcUserAccountMngmtMW
- MsAcUserAccountMngmtMWDerived -- This class represents the main window.
- MsAcViewProfileDialog

- MsAcViewProfileDialogDerived
- UIComponent -- Base class for all C++/Motif UI components.

Libraries Linked

- agentevent -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsEmMailRelA -- This Library is used for the emails using sendmail utility and the nnpst for Bulletin board messages.
- CsFtFTPRelA -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObj -- This library provides functions to use FTP at a scheduled time by the User.
- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- EcCf -- The Config library (CF) is a static library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistry
- EcDcMsgPsngr -- This library consists of message passing objects used by both the client and server side.
- EcDnDir -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcFh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLoc -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcNsServiceLocator -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcPf -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPoDbRW
- EcPtSpecialLock -- This library provides classes for mutex operations and thread IDs.
- EcSeCmi -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeServerKeyMgmt -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbed -- This static Library is the stubbed version of EcSeSybSecurity.
- EcSeUtilityDbStubbed -- This static Library is stub version of the EcSeUtilityDb library.
- EcTiTime -- This library is used to obtain the current time in various formats, and manipulate the time.

- EcUr -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUt -- EcUt is a utility library for all the ECS applications.
- EcUtFactory -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtGUIg_mt_eh_tp
- EcUtHelpg_mt_eh_tp
- event -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- MsAcClnt -- The Accountability Management Service makes the user profile available to the various subsystems, such as the Data Server subsystem, information such as the user's electronic mail address and the shipping address, which are used for the distribution of
- MsAcComm -- This library contains class used for both Accountability Server and Client

process EcMsAcOrderGUI

/ecs/formal/MSS/MCI/Ac/src/EcAcOrderUI

This graphical user interface enables the user to retrieve the order and request from the Accountability database. The following functions are available:

1. Retrieve order and request by order id or request id.
2. Retrieve order and request by user name.
3. Retrieval can be filtered by order and request status.

Libraries Linked

- agentevent -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsFtFTPRelA -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObj -- This library provides functions to use FTP at a scheduled time by the User.
- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- EcCf -- The Config library (CF) is a static library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistry
- EcDcMsgPsgn1 -- This library consists of message passing objects used by both the client and server side.
- EcDnDir -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcFh -- This library provides fault handling capabilities to ECS applications.

- EcNsServiceLoc -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcNsServiceLocator -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcPf -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPoDbRW
- EcPtSpecialLock -- This library provides classes for mutex operations and thread IDs.
- EcSeCmi -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeServerKeyMgmt -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbed -- This static Library is the stubbed version of EcSeSybSecurity.
- EcSeUtilityDbStubbed -- This static Library is stub version of the EcSeUtilityDb library.
- EcTiTime -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUr -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUt -- EcUt is a utility library for all the ECS applications.
- EcUtFactory -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtGUIg_mt_eh_tp
- EcUtHelpg_mt_eh_tp
- event -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- MsAcClnt -- The Accountability Management Service makes the user profile available to the various subsystems, such as the Data Server subsystem, information such as the user's electronic mail address and the shipping address, which are used for the distribution of
- MsAcComm -- This library contains class used for both Accountability Server and Client

process EcMsAcOrderSrvr

/ecs/formal/MSS/MCI/Ac/src

The Order Tracking Server provides an external interface to other CSCIs/CSCs. The functions are:

1. Insert, delete, update, retrieve order
2. Insert, delete, update, retrieve request
3. Retrieve a list of orders
4. Retrieve a list of requests
5. Update order status

6. Update request status

The EcMsAcOrderSrvr supports:

- * Single requests at a time
- * Multiple concurrent requests
- * Asynchronous request processing
- * Request processing de-coupled from an RPC thread
- * Multiple threads within a single request

Libraries Linked

- agentevent -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsEmMailRelA -- This Library is used for the emails using sendmail utility and the nnpst for Bulletin board messages.
- CsFtFTPRelA -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObj -- This library provides functions to use FTP at a scheduled time by the User.
- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- EcCf -- The Config library (CF) is a static library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistry
- EcDcMsgPsnl -- This library consists of message passing objects used by both the client and server side.
- EcDnDir -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcFh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLoc -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcNsServiceLocator -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcPf -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPoDbRW
- EcPtSpecialLock -- This library provides classes for mutex operations and thread IDs.
- ECSEAuthn
- EcSeCmi -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).

- EcSeServerKeyMgmt -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbed -- This static Library is the stubbed version of EcSeSybSecurity.
- EcSeUtilityDbStubbed -- This static Library is stub version of the EcSeUtilityDb library.
- EcTiTime -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUr -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUt -- EcUt is a utility library for all the ECS applications.
- EcUtFactory -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- event -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- MD5Encrypt

process EcMsAcRegUserSrvr

/ecs/formal/MSS/MCI/Ac/src

User registration server provides the operators the capability to create ECS user accounts against requests submitted by guest users wishing to become authorized ECS users. The registration service provides the capabilities for the creation, modification and maintenance of accounts with user profiles. The user profile replicated to all DAAC. Other DAAC capable to browse foreign user profile, but only capable to modify user profile belongs to the local DAAC. The Accountability Management Service makes the user profile available to the various subsystems, such as the Data Server subsystem, information such as the user's electronic mail address and the shipping address, which are used for the distribution of data products ordered.

Libraries Linked

- agentevent -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsEmMailRelA -- This Library is used for the emails using sendmail utility and the nnpst for Bulletin board messages.
- CsFtFTPRelA -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObj -- This library provides functions to use FTP at a scheduled time by the User.
- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- EcCf -- The Config library (CF) is a static library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistry

- EcDcMsgPsnng1 -- This library consists of message passing objects used by both the client and server side.
- EcDnDir -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcFh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLoc -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcNsServiceLocator -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcPf -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPoDbRW
- EcPtSpecialLock -- This library provides classes for mutex operations and thread IDs.
- ECSAuthn
- EcSeCmi -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeServerKeyMgmt -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbed -- This static Library is the stubbed version of EcSeSybSecurity.
- EcSeUtilityDbStubbed -- This static Library is stub version of the EcSeUtilityDb library.
- EcTiTime -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUr -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUt -- EcUt is a utility library for all the ECS applications.
- EcUtFactory -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- event -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- MD5Encrypt

process EcMsAcSMCRegUserGUI

/ecs/formal/MSS/MCI/Ac/src/MsAcSMCRegUserGUI

Classes

- EcAcTabState -- Create one instance of this for each tab in a tabstack.
- MsAcErrorMsgBox -- Created by Builder Xcessory Version 5.0.3.
- MsAcErrorMsgBoxDerived

- MsAcInfoMsgBox -- Created by Builder Xcessory Version 5.0.3.
- MsAcInformation
- MsAcInformationDerived
- MsAcManageExistingAccntMW
- MsAcManageExistingAccntMWDerived -- This class does all the operations that needs to manage the existing accounts.
- MsAcProcessAccntReqMW
- MsAcProcessAccntReqMWDerived -- This class does all the operations that needs to process an request account.
- MsAcRegUsrUtl -- The MsAcRegUsrUtl class is a set of static functions of general utility to the Regsiter User GUI.
- MsAcUserAccountMngmtMW
- MsAcUserAccountMngmtMWDerived -- This class represents the main window.
- MsAcViewProfileDialog
- MsAcViewProfileDialogDerived
- UIComponent -- Base class for all C++/Motif UI components.

Libraries Linked

- agentevent -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsEmMailRelA -- This Library is used for the emails using sendmail utility and the nnpst for Bulletin board messages.
- CsFtFTPRelA -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObj -- This library provides functions to use FTP at a scheduled time by the User.
- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- EcCf -- The Config library (CF) is a static library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistry
- EcDcMsgPsgn1 -- This library consists of message passing objects used by both the client and server side.
- EcDnDir -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcFh -- This library provides fault handling capabilities to ECS applications.

- EcNsServiceLoc -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcNsServiceLocator -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcPf -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPoDbRW
- EcPtSpecialLock -- This library provides classes for mutex operations and thread IDs.
- EcSeCmi -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeServerKeyMgmt -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbed -- This static Library is the stubbed version of EcSeSybSecurity.
- EcSeUtilityDbStubbed -- This static Library is stub version of the EcSeUtilityDb library.
- EcTiTime -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUr -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUt -- EcUt is a utility library for all the ECS applications.
- EcUtFactory -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- EcUtGUIg_mt_eh_tp
- EcUtHelpg_mt_eh_tp
- event -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- MsAcClnt -- The Accountability Management Service makes the user profile available to the various subsystems, such as the Data Server subsystem, information such as the user's electronic mail address and the shipping address, which are used for the distribution of
- MsAcComm -- This library contains class used for both Accountability Server and Client

process EcMsAgGenProxy

/ecs/formal/MSS/MACI/src

The Proxy agent is provided by the Management Agent Services for the purposes of managing non-SNMP manageable COTS products. Its front-end has the MSS instrumentation code to communicate with the subagent. Its back-end communicates with the COTS.

Libraries Linked

- agentevent -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.

- CsFtFTPRelA -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObj -- This library provides functions to use FTP at a scheduled time by the User.
- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- EcCf -- The Config library (CF) is a static library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistry
- EcDcMsgPsngr -- This library consists of message passing objects used by both the client and server side.
- EcDnDir -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcFh -- This library provides fault handling capabilities to ECS applications.
- EcMsAgDeputyClient
- EcNsServiceLoc -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcNsServiceLocator -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcPf -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPoDbRW
- EcPtSpecialLock -- This library provides classes for mutex operations and thread IDs.
- EcSeCmi -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeServerKeyMgmt -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbed -- This static Library is the stubbed version of EcSeSybSecurity.
- EcSeUtilityCtStubbed -- This static Library is stub version of the EcSeUtilityCt library.
- EcSeUtilityDbStubbed -- This static Library is stub version of the EcSeUtilityDb library.
- EcTiTime -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUr -- A Universal Reference (UR) is created as a logical reference to an extant ECS object.
- EcUt -- EcUt is a utility library for all the ECS applications.
- EcUtFactory -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.

- event -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.

process EcMsAgSubAgent

/ecs/formal/MSS/MACI/src

The subagent is used to monitor and control ECS custom and COTS applications running on its host. The ECS subagent communicates management requests and responses from the master agent and the Deputy agent to either an ECS developed application or to a COTS application via the Proxy Agent. It supports the MIB extensions and performs local polling on the resources on the host. The subagent is custom developed code that uses some COTS libraries such as PEER tools to make itself remotely manageable.

Classes

- MsAgSubAgent -- MsAgSubAgent is a container class which instantiates an event manager, a monitor, a table manager, a subagent config, a deputy gate, a port monitor, and a discoverer class.

Libraries Linked

- agentevent -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsFtFTPRelA -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObj -- This library provides functions to use FTP at a scheduled time by the User.
- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- EcCf -- The Config library (CF) is a static library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistry
- EcDcMsgPsgng1 -- This library consists of message passing objects used by both the client and server side.
- EcDnDir -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcFh -- This library provides fault handling capabilities to ECS applications.
- EcMsAgDeputyClient
- EcNsServiceLoc -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcNsServiceLocator -- The Service Locator library provides an implementation independent mechanism for specifying service locations.

- EcPf -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPoDbRW
- EcPtSpecialLock -- This library provides classes for mutex operations and thread IDs.
- EcSeCmi -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeServerKeyMgmt -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbed -- This static Library is the stubbed version of EcSeSybSecurity.
- EcSeUtilityCtStubbed -- This static Library is stub version of the EcSeUtilityCt library.
- EcSeUtilityDbStubbed -- This static Library is stub version of the EcSeUtilityDb library.
- EcTiTime -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUr -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUt -- EcUt is a utility library for all the ECS applications.
- EcUtFactory -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- event -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.

process MsCsSurveyMgrServer

/ecs/formal/MSS/MCI/Cs/src

The MsAcSuveyClientMain is a common survey server that used to tranfer data between the common survey database and client, including create, retrieve and update functionality for CLS subsystem.

Libraries Linked

- agentevent -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.
- CsFtFTPReIA -- This library provides a Wrapper for FTP.
- CsFtFTPSchedObj -- This library provides functions to use FTP at a scheduled time by the User.
- EcAgInstrm -- This library contains the instrumentation code which is linked into all ECS managed servers.
- EcCf -- The Config library (CF) is a static library provides the necessary software for the PF_Client & the PF_Server applications define their own set of configuration related information in a single location and retrieve them at the application startup.
- EcCsRegistry

- EcDcMsgPsngr1 -- This library consists of message passing objects used by both the client and server side.
- EcDnDir -- This provides classes to manipulate CDS entries, and operations on their attributes using XDS APIs.
- EcFh -- This library provides fault handling capabilities to ECS applications.
- EcNsServiceLoc -- This library contains both the client and server side APIs to allow servers to advertise their services and to allow clients to locate the servers.
- EcNsServiceLocator -- The Service Locator library provides an implementation independent mechanism for specifying service locations.
- EcPf -- This library provides flexible mechanism for ECS client and server applications to transparently include ECS infrastructure features from a library of services.
- EcPoDbRW
- EcPtSpecialLock -- This library provides classes for mutex operations and thread IDs.
- EcSeCmi -- Cryptographic Management Interface (CMI) provides a means for processes to obtain randomized passwords with which to gain access to non-DCE services (e.g., Sybase).
- EcSeServerKeyMgmt -- This library provides a mechanism for servers to read their DCE login key from a keytab file.
- EcSeSybSecurityStubbed -- This static Library is the stubbed version of EcSeSybSecurity.
- EcSeUtilityDbStubbed -- This static Library is stub version of the EcSeUtilityDb library.
- EcTiTime -- This library is used to obtain the current time in various formats, and manipulate the time.
- EcUr -- A Universal Reference (UR) is created as a logical reference to a extant ECS object.
- EcUt -- EcUt is a utility library for all the ECS applications.
- EcUtFactory -- The EcUtFactory should be used when you dynamically create objects based on the a class identifier.
- event -- Purpose of this library is to provide a framework for MSS Agent to store information to the MSS log file and rename the file when the file is full.